



## ISO 19453-6

# Road vehicles — Environmental conditions and testing for electrical and electronic equipment for drive system of electric propulsion vehicles —

## Part 6: Traction battery packs and systems

*Véhicules routiers — Spécifications d'environnement et essais de l'équipement électrique et électronique pour les véhicules à propulsion électrique —*

*Partie 6: Packs et systèmes de batterie de traction*

Second edition  
2026-09

This is a preview of ISO 19453-6:2026. Click [here](#) to purchase the full version from the ANSI store.



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2026

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

This is a preview of ISO 19453-6:2026. [Click here to purchase the full version from the ANSI store.](#)

|                                                                           |           |
|---------------------------------------------------------------------------|-----------|
| <b>Foreword</b>                                                           | <b>v</b>  |
| <b>Introduction</b>                                                       | <b>vi</b> |
| <b>1 Scope</b>                                                            | <b>1</b>  |
| <b>2 Normative references</b>                                             | <b>1</b>  |
| <b>3 Terms and definitions</b>                                            | <b>2</b>  |
| <b>4 Symbols and abbreviated terms</b>                                    | <b>3</b>  |
| 4.1 Symbols                                                               | 3         |
| 4.2 Abbreviated terms                                                     | 4         |
| <b>5 Operating modes</b>                                                  | <b>4</b>  |
| 5.1 General                                                               | 4         |
| 5.2 Operating mode 5                                                      | 5         |
| 5.3 Operating mode 6                                                      | 5         |
| 5.4 Operating mode 7                                                      | 6         |
| <b>6 Functional status classification</b>                                 | <b>6</b>  |
| <b>7 Functional status checks</b>                                         | <b>6</b>  |
| 7.1 Electrical requirements check                                         | 6         |
| 7.1.1 General                                                             | 6         |
| 7.1.2 Equipotential bonding                                               | 6         |
| 7.1.3 Isolation resistance test                                           | 7         |
| 7.1.4 Withstand voltage test                                              | 7         |
| 7.2 Mechanical requirements check                                         | 7         |
| 7.2.1 Technical tightness check of battery pack or system enclosure       | 7         |
| 7.2.2 Leak tightness check of internal temperature control system         | 7         |
| <b>8 Tests and requirements</b>                                           | <b>8</b>  |
| 8.1 Mechanical categories of battery packs or systems                     | 8         |
| 8.1.1 General                                                             | 8         |
| 8.1.2 Category 1                                                          | 8         |
| 8.1.3 Category 2                                                          | 9         |
| 8.1.4 Category 3                                                          | 9         |
| 8.2 Pre-conditioning                                                      | 9         |
| 8.2.1 General                                                             | 9         |
| 8.2.2 Thermo-mechanical pre-conditioning                                  | 10        |
| 8.3 Thermal cycling tests                                                 | 10        |
| 8.3.1 General                                                             | 10        |
| 8.3.2 Thermal cycling for DUT without internal temperature control system | 11        |
| 8.3.3 Thermal cycling for DUT with internal temperature control system    | 12        |
| 8.3.4 Thermal cycling with electric operation                             | 13        |
| 8.4 Structural durability and strength tests                              | 16        |
| 8.4.1 General                                                             | 16        |
| 8.4.2 Fixture                                                             | 16        |
| 8.4.3 Pre-conditioning for mechanical tests                               | 16        |
| 8.4.4 Durability test                                                     | 16        |
| 8.4.5 Mechanical shock                                                    | 23        |
| 8.4.6 Requirements                                                        | 24        |
| 8.5 Water protection                                                      | 24        |
| 8.5.1 Test                                                                | 24        |
| 8.5.2 Requirements                                                        | 24        |
| 8.6 Dust protection                                                       | 24        |
| 8.6.1 Test                                                                | 24        |
| 8.6.2 Requirements                                                        | 25        |
| 8.7 Humid heat condensation test                                          | 25        |
| 8.7.1 Purpose                                                             | 25        |

This is a preview of ISO 19453-6:2026. [Click here to purchase the full version from the ANSI store.](#)

|                     |                                                                                                         |           |
|---------------------|---------------------------------------------------------------------------------------------------------|-----------|
| 8.8                 | Damp heat, steady state test .....                                                                      | 27        |
| 8.8.1               | Purpose .....                                                                                           | 27        |
| 8.8.2               | Test .....                                                                                              | 28        |
| 8.8.3               | Requirement .....                                                                                       | 28        |
| 8.9                 | Corrosion .....                                                                                         | 28        |
| 8.9.1               | General .....                                                                                           | 28        |
| 8.9.2               | Mixed gas corrosion .....                                                                               | 28        |
| 8.9.3               | Salt-spray test for external mounting location .....                                                    | 29        |
| 8.9.4               | Salt corrosion test for internal mounting location .....                                                | 30        |
| 8.10                | Chemical resistance .....                                                                               | 33        |
| <b>Annex A</b>      | <b>(informative) Example of leak tightness check .....</b>                                              | <b>34</b> |
| <b>Annex B</b>      | <b>(informative) Test concept for additional mechanical loads on a battery pack or system .....</b>     | <b>35</b> |
| <b>Annex C</b>      | <b>(informative) Example of electrical and thermal profile for the mechanical durability test .....</b> | <b>38</b> |
| <b>Annex D</b>      | <b>(informative) Example of electrical profile for heat dissipation .....</b>                           | <b>39</b> |
| <b>Annex E</b>      | <b>(informative) Example of acceptance criterion for corrosion infiltration .....</b>                   | <b>40</b> |
| <b>Bibliography</b> | <b>.....</b>                                                                                            | <b>42</b> |

This is a preview of ISO 19453-6:2026. Click here to purchase the full version from the ANSI store.

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at [www.iso.org/patents](http://www.iso.org/patents). ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 32, *Electrical and electronic components and general system aspects*.

This second edition cancels and replaces the first edition (ISO 19453-6:2020), which has been technically revised.

The main changes are as follows:

- relinking references to the withdrawn ISO 19453-1 to ISO 19453-5 with the corresponding sections after the merger of this series with the ISO 16750 (all parts) [I1](#) series.

A list of all parts in the ISO 16750 (all parts) [I1](#) series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

This is a preview of ISO 19453-6:2026. [Click here to purchase the full version from the ANSI store.](#)

For over fifty years, traction batteries for electric vehicles have been developed to achieve high energy density and high-power output. Specifically, lead-acid battery, Ni-Cd battery and Ni-MH battery with aqueous electrolyte were most applied to electric vehicles in the early days. Thermal activated batteries, such as molten salt batteries, like sodium sulfur battery, and Zebra battery, were also examined. Lithium-ion battery penetrated the consumer market in portable battery application from 1991. Currently, it is the most promising candidate of traction battery for electric vehicles. ISO 6469-1 [2] specifies safety requirement for rechargeable energy storage system (RESS), and the ISO 12405 (all parts) [3] series was published to specify performance and reliability tests. This document focuses on environmental and endurance tests of lithium-ion battery systems.

The ISO 16750 (all parts) [1] series specifies the test conditions on environment and reliability for electrical and electric equipment for road vehicles. For the 2023 edition of the ISO 16750 (all parts) [1] series, the corresponding parts of the ISO 19453 (all parts) [4] series were merged and reflected into their ISO 16750 (all parts) [1] counterparts. The battery pack or system is the electric system which charges and discharges electricity through the converter. The test condition for mechanical load in ISO 16750-3 [5] is too severe to apply to the battery pack or system from the standpoint of frequency range and amplitude of vibration in the test input spectrum. The test conditions for climatic load in ISO 16750-4 [6] are also excessive to apply to the battery pack or system, because the lithium-ion battery pack is designed to control temperature within an adequate operational range. That is the reason why appropriate conditions for the lithium-ion battery are specified in this document.

The purpose of this document is to assist its user in systematically defining, applying or both, a set of internationally accepted environmental conditions, tests and operating requirements, which are based on the anticipated actual environment in which the equipment will be operated and exposed to during its life cycle. This document has been developed based on fundamental investigations and vehicle measurements on voltage class A and B battery pack/system. The following environmental factors have been considered in the development:

- World geography and climate

Electric propulsion vehicles are operated in nearly all terrestrial regions of the earth. Significant variation in environmental conditions due to climatic environment, including diurnal and seasonal cycles, can therefore be expected. Consideration has been given to worldwide ranges in the temperature, humidity, precipitation and atmospheric conditions, including dust, pollution and altitude.

- Type of electric propulsion vehicle

Operating environment in an electric propulsion vehicle can depend on its electric powertrain architecture, as well as its mass, size, supply voltage and so on. Consideration has been given to typical types of series production electric propulsion vehicle architectures, such as hybrid electric vehicles, battery electric vehicles, range extender hybrid electric vehicles, and fuel cell vehicles, but not including equipment specific for fuel cell system.

- Vehicle use conditions and operating modes

Environmental conditions in and on the vehicle vary significantly with vehicle use (e.g. driving, charging during parking, etc.). Operating modes, such as starting, driving, braking, stopping and so on, have been considered, in particular, for traction battery system.

- Battery durability

For battery system, it is necessary to be resistant to environmental conditions experienced during manufacture, shipping, handling, storage, vehicle assembly, vehicle usage and vehicle maintenance and repair.

- Component mass and volume

The mass of battery pack is generally in the range of around 20 kg up to 60 kg for HEV, 80 kg to 150 kg for PHEV, and more than 200 kg for BEV (weight assumptions from the year 2020). The battery pack has

— Mounting location in the vehicle

HEV battery packs are generally installed inside the vehicle, PHEV battery packs are installed both outside and inside, and BEV battery packs are generally installed outside. The environmental condition, such as water splashing, dust, salt spray, humidity or corrosion for battery packs installed outside the vehicle interior is more severe than for battery packs installed inside. In this document, test conditions are specified according to mounting location.

a) Applicability to manufacturers' responsibility

Due to technology limitations or variations in vehicle design, the vehicle manufacturer may be required to place a component in a location where it cannot withstand the environmental conditions described in the ISO 16750 (all parts) [\[1\]](#) series. Under these circumstances, it is the responsibility of the vehicle manufacturer to provide the necessary environmental protection.

b) Applicability to wiring harnesses, cables and electrical connectors

Although some environmental conditions and tests in the ISO 16750 (all parts) [\[1\]](#) series may be relevant to vehicle wiring harnesses, cables and connectors, its scope is not sufficient to be used as a complete standard. It is, therefore, not recommended that the ISO 16750 (all parts) [\[1\]](#) series be directly applied to such devices and equipment.

c) Applicability to parts or assemblies inside the equipment

The ISO 16750 (all parts) [\[1\]](#) series describes environmental conditions and tests to be applied to electrical and electronic equipment directly mounted in or on the vehicle. It is not intended for direct application to parts or assemblies that are part of the equipment. For example, the ISO 16750 (all parts) [\[1\]](#) series should not be directly applied to integrated circuits (ICs) and discrete components, electrical connectors, printed circuit boards (PCBs), gauges, etc., that are attached in or on the equipment. Electrical, mechanical, climatic and chemical loads for such parts and assemblies can be quite different from those described in the ISO 16750 (all parts) [\[1\]](#) series.

On the other hand, it is desirable to use the ISO 16750 (all parts) [\[1\]](#) series to help derive environmental conditions and test requirements for parts and assemblies that are intended for use in road vehicle equipment. For example, a temperature range from  $-40\text{ }^{\circ}\text{C}$  to  $90\text{ }^{\circ}\text{C}$  may be specified for parts or assemblies contained inside a piece of equipment having a temperature range of  $-40\text{ }^{\circ}\text{C}$  to  $70\text{ }^{\circ}\text{C}$  and an additional temperature rise of 20 K.

d) Applicability relative to system integration and validation

The user of the ISO 16750 (all parts) [\[1\]](#) series is cautioned to understand that its scope is limited to conditions and testing at the equipment level and, therefore, does not represent all conditions and testing necessary for complete verification and validation of the vehicle system, for example, cold water shock tests were omitted from this document. Environmental and reliability testing of equipment parts and vehicle systems can be required. For example, the ISO 16750 (all parts) [\[1\]](#) series does not necessarily ensure that environmental and reliability requirements for solder joints, solderless connections, integrated circuits and so on are met. Such items are assured at the part, material or assembly level. Additionally, vehicle and system level testing might be required to validate the equipment in the vehicle application.