

This is a preview of "ISO 22199:2009". [Click here to purchase the full version from the ANSI store.](#)

Second edition
2009-12-15

Electromagnetic compatibility — Product family standard for lifts, escalators and moving walks — Emission

Compatibilité électromagnétique — Norme pour la famille de produits: ascenseurs, escaliers mécaniques et trottoirs roulants — Émission



Reference number
ISO 22199:2009(E)

© ISO 2009

This is a preview of "ISO 22199:2009". [Click here to purchase the full version from the ANSI store.](#)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

This is a preview of "ISO 22199:2009". [Click here to purchase the full version from the ANSI store.](#)

Contents

Page

Foreword	iv
Introduction.....	v
1 Scope	1
2 Normative references	1
3 Terms, definitions and abbreviated terms	2
3.1 Terms and definitions	2
3.2 Abbreviated terms	4
4 Test set-up procedure.....	4
4.1 General	4
4.2 Radiated and conducted radio frequency emissions	4
4.3 Mains supply harmonics	7
5 Applicability of tests	7
6 Emission limits	7
6.1 Enclosure ports — radiative.....	7
6.2 a.c. mains ports — conductive	7
6.3 Output power ports — conductive	7
6.4 Impulse noise.....	8
6.5 Voltage fluctuations	8
6.6 Mains supply current harmonics	8
6.7 Measurement	8
7 Documentation for the installer of the apparatus/assembly of apparatus.....	10
Bibliography.....	11

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 22199 was prepared by Technical Committee ISO/TC 178, *Lifts, escalators and moving walks*.

This second edition cancels and replaces the first edition (ISO 22199:2006), which has been technically revised.

This is a preview of "ISO 22199:2009". [Click here to purchase the full version from the ANSI store.](#)

Introduction

ISO 22199 is a type-C standard as stated in ISO 12100-1. When provisions of a type-C standard are different from those which are stated in type-A or type-B standards, the provisions of the type-C standard take precedence over the provisions of the other standards for machines that have been designed and built according to the provisions of the type-C standard.

This International Standard is based on European Standard EN 12015:2004.

EN 12015 specifies new requirements to control the emissions below 30 MHz of the drive to machine/motor connection and mains electricity supply harmonic emissions and voltage fluctuations. The previous edition of this International Standard addressed these requirements. However, as CISPR 11 and CISPR 14-1 have been revised since the publication of the previous edition of this International Standard, the technical requirements of this International Standard are also being revised.

The requirements of this International Standard have been specified so as to ensure a level of electromagnetic emission that causes minimal disturbance to other equipment. The levels, however, do not cover the following cases:

- a) where the probability of an occurrence likely to produce emissions in excess of those which are normally experienced is extremely low, e.g. the emergency stopping of a lift, escalator or passenger conveyor under a fault condition;
- b) where highly susceptible apparatus is used in the close proximity of the equipment covered by this International Standard, in which case further measures might have to be taken to
 - 1) reduce the electromagnetic emission to below the levels specified in this International Standard, or
 - 2) increase the immunity of the affected apparatus.

The emission limits given are on the basis that equipment of the product family range is installed both indoors and outdoors in all types of building, involves the switching of heavy currents and high inductive loads and, generally, is connected to a low-voltage system.

The following explains the rationale for the revision of this International Standard.

Harmonic emission requirements stated by EN 12015 were initially developed on limits defined by a draft version of IEC/TS 61000-3-4 and IEC 77A/169/CDV, which were at that time the only documents (technical reports) available for harmonic emission above 16 A, applicable to three-phase equipment.

In 2000, a harmonic emission standard was created to cover the range of equipment from 16 A to 75 A, namely IEC 61000-3-12. IEC/TS 61000-3-4 remains valid as a technical report for current above 75 A, but it has not been modified or converted into an International Standard, as required by IEC rules.

IEC 61000-3-12 states different limits compared to those stated by EN 12015, which consequently have become obsolete and not consistent with new harmonized limits. The modifications in this edition of this International Standard are the following.

- a) Important changes
 - 1) Requirements to control the emissions below 30 MHz of the drive to machine/motor connection are introduced. The emission limits are independent of the magnitude of the conducted current. Limits and test method are those given in CISPR 14-1. Regarding other ports, the radiated tests above 30 MHz cover the cable connections and there are no known problems below 30 MHz.

This is a preview of "ISO 22199:2009". [Click here to purchase the full version from the ANSI store.](#)

- 2) Requirements to control mains electricity supply harmonic emissions and voltage fluctuations are introduced.

NOTE The radiation measurements in Table 1 have been harmonized with CISPR 11.

- 3) The term "installation" has been changed to "system". This is because official interpretation defines fixed installations as not being covered by the conformity assessment requirements of the electromagnetic compatibility (EMC) Directive, which is valid for apparatus and systems. This International Standard is applicable to the apparatus and assembly of apparatus of lifts and escalators and assembly into systems.

b) Environmental issues

- 1) Lifts, escalators and moving walks are systems whose apparatus and assembly of apparatus are distributed (and some of which move) throughout the building. The definition in EMC terms of the use of the building (residential or industrial) cannot be predetermined or assumed to be fixed. Therefore, to cover requirements in all cases, no differentiation between environments has been made and a single set of limits has been maintained. This set of high-frequency limits is based on the industrial limits of IEC 61000-6-4 and is known to be above the usual limits for the residential environment. This is justified by the experience that systems in compliance with this International Standard have not been known to cause EMC interference with regard to mains and radiated emissions above 30 MHz.
- 2) Regarding conducted limits, these are also based on the fact that the supply cabling is separated from other building supplies at least up to the point of common coupling (PCC). Additionally, system wiring is segregated in accordance with the manufacturer's specifications.
- 3) Concerning radiated emission limits above 30 MHz, the lift, escalator or moving walk area is separated, to a large extent, from domestic appliances.
- 4) All the limits used take into account that systems have to comply with the safety protection requirements regarding earth leakage currents. The application of more stringent limits than have been shown to be adequate would require the use of larger filters (both inductance and capacitance). The use of these will increase the susceptibility of the system to low electricity mains supply conditions and increase earth leakage currents. There is also an increase in power dissipation in the filter, causing (in the general case) increased energy consumption, additional ventilation and cooling requirements for the building. This is especially valid for higher duty systems:

- limits for 5th, 7th harmonic are higher in IEC 61000-3-12:2004, Table 3;
- limits for 11th, 13th harmonic are higher in EN 12015;
- limits for total harmonic distortion (THD) are higher in IEC 61000-3-12:2004, Table 3;
- limits for partial weighted harmonic distortion (PWHD) are higher in IEC 61000-3-12:2004, Table 3;
- no more limits for even harmonics above 12th order because the overall distortion is taken into account in THD and PWHD values in IEC 61000-3-12:2004, Table 3;
- no more limits for odd harmonic orders because the overall distortion is taken into account in THD and PWHD values in IEC 61000-3-12:2004, Table 3;
- no more limits for individual harmonic currents below 1 % in IEC 61000-3-12:2004, 4.2;
- limits for short duration referred to harmonic for the first 10 s during switching on or off are not taken into account in IEC 61000-3-12:2004, 4.2.3.

This is a preview of "ISO 22199:2009". [Click here to purchase the full version from the ANSI store.](#)

- 5) Harmonic limits in EN 12015 are referred to a short-circuit power, $R_{sce} = 250$, which was taken as an average value for lift, escalator and moving walk application (see EN 12015:2004, 4.3); for this reason, harmonic limits should be compared with values referred to $R_{sce} = 250$ in IEC 61000-3-12.
- 6) Elevator, escalator and moving walk are considered to be a three-phase balanced system when operating at rated current; for this reason, Table 3 of IEC 61000-3-12:2004 should be considered.
- 7) The limits given in this International Standard recognize that the product family covers a total range of lifts, escalators and moving walks used in residential buildings, offices, hospitals, hotels, industrial plants, etc. and that lifts, escalators and passenger conveyors are deemed to have their own dedicated power supply and be connected with the consent of the supply authority to a low impedance source.

The related EMC product family standard for immunity is ISO 22200.