First edition 2012-09-15

# Geotechnical investigation and testing — Field testing —

Part 1: Electrical cone and piezocone penetration test

Reconnaissance et essais géotechniques — Essais en place — Partie 1: Essais de pénétration au cône électrique et au piézocône



Reference number ISO 22476-1:2012(E)

## ISO 22476-1:2012(E)

This is a preview of "ISO 22476-1:2012". Click here to purchase the full version from the ANSI store.



## **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents	Page

Forewordv		
Introductionvi		
1	Scope	.1
2	Normative references	.2
3	Terms, definitions and symbols	
3.1 3.2	Terms and definitions	
4	Equipment	
4.1	Cone penetrometer	10
4.2	Tolerances	
4.3 4.4	Surface roughness  Cone	
4.4 4.5	Friction sleeve	
4.6	Filter element	
4.7	Gaps and soil seals	
4.8	Push rods	
4.9 4.10	Measuring system  Thrust machine	
_		
5	Test procedures	
5.1 5.2	Selection of cone penetrometerSelection of equipment and procedures	
5.3	Position and level of thrust machine	
5.4	Preparation of the test	
5.5	Pushing of the cone penetrometer	
5.6 5.7	Use of friction reducer  Frequency of logging parameters	
5. <i>7</i> 5.8	Registration of penetration length	
5.9	Dissipation test	
5.10	Test completion	21
5.11	Equipment checks and calibrations	
5.12	Safety requirements	
6	Test results	
6.1 6.2	Measured parameters	
6.2 6.3	Correction of parameters	
-	·	
7 7.1	ReportingGeneral	
7.2	Reporting of test results	
7.3	Presentation of test results	26
7.4	Presentation of test results and calculated parameters	26
Annex	A (normative) Maintenance, checks and calibration	28
Annex	B (normative) Calculation of penetration depth	32
Annex	C (informative) Correction of sleeve friction for water pressure	33
Annex	D (informative) Preparation of the piezocone	34
Annex	E (informative) Uncertainties in cone penetrometer testing	35

# ISO 22476-1:2012(E)

This is a preview of "ISO 22476-1:2012". Click here to purchase the full version from the ANSI store.

Bibliography	36
Figures	
Figure 1 — Cross section of an example of a cone penetrometer	3
Figure 2 — Locations of pore pressure filters	6
Figure 3 — Penetration length and penetration depth (schematic only)	8
Figure 4 — Tolerance requirements for use of 1000 mm <sup>2</sup> cone penetrometer	12
Figure 5 — Geometry and tolerances of friction sleeve	13
Figure 6 — Correction of cone resistance and sleeve friction due to the unequal end area effect	23
Figure A.1 — Pressure chamber for determination of the net area ratio, a	30
Tables	
Table 1 — Types of cone penetration test	17
Table 2 — Application classes	18
Table A 1 — Control scheme for maintenance routines	29

#### **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 22476-1 was prepared by the European Committee for Standardization (CEN) Technical Committee CEN/TC 341, *Geotechnical investigation and testing*, in collaboration with Technical Committee ISO/TC 182, *Geotechnics*, Subcommittee SC 1, *Geotechnical investigation and testing*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

ISO 22476 consists of the following parts, under the general title *Geotechnical investigation and testing*— *Field testing*:

- Part 1: Electrical cone and piezocone penetration test
- Part 2: Dynamic probing
- Part 3: Standard penetration test
- Part 4: Ménard pressuremeter test
- Part 5: Flexible dilatometer test
- Part 7: Borehole jack test
- Part 9: Field vane test
- Part 10: Weight sounding test [Technical Specification]
- Part 11: Flat dilatometer test [Technical Specification]
- Part 12: Mechanical cone penetration test (CPTM)

# Introduction

The electrical cone penetration test (CPT) consists of pushing a cone penetrometer using a series of push rods into the soil at a constant rate of penetration. During penetration, measurements of cone resistance and sleeve friction are recorded. The piezocone penetration test (CPTU) also includes the measurement of pore pressures around the cone. The test results can be used for interpretation of stratification, classification of soil type and evaluation of engineering soil parameters. Two International Standards define cone penetration tests: ISO 22476-1 defines CPT and CPTU practice using electronic transducers; ISO 22476-12 defines CPT practice using mechanical measuring systems.

"Cone resistance" is the term used in practice and in this part of ISO 22476, although "cone penetration resistance" is a more correct description of the process.

The test results of this part of ISO 22476 are specially suited for the qualitative and/or quantitative determination of a soil profile together with direct investigations (e.g. sampling according to ISO 22475-1 [2]) or as a relative comparison of other *in situ* tests.

The results from a cone penetration test are used to evaluate:

—	stratification;
_	soil type;
	geotechnical parameters such as
	<ul><li>soil density,</li></ul>
	<ul> <li>shear strength parameters, and</li> </ul>
	<ul> <li>deformation and consolidation characteristics.</li> </ul>