First edition 2021-06

Plastics piping systems for pressure and non-pressure water supply, drainage or sewerage — Glassreinforced thermosetting plastics (GRP) systems based on unsaturated polyester (UP) resin

Systèmes de canalisations en matières plastiques pour l'alimentation en eau, les branchements et les collecteurs d'assainissement avec ou sans pression — Systèmes en plastiques thermodurcissables renforcés de verre (PRV) à base de résine de polyester non saturé (UP)



ISO 23856:2021(E)

This is a preview of "ISO 23856:2021". Click here to purchase the full version from the ANSI store.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Contents				
Fore	eword			v
1				
_	-			
2			ces	
3	Terms and definitions			
4	General			
	4.1		1	
			gories	12
			ninal size	
			ninal stiffness	
	4.0		ninal pressure	
	4.2		1	
			eral Iforcement	
		_	n	
			regates and fillers	
		00	rmoplastics liners	
			tomers	
		4.2.7 Meta	als	14
	4.3	Wall construction		14
			er layer	14
			ctural layer	
			er layer	
	4.4			
	4.5		nditions for testing	
			perature	
			perties of water for testingding conditions	
			ditioning	
			surement of dimensions	
	4.6 Elapsed time, <i>x</i> , for determination of long-term properties			
	4.7	Joints		
			eral	
		4.7.2 Type	es of joint	16
		4.7.3 Flex	ibility of the joint	16
			ing ring	
			esives	
		4.8 Effect on water quality		
	4.9	Assessment	of conformity	1/
5	Pipe	Pipes		
	5.1	Type of pipes		
	5.2	Geometrical characteristics		
			neter	
			l thickness	
	E 2	,	gth	
	5.3		characteristicsal ring stiffnessal	
			g-term creep ring stiffness	
			al resistance to failure in a deflected condition	
			mate long-term resistance to failure in a deflected condition	
			al longitudinal tensile strength	
			al design and failure pressures for pressure pipes	

iii

		5.3.7 Long-term failure pressure	32			
	5.4	Resistance to chemical attack				
		5.4.1 General				
		5.4.2 Procedure using failure points				
		5.4.3 Procedure using specified levels of strain				
		5.4.4 Test piece length				
		5.4.5 Test solution				
	5.5	Marking	35			
6	Fitti	ngs	36			
	6.1					
		6.1.1 General	36			
		6.1.2 Diameter series	36			
		6.1.3 Nominal pressure (PN)				
		6.1.4 Nominal stiffness (SN)				
		6.1.5 Fitting type				
		6.1.6 Mechanical characteristics of fittings				
		6.1.7 Installed leaktightness of fittings				
		6.1.8 Dimensions				
	6.2	Bends				
		6.2.1 Classification of bends				
	()					
	6.3	Branches 6.3.1 Classification of branches 6.3.1				
		6.3.1 Classification of branches 6.3.2 Dimensions and tolerances of branches				
	6.4	Reducers				
	0.4	6.4.1 Classification of reducers				
		6.4.2 Dimensions and tolerances of reducers				
	6.5	Non-pressure saddles				
	0.5	6.5.1 Classification of saddles				
		6.5.2 Dimensions of saddles and associated tolerances				
	6.6	Flanges				
		6.6.1 Classification of flanges				
		6.6.2 Dimensions and tolerances for adaptors				
	6.7	Marking				
7	Loint	Joints				
,	7.1	General				
	7.1	7.1.1 Interchangeability				
		7.1.2 Requirements				
		7.1.3 Test temperature				
		7.1.4 Non-pressure joints				
		7.1.5 Dimensions				
	7.2	Flexible joints				
		7.2.1 General				
		7.2.2 Maximum allowable draw	51			
		7.2.3 Maximum allowable angular deflection	51			
		7.2.4 Flexible non-end-load-bearing joints with elastomeric sealing rings	51			
		7.2.5 Flexible end-load-bearing joints with elastomeric sealing rings	52			
	7.3	Rigid joints				
		7.3.1 Wrapped or cemented				
		7.3.2 Bolted flange joints				
	7.4	Marking	54			
Anne		ormative) Principles used to establish the design requirements based on				
	regre	ession testing and consideration of the variability of the product	55			
Bibli	ograph	ıy	60			

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 138, *Plastics pipes, fittings and valves for the transport of fluids*, Subcommittee SC 6, *Reinforced plastics pipes and fittings for all applications*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 155, *Plastics piping systems and ducting systems*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This first edition cancels and replaces ISO 10639:2017 (second edition) and ISO 10467:2018 (second edition), which have been technically revised.

The main changes compared to the previous editions are as follows:

- documents combined;
- editorial changes throughout.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document has been produced by merging ISO 10639, ISO 10467, EN 1796 and EN 14364. As these standards were almost identical, apart from the requirements for chemical resistance of sewer pipes on the one hand, and no negative impact on water quality of drinking water pipes on the other hand, it was decided that it would be beneficial for users to be able to refer to a single document, irrespective of application or region.

The content of this document is summarized as follows:

<u>Clause 4</u> specifies the general aspects of GRP UP piping systems.

<u>Clause 5</u> specifies the characteristics of pipes made from GRP UP with or without aggregates and/or fillers. The pipes can have a thermoplastics or thermosetting resin liner. <u>Clause 5</u> also specifies the test parameters for the test methods referred to in this document. For pipes intended for sewer applications, the resistance to chemical attack is stated in <u>5.4</u>. For other applications, the requirements in <u>5.3.4</u> apply.

<u>Clause 6</u> specifies the characteristics of fittings made from GRP UP, with or without a thermoplastics or thermosetting resin liner. <u>Clause 6</u> specifies the dimensional and performance requirements for bends, branches, reducers, saddles and flanged adaptors. <u>Clause 6</u> covers requirements to prove the structural design of fittings. It is applicable to fittings made using any of the following techniques:

- fabrication from straight pipes;
- moulding by
 - 1) filament winding,
 - 2) tape winding,
 - 3) contact moulding, and
 - 4) hot or cold compression moulding.

<u>Clause 7</u> is applicable to joints to be used in the GRP UP piping systems, both buried and non-buried. It covers requirements to prove the design of the joint. <u>Clause 7</u> specifies type test performance requirements for the following joints as a function of the declared nominal pressure rating of the pipeline or system:

- a) socket-and-spigot (including double-socket) joints or mechanical joints;
- b) locked socket-and-spigot joints;
- c) cemented or wrapped joints;
- d) bolted flange joints.