

This is a preview of "ISO 25377:2020". [Click here to purchase the full version from the ANSI store.](#)

First edition
2020-12

Hydrometric uncertainty guidance (HUG)

Lignes directrices relatives à l'incertitude en hydrométrie



Reference number
ISO 25377:2020(E)

© ISO 2020

This is a preview of "ISO 25377:2020". [Click here to purchase the full version from the ANSI store.](#)



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

This is a preview of "ISO 25377:2020". Click here to purchase the full version from the ANSI store.

Contents

	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols	1
5 ISO/IEC Guide 98-3 (GUM) — Basic definitions and rules	3
5.1 General	3
5.2 Uncertainty of sets of measurements	3
5.3 Random and systematic effects	4
5.4 Uncertainty models — Probability distributions	5
5.5 Combining uncertainties — Law of propagation of uncertainties	5
5.6 Expressing results	6
6 Open channel flow — Velocity area methods	6
6.1 General	6
6.2 Mean velocity, \bar{V}_x	7
6.3 Velocity-area method for discharge calculation	8
6.4 Measurement of velocity	9
6.5 Uncertainty associated with the velocity-area method	9
6.5.1 General	9
6.5.2 Random and systematic effects	11
6.6 Integration uncertainties $[u^*(F_y), u^*(F_z)]$	11
6.6.1 General	11
6.6.2 Vertical scanning uncertainties	11
6.6.3 Horizontal scanning uncertainties	12
6.7 Perimeter flow uncertainties, $u(Q_p)$	12
7 Open channel flow — Critical depth methods	13
7.1 General	13
7.2 Head and geometry determination	13
7.3 Iterative calculation	14
7.4 Evaluating uncertainty	14
8 Dilution methods	15
8.1 General	15
8.2 Continuous feed	15
8.3 Transient mass	17
9 Hydrometric instrumentation	18
9.1 Performance specifications	18
9.2 Validity of uncertainty statements	18
9.3 Manufacturer's specifications	19
9.4 Performance guide for hydrometric equipment for use in technical standard examples	20
10 Guide for the drafting of uncertainty clauses in hydrometric standards	21
10.1 General	21
10.2 Equipment, methods and measurement systems	21
10.2.1 General	21
10.2.2 Equipment	21
10.2.3 Methods	21
10.2.4 Systems	22

This is a preview of "ISO 25377:2020". [Click here to purchase the full version from the ANSI store.](#)

11	Examples	22
11.1	General.....	22
11.2	Uncertainty in water level measurement.....	22
11.2.1	Example 1: Float/shaft encoder sensor installed in stilling well at gauging station.....	22
11.2.2	Example 2: Pressure transmitter installed in tube.....	23
11.3	Uncertainty in flow measurement using flow measurement structures.....	23
11.4	Uncertainty in flow measurement by current meter.....	26
Annex A (informative)	Introduction to hydrometric uncertainty	31
Annex B (informative)	Introduction to Monte Carlo Simulation (MCS)	48
Annex C (informative)	Interpolated Variance Estimation (IVE) method	53
Annex D (informative)	Performance guide for hydrometric equipment for use in technical standard examples	57
Annex E (informative)	Uncertainty analysis of stage-discharge relation	60
Annex F (informative)	Measurement of velocity	64
Bibliography	69

This is a preview of "ISO 25377:2020". [Click here to purchase the full version from the ANSI store.](#)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 113, *Hydrometry*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The management of a natural environment requires knowledge, by measurement, of what is happening. Only then can effective action be taken and the effectiveness of the action assessed. Much depends on the quality of the knowledge itself.

The quality of measurable knowledge is stated in terms of measurement uncertainty. The internationally agreed method for assessing measurement quality is the guide to the estimation of uncertainty in measurement (GUM). Without this uniformity of measurement standards, equitable sharing of the environment is not possible and international obligations to care for the environment would be weakened.

The essential purpose of the GUM is for a statement of the quality of a measurement result to be presented with all measurements described in technical standards. Without this, no two measurements can be compared, or standards set. Whereas the GUM is a reference document serving the universal requirements of metrology, the Hydrometric uncertainty guidance (HUG) document is specific to hydrometry, i.e. to the measurement of the components of the hydrological cycle. It borrows from the GUM the methods that are the most applicable to hydrometry and applies them to techniques and equipment used in hydrometry.

In the past, error analysis has provided an indication of measurement quality, but such statements cannot properly convey the quality of the result because it presupposes knowledge of a true, error-free, value against which the measured result can be compared. The true value can never be known and uncertainty remains. For this reason, the GUM uses the concept of uncertainty and uses it for all stages and components of the measurement process. This ensures consistency.

The GUM defines standard uncertainty of a result as being equivalent to a standard deviation. This can be the standard deviation of a set of measured values or of probable values. This is broadly similar to the approach used in error analysis that preceded the uncertainty technique. However, the GUM provides additional methods of estimating uncertainty based on probability models. The two approaches are equivalent, but uncertainty requires only a knowledge or estimate of the dispersion of measurement about its mean value, and not the existence of a true value. It is assumed that a careful evaluation of the components of measurement uncertainty brings the mean value close to a probable true value, at least well within its margin of uncertainty.

In more general terms, uncertainty is a parameter that characterizes the dispersion of measurable values that can be attributed to their mean value.

By treating standard deviations and probability models as if they approximated to Gaussian (or normal) distributions, the GUM provides a formal methodology for combining components of uncertainty in measurement systems where several input variables combine to determine the result.

Within this formal framework, the GUM can be consistently applied to a range of applications and, thereby, be used to make meaningful comparisons of results.

The HUG seeks to promote an understanding of the nature of measurement uncertainty and its significance in estimating the 'quality' of a measurement or a determination in hydrometry.

Hydrometry is principally concerned with the determination of flow in rivers and man-made channels. This includes:

- environmental hydrometry, i.e. the determination of the flow of natural waters (largely concerned with hydrometric networks, water supply and flood protection);
- industrial hydrometry, i.e. the determination of flows within industrial plants and discharges into the natural environment (largely concerned with environment protection and also irrigation).

Both are the subject of international treaties and undertakings. For this reason, measured data is intended to conform to the GUM to assure that results can be compared.

This is a preview of "ISO 25377:2020". [Click here to purchase the full version from the ANSI store.](#)

Hydrometry is also concerned with the determination of rainfall, the movement/diffusion of groundwater and the transport by water flow of sediments and solids. This version of the HUG is concerned with flow determination only.

The results from hydrometry are used by other disciplines to regulate and manage the environment. If knowledge is required of biomass, sedimentary material, toxins, etc., the concentration of these components is determined and their uncertainty estimated. The uncertainty of mass-load can then be determined from the uncertainty of flow determination. The components of this calculation are made compatible through compliance with the GUM.

For practitioners of hydrometry and for engineers, the GUM is not a simple document to refer to. The document has been drafted to provide a legal framework for professional metrologists with a working knowledge of statistical methods and their mathematical representation. A helpful document, see Reference [2], is an abbreviated version of the GUM written to be more accessible to engineers and to specialists in fields other than metrology.

The HUG, although simplifying the concepts, in no way conflicts with the principles and methods of the GUM. Accordingly, the HUG interprets the GUM to apply its requirements to hydrometry in a practical way, and, hopefully, in a way accessible to engineers and those responsible for managing the environment.

In addition, the HUG introduces and develops the Monte Carlo Simulation, a complementary technique, which has benefits for hydrometry, inasmuch as complex measurement systems can be represented realistically.

The HUG summarizes basic hydrometric methods defined in various technical standards. The HUG develops uncertainty estimation formulae from the GUM for these basic methods. The basic hydrometric methods described in the HUG might not be identical to those recited in the published technical standards. In such cases, the methods described in these standards are to be taken as authoritative. However, clauses in technical standards that concern uncertainty should be adapted to be in accordance with the HUG.

NOTE 1 There is no unified definition of space coordinates within the hydrometric standards. The textbook conventional axes are adopted in this document when describing open channel flow: the x axis being horizontal and positive in the mean flow direction, the y axis being orthogonal to the x axis in the horizontal plane and the z axis being vertical positive.

NOTE 2 For a complete appreciation of the scope of definitions used in measurement uncertainty, the reader is referred to the GUM^[1] or to NIST Technical Note 1297^[2].