First edition 2009-07-15

Road vehicles — End-of-life activation of on-board pyrotechnic devices —

Part 5:

Additional communication line with pulse width modulated signal

Véhicules routiers — Activation de fin de vie des dispositifs pyrotechniques embarqués —

Partie 5: Ligne de communication additionnelle avec signal modulé par largeur d'impulsion



Reference number ISO 26021-5:2009(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org Published in Switzerland

Contents

Forewordiv		
Introdu	ntroductionv	
1	Scope	. 1
2	Normative references	. 1
3	Terms and definitions	. 1
4	Abbreviated terms	. 2
5	Conventions	. 2
6 6.1 6.2 6.3	Pyrotechnic device deployment via on-board diagnostic architecture Vehicle system description Example of in-vehicle hardware and software provision Additional communication line	. 2 . 2 . 3 . 3
7 7.1 7.2 7.3 7.4	ACL with PWM specification Hardware description PCU hardware compatibility to the L line Allowed supply voltage Signal description	4455
8 8.1 8.2	Deployment process with ACL line and PWM signal General information Deployment process description	8 8 8
9	Connections to the vehicle	14
Bibliog	ibliography1	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 26021-5 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 3, *Electrical and electronic equipment*.

ISO 26021 consists of the following parts, under the general title *Road vehicles* — *End-of-life activation of on-board pyrotechnic devices*:

- Part 1: General information and use case definitions
- Part 2: Communication requirements
- Part 3: Tool requirements
- Part 4: Additional communication line with bidirectional communication
- Part 5: Additional communication line with pulse width modulated signal

Introduction

Worldwide, nearly all new vehicles are equipped with one or more safety systems. This can include advanced protection systems based on pyrotechnic actuators. All components which contain pyrotechnic substances can be handled in the same way.

Recycling these vehicles demands a new process to ensure that the deactivation of airbags is safe and cost-efficient. Due to the harmonization of the on-board diagnostic (OBD) interface, there is a possibility of using it for on-board deployment, which is based on the same tools and processes.

Representatives of the global automobile industry agreed that automobile manufacturers

- do not support reuse as an appropriate treatment method for pyrotechnic devices,
- believe treatment of pyrotechnic devices is required before shredding, and
- support in-vehicle deployment as the preferred method.

Based on this agreement, the four big associations of automobile manufacturers (ACEA, Alliance, JAMA and KAMA) started to develop a method for the "in-vehicle deployment of pyrotechnic components in cars with the pyrotechnic device deployment tool (PDT)". The objective is that in the future a dismantler will use only one tool without any accessories to deploy all pyrotechnic devices inside an end-of-life vehicle (ELV) by using an existing interface to the car.

Because of different requirements and safety concepts an additional communication line (ACL) is added to the basic controller area network (CAN) communication method. In this part of ISO 26021 ACL is used to mean an additional communication line with pulse width modulated signal. This direct hardware (HW) connection is used for systems with a specific safing concept, to bypass it and then enable the deployment of such systems.