First edition 2010-12-15

Hand-held portable power tools — Test methods for evaluation of vibration emission —

Part 4: Straight grinders

Machines à moteur portatives — Méthodes d'essai pour l'évaluation de l'émission de vibrations —

Partie 4: Meuleuses droites



Reference number ISO 28927-4:2010(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Contents

Foreword	iv
Introduction	vi
1 Scope	1
2 Normative references	1
 3 Terms, definitions and symbols 3.1 Terms and definitions 3.2 Symbols 	2
4 Basic standards and vibration test codes	3
5 Description of the family of machines	3
 6 Characterization of vibration	4 4 5
 7 Instrumentation requirements	5 5 6 6 6
 8 Testing and operating conditions of the machinery	6 7 7
 9 Measurement procedure and validity 9.1 Reported vibration values 9.2 Declaration and verification of the vibration emission value 	10
10 Measurement report	11
Annex A (informative) Model test report for vibration emission of straight grinders	13
Annex B (normative) Determination of uncertainty	15
Annex C (normative) Design of test wheel	17
Bibliography	23

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 28927-4 was prepared by Technical Committee ISO/TC 118, Compressors and pneumatic tools, machines and equipment, Subcommittee SC 3, Pneumatic tools and machines.

This first edition of ISO 28927-4, together with ISO 28927-1, cancels and replaces ISO 8662-4:1994, of which it constitutes a technical revision. The most important changes are

- vibration measurement in three axes and at both hand positions;
- new transducer locations with improved definitions of the transducer positions and orientation are used;
- rotational speed is raised to no load free running speed;
- the test wheels are modified and the definition is improved.

ISO 28927 consists of the following parts, under the general title Hand-held portable power tools — Test methods for evaluation of vibration emission:

- Part 1: Angle and vertical grinders
- Part 2: Wrenches, nutrunners and screwdrivers¹⁾
- Part 3: Polishers and rotary, orbital and random orbital sanders²)
- Part 4: Straight grinders³⁾
- Part 5: Drills and impact drills⁴⁾

¹⁾ Replaces ISO 8662-7, Hand-held portable power tools — Measurement of vibrations at the handle — Part 7: Wrenches, screwdrivers and nut runners with impact, impulse or ratchet action. All screwdrivers and nutrunners except for one-shot tools now covered.

²⁾ Replaces ISO 8662-8, Hand-held portable power tools — Measurement of vibrations at the handle — Part 8: Polishers and rotary, orbital and random orbital sanders.

³⁾ Together with ISO 28927-1, replaces ISO 8662-4, Hand-held portable power tools — Measurement of vibrations at the handle — Part 4: Grinders.

- Part 6: Rammers^o)
- Part 7: Nibblers and shears⁶⁾
- Part 8: Saws, polishing and filing machines with reciprocating action and small saws with oscillating or rotating action⁷)
- Part 9: Scaling hammers and needle scalers⁸⁾
- Part 10: Percussive drills, hammers and breakers⁹⁾
- Part 11: Stone hammers¹⁰⁾
- Part 12: Die grinders¹¹⁾

4) Replaces ISO 8662-6, Hand-held portable power tools — Measurement of vibrations at the handle — Part 6: Impact drills. Non-impacting drills now covered.

5) Replaces ISO 8662-9, Hand-held portable power tools — Measurement of vibrations at the handle — Part 9: Rammers.

6) Replaces ISO 8662-10, Hand-held portable power tools — Measurement of vibrations at the handle — Part 10: Nibblers and shears.

7) Replaces ISO 8662-12, Hand-held portable power tools — Measurement of vibrations at the handle — Part 12: Saws and files with reciprocating action and saws with oscillating or rotating action.

8) Together with ISO 28927-11 (to be published), replaces ISO 8662-14, Hand-held portable power tools — Measurement of vibrations at the handle — Part 14: Stone-working tools and needle scalers.

9) To be published. Replaces ISO 8662-2, Hand-held portable power tools — Measurement of vibrations at the handle — Part 2: Chipping hammers and riveting hammers, ISO 8662-3, Hand-held portable power tools — Measurement of vibrations at the handle — Part 3: Rock drills and rotary hammers, and ISO 8662-5, Hand-held portable power tools — Measurement of vibrations at the handle — Part 5: Pavement breakers and hammers for construction work. It also incorporates the Amendments ISO 8662-2:1992/Amd.1:1999, ISO 8662-3:1992/Amd.1:1999 and ISO 8662-5:1992/Amd.1:1999. Chipping and riveting hammers, rock drills and rotary hammers all covered.

10) To be published. Together with ISO 28927-9, replaces ISO 8662-14, Hand-held portable power tools — Measurement of vibrations at the handle — Part 14: Stone-working tools and needle scalers.

11) To be published. Replaces ISO 8662-13, Hand-held portable power tools — Measurement of vibrations at the handle — Part 13: Die grinders. It also incorporates the Technical Corrigendum ISO 8662-13:1997/Cor.1:1998.

Introduction

This document is a type-C standard as stated in ISO 12100.

When requirements of this type-C standard are different from those which are stated in type-A or -B standards, the requirements of this type-C standard take precedence over the requirements of the other standards for machines that have been designed and built according to the requirements of this type-C standard.

The vibration test codes for portable hand-held machines given in ISO 28927 (all parts) are based on ISO 20643, which gives general specifications for the measurement of the vibration emission of hand-held and hand-guided machinery. ISO 28927 (all parts) specifies the operation of the machines under type-test conditions and other requirements for the performance of type tests. The structure/numbering of its clauses follows that of ISO 20643.

The basic principle for transducer positioning first introduced in the EN 60745 series of European standards is followed, representing a deviation from ISO 20643 for reasons of consistency. The transducers are primarily positioned next to the hand in the area between the thumb and the index finger, where they give the least disturbance to the operator gripping the machine.

It has been found that vibrations generated by grinders vary considerably in typical use. The variation is largely due to the variances in the unbalance of the machine with the grinding wheel mounted. The unbalance also changes when the wheel is worn through the operation.

In order to provide a method that gives good measurement reproducibility, the procedure adopted in this part of ISO 28927 uses a test wheel of known unbalance mounted on a machine and run under no-load conditions. The unbalance for the different types of test wheels are chosen to give vibration values that are as far as possible in accordance with ISO 20643. The procedures of ISO 5349 (all parts) are required whenever exposure at the workplace is to be assessed.

Underestimation of the vibration for machines equipped with technical means to automatically reduce unbalances is taken into account by multiplying the vibration values of such machines with a correction factor of 1,3.

The values obtained are type-test values intended to be representative of the average of the upper quartile of typical vibration magnitudes in real-world use of the machines. However, the actual magnitudes vary considerably from time to time and depend on many factors, including the operator, the task and the inserted tool or consumable. The state of maintenance of the machine itself might also be of importance. Under real working conditions the influences of the operator and process can be particularly important at low magnitudes. It is therefore not recommended that emission values below $2,5 \text{ m/s}^2$ be used for estimating the vibration magnitude for estimating the machine.

If accurate values for a specific work place are required, then measurements [according to ISO 5349 (all parts)] in that work situation could be necessary. Vibration values measured in real working conditions can be either higher or lower than the values obtained using this part of ISO 28927.

Higher vibration magnitudes can easily occur in real work situations caused by the use of excessively unbalanced grinding wheels, worn flanges or bent spindles.

The vibration test codes given in ISO 28927 (all parts) supersede those given in ISO 8662 (all parts), which has been replaced by the corresponding parts of ISO 28927 (see Foreword).

NOTE ISO 8662-11, Hand-held portable power tools — Measurement of vibrations at the handle — Part 11: Fastener driving tools could be replaced by a future part of ISO 28927.