

This is a preview of "ISO 29821:2018". [Click here to purchase the full version from the ANSI store.](#)

First edition
2018-01

Condition monitoring and diagnostics of machines — Ultrasound — General guidelines, procedures and validation

*Surveillance des conditions et diagnostic d'état des machines —
Ultrasons*



Reference number
ISO 29821:2018(E)

© ISO 2018



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Published in Switzerland

This is a preview of "ISO 29821:2018". Click [here](#) to purchase the full version from the ANSI store.

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle of the airborne and structure-borne method	2
4.1 General.....	2
4.2 Application of airborne and structure-borne ultrasound within condition monitoring programmes.....	2
4.3 Correlation with other technologies.....	2
5 Ultrasound equipment	3
5.1 General.....	3
5.2 Kinds of sensors.....	5
5.3 Airborne sensor choice.....	5
5.4 Structure-borne sensor choice.....	6
5.5 Instrument characteristics.....	6
5.5.1 General.....	6
5.5.2 Frequency response.....	6
6 Data collection guidelines	7
6.1 General.....	7
6.2 Comparative ultrasound.....	7
6.3 Baseline method — Quantitative ultrasound.....	7
7 Training requirements	9
8 Assessment criteria	9
8.1 General.....	9
8.2 Error sources, accuracy and repeatability.....	11
9 Interpretation guidelines	12
10 Diagnosing ultrasonic problems	12
10.1 Principles of diagnostics using ultrasound.....	12
10.2 Generation of ultrasound.....	13
10.2.1 Surface friction.....	13
10.2.2 Fluid flow.....	13
10.2.3 Ionization.....	13
10.2.4 Impacting.....	13
11 Sensitivity validation guidelines	13
12 Monitoring interval	13
13 Data interpretations	13
14 Reporting	14
Annex A (informative) Example of a compressed air leak survey	15
Annex B (informative) Typical examples of ultrasound test reports	18
Annex C (informative) Example of a generic sensitivity validation procedure — Ultrasonic tone generator method	22
Bibliography	24

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 108, *Mechanical vibration, shock and condition monitoring*, Subcommittee SC 5, *Condition monitoring and diagnostics of machine systems*.

This first edition of ISO 29821 cancels and replaces ISO 29821-1:2011 and ISO 29821-2:2016, which has been technically revised.

This is a preview of "ISO 29821:2018". [Click here to purchase the full version from the ANSI store.](#)

Introduction

This document provides specific guidance on the interpretation of ultrasonic readings and wave files or frequency and time domain printouts (sometimes called “sound characteristics”) as part of a programme for condition monitoring and diagnostics of machines. Airborne (AB) and structure-borne (SB) ultrasound can be used to detect abnormal performance or machine anomalies. The anomalies are detected as high frequency acoustic events caused by turbulent flow, ionization events, impacts and friction, which are caused, in turn, by incorrect machinery operation, leaks, improper lubrication, worn components, and/or electrical discharges.

Airborne and structure-borne ultrasound is based on measuring the high frequency sound that is generated by either turbulent flow, friction, impacts or by the ionization created from the anomalies. The inspector therefore requires an understanding of ultrasound and how it propagates through the atmosphere and through structures as a prerequisite to the creation of an airborne and structure-borne ultrasound programme. Ultrasonic energy is present with the operation of all machines. It can be in the form of friction, turbulent flow, impacts and/or ionization as a property of the process, or produced by the process itself. As a result, ultrasonic emissions are created and these are an ideal parameter for monitoring the performance of machines, the condition of machines, and for diagnosing machine anomalies. Ultrasound is an ideal technology to do this monitoring because it provides an efficient way to quickly and non-invasively determine the location of an anomaly with little setup and in a very short period of time.