This is a preview of "ISO 3410:1989". Click here to purchase the full version from the ANSI store.

STANDARD

3410

Second edition 1989-08-01

Agricultural machinery — Endless variable-speed V-belts and groove sections of corresponding pulleys

Machines agricoles — Courroies trapézoïdales sans fin pour variateurs de vitesse et profils de gorge des poulies correspondantes



This is a preview of "ISO 3410:1989". Click here to purchase the full version from the ANSI store.

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 3410 was prepared by Technical Committee ISO/TC 41, *Pulleys and belts (including veebelts).*

This second edition cancels and replaces the first edition (ISO 3410 : 1976), of which it constitutes a technical revision.

Annex A of this International Standard is for information only.

© ISO 1989

International Organization for Standardization

Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Agricultural machinery – Endless variable-speed V-belts and groove sections of corresponding pulleys

1 Scope

This International Standard specifies the main dimensions of endless variable-speed V-belts intended for use on agricultural machinery (and, in particular, harvester-thresher machines), together with the groove section of the corresponding fixed- or variable-diameter pulleys.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 3 : 1973, Preferred numbers — Series of preferred numbers.

ISO 1081 : 1980, Drives using V-belts and pulleys — Terminology.

ISO 9608 : 1988, V-belts — Uniformity of belts — Centre distance variation — Specifications and test method.

3 Definitions and symbols

For the purposes of this International Standard, the terms and symbols relating to drives using V-belts (i.e. belts and grooved pulleys) defined in ISO 1081 apply.

4 Dimensions and tolerances

4.1 Belts

4.1.1 General

An endless variable-speed V-belt on agricultural machinery transmits a high degree of force per unit of section; when it approaches a groove pulley, its cross-section undergoes appreciable deformations. For this reason, the various dimensions which are defined hereunder are to be taken as being those of the belt placed on the device used for the measurement of its length, and subjected to the force *F*. The dimensions w_{pr} , *B*, *W* and *T* are those relating to the parts of the belt when in contact with the measuring pulleys.

4.1.2 Cross-sections (see figure 1)

The cross-section is characterized by a "relative height" (relation of height T of sides to pitch width w_p) which, on average, is in the region of 0,5; the pitch line is shown as being at approximately one-third of the height of the profile below the large base of the trapezium. The cross-sectional dimensions are given in table 2.

4.1.3 Lengths

The range of datum lengths is that of the R 40 series of preferred numbers (see ISO 3) from 630 mm to 5 000 mm (see table 3). If intermediate values are required, they shall be taken from the R 80 series of preferred numbers (see ISO 3).

4.1.4 Tolerance on length

The length of the belts is affected by the maximum admissible variations of $\frac{p}{2}$, where *p* is calculated, with a certain amount of approximation, using the formula

$$p = 0.8\sqrt[3]{L} + 0.006 L$$

L being the preferred number from the R 10 series equal to or immediately greater than the datum length, expressed in millimetres.

4.1.5 Centre distance variations

Centre distance variations are given in relation to the belt top width in table 1.

| | | Dimensi | ions in millimetres |
|-------------|----------------------|------------|---------------------|
| Belt length | | Top width | |
| over | up to (inclusive) | ≤ 25 | > 25 |
| | | ΔE | |
| _ | 1 000 | 1,2 | 1,8 |
| 1 000 | 2 000 | 1,6 | 2,2 |
| 2 000 | 5 000 | 2 | 3,4 |
| 5 000 | _ | 2,5 | 3,4 |

Table 1 — Centre distance variations

4.2 Grooved pulleys

These belts are almost always used with two variable-diameter pulleys (type 2), one of these pulleys possibly allowing for the release of the drive (type 3); more rarely, this type of belt can be made to function jointly with a fixed-diameter pulley (type 1). Table 4 gives, for each of these types, the datum diameter minimum values and radial dimensions of the groove.