

This is a preview of "ISO 37164:2021". [Click here to purchase the full version from the ANSI store.](#)

First edition
2021-05

Smart community infrastructures — Smart transportation using fuel cell light rail transit (FC-LRT)



Reference number
ISO 37164:2021(E)

© ISO 2021

This is a preview of "ISO 37164:2021". Click here to purchase the full version from the ANSI store.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

This is a preview of "ISO 37164:2021". [Click here to purchase the full version from the ANSI store.](#)

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Concept of smart transportation using FC-LRT	1
4.1 General.....	1
4.2 Satisfaction of SDGs.....	2
5 Operation of smart transportation using FC-LRT	2
5.1 Objectives.....	2
5.2 Minimum requirements and recommendations for organizing smart transportation.....	2
5.2.1 General.....	2
5.2.2 Recharging.....	2
5.2.3 Scheduling and dispatching.....	3
5.2.4 Maintenance work.....	3
5.2.5 Passenger services.....	3
5.2.6 Driving conditions.....	3
5.2.7 Driving skills and performance.....	3
5.2.8 Hydrogen delivery and storage.....	3
5.2.9 Emergency responses.....	3
5.2.10 Energy saving.....	4
6 Maintenance of the quality of smart transportation using FC-LRT	4
6.1 General.....	4
6.2 Parameters to be observed.....	4
6.3 Modification of smart transportation.....	4
Bibliography	5

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 268, *Sustainable cities and communities*, Subcommittee SC 1, *Smart community infrastructures*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

This is a preview of "ISO 37164:2021". [Click here to purchase the full version from the ANSI store.](#)

Introduction

Light rail transit (LRT) has been used as convenient urban public transportation in cities for over 100 years, due to its smooth acceleration and deceleration performance, good ride comfort and larger passenger capacity than bus vehicles. Although LRT has high energy efficiency and operation stability, as well as producing zero emissions, it has shortcomings. Conventional LRT is powered with electricity supplied from the outside of vehicles through catenaries and pantographs. Setting up catenaries and substations calls for considerably high capital cost and long construction times, and spoils urban views. The voltage of electricity depends on power grids and service lines, resulting in poor interconnection in rail service networks by LRT. If the grid power fails, services are suspended on all LRT lines. LRT equipped with energy storage using batteries and super capacitors is available, but the working distance in relation to charging time is not long enough for commercial services.

Fuel cell light rail transit (FC-LRT) solves such problems with conventional LRT. Normally, hydrogen fuel cells are adopted as power sources for FC-LRT. It is not necessary to equip rolling stock with pantographs, hang catenaries or install substations, resulting in preservation of the urban view and open skies. The elimination of the facilities leads to reduction in construction and maintenance costs and time, and also safety improvements, especially on the risk with high-voltage grids exposed in cities. Fuel-cell-powered vehicles emit no GHGs or small particles, only water. LRT vehicles with energy storage, which do not rely on grids for power supply, can run on tracks independently of voltage, whether electrified or not, wherever the track gauges are the same. The on-board power source makes LRT highly resilient, especially when the power grid fails. Fuel cells enable LRT vehicles to run for longer distances than possible with other on-board energy storage.