

Second edition
2018-02

Acoustics — Determination of sound power levels of noise sources using sound pressure — Engineering methods for small, movable sources in reverberant fields —

Part 2: Methods for special reverberation test rooms

Acoustique — Détermination des niveaux de puissance acoustique émis par les sources de bruit à partir de la pression acoustique — Méthodes d'expertise en champ réverbéré applicables aux petites sources transportables —

Partie 2: Méthodes en salle d'essai réverbérante spéciale



Reference number
ISO 3743-2:2018(E)

© ISO 2018

This is a preview of "ISO 3743-2:2018". Click [here](#) to purchase the full version from the ANSI store.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

This is a preview of "ISO 3743-2:2018". [Click here to purchase the full version from the ANSI store.](#)

Contents

	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	2
5 Noise source	2
6 Requirements for special reverberation test room	2
6.1 General.....	2
6.2 Volume of test room.....	2
6.3 Reverberation time of test room.....	3
6.4 Surface treatment.....	3
6.5 Criterion for background noise.....	3
6.6 Criteria for temperature and humidity.....	4
6.7 Evaluation of suitability of test room.....	4
7 Instrumentation	5
7.1 General.....	5
7.2 Microphone and its associated cable.....	5
7.3 Amplifier and weighting network.....	5
7.4 Octave-band filters.....	6
7.5 Squaring and averaging circuits and indicating device.....	6
7.6 Frequency response of the instrumentation system.....	6
7.7 Calibration.....	6
8 Installation and operation of source under test	6
8.1 General.....	6
8.2 Source location.....	6
8.3 Source mounting.....	7
8.4 Auxiliary equipment.....	7
8.5 Operation of source during the test.....	7
9 Measurements in test room	8
9.1 General.....	8
9.2 Period of observation.....	8
9.3 Microphone positions.....	8
9.4 Number of microphones and source positions.....	8
9.5 Criteria for the presence of spectral irregularities.....	10
9.6 Averaging technique with moving microphones.....	10
9.6.1 General.....	10
9.6.2 Path length for continuous averaging.....	10
9.6.3 Location of path within test room.....	10
9.6.4 Speed of traverse.....	10
9.7 Array of fixed microphones.....	11
9.8 Correction for background sound pressure levels.....	11
10 Calculation of sound power levels	11
10.1 Calculation of mean band pressure levels.....	11
10.2 Direct method for determining sound power levels.....	12
10.3 Comparison method for determining band power levels.....	12
10.4 A-weighted sound power levels determined by the comparison method.....	13
11 Measurement uncertainty	13
11.1 Methodology.....	13
11.2 Determination of σ_{omc}	14

This is a preview of "ISO 3743-2:2018". [Click here to purchase the full version from the ANSI store.](#)

11.3	Determination of σ_{R0}	14
11.3.1	General.....	14
11.3.2	Round robin test.....	14
11.3.3	Modelling approach for σ_{R0}	15
11.4	Typical upper bound values of σ_{R0}	15
11.5	Total standard deviation σ_{tot} and expanded uncertainty U	16
12	Information to be recorded	16
12.1	General.....	16
12.2	Sound source under test.....	16
12.3	Acoustical environment.....	17
12.4	Instrumentation.....	17
12.5	Acoustical data.....	17
13	Information to be reported	17
Annex A	(normative) Characteristics and calibration of reference sound source	18
Annex B	(informative) Guidelines for the design of special reverberation test rooms	19
Annex C	(informative) Examples of suitable instrumentation systems	24
Annex D	(informative) Guidance on the development of information on measurement uncertainty	26
Annex E	(normative) Sound power level under reference meteorological conditions	36
Annex F	(normative) Calculation of A-weighted sound power levels from octave band levels	37
Bibliography	38

This is a preview of "ISO 3743-2:2018". [Click here to purchase the full version from the ANSI store.](#)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*.

This second edition cancels and replaces the first edition (ISO 3743-2:1994), of which it constitutes a minor revision. The main changes are the following:

- Table 0.1 in the Introduction deleted;
- restructuring of the content of [Clause 1](#);
- references updated;
- clause on measurement uncertainty revised to be in-line with the other standards of the ISO 3740 series (now [Clause 11](#));
- new [Annexes D, E, and F](#) added;
- new entries in Bibliography added.

A list of all the parts in the ISO 3743 series can be found on the ISO website.

Introduction

ISO 3743 is one standard of the series ISO 3741 to ISO 3747 series, which specifies various methods for determining the sound power levels of machines, equipment and sub-assemblies. These basic standards specify the acoustical requirements for measurements appropriate for different test environments. When selecting one of the methods of the series ISO 3741 to ISO 3747, it is necessary to select the most appropriate for the conditions and purposes of the noise test. General guidelines to assist in the selection are provided in ISO 3740. The series ISO 3741 to ISO 3747 gives only general principles regarding the operating and mounting conditions of the machine or equipment under test. Reference should be made to the noise test code for a specific type of machine or equipment, if available, for specifications on mounting and operating conditions.

The method given in this document enables measurement of sound pressure levels with A-weighting and in octave bands at pre-scribed fixed microphone positions or along prescribed paths. It allows determination of A-weighted sound power levels or sound power levels with other weighting and octave-band sound power levels. Quantities which cannot be determined are the directivity characteristics of the source and the temporal pattern of noise radiated by sources emitting non-steady noise.

ISO 3743-1 and this document specify engineering methods for determining the A-weighted and octave-band sound power levels of small noise sources. The methods are applicable to small machines, devices, components and sub-assemblies which can be installed in a special reverberation test room or in a hard-walled test room with prescribed acoustical characteristics. The methods are particularly suitable for small items of portable equipment; they are not intended for larger pieces of stationary equipment which, due to their manner of operation or installation, cannot readily be moved into the test room and operated as in normal usage. The procedures are intended to be used when an engineering grade of accuracy is desired without requiring the use of laboratory facilities.

In ISO 3743-1, a comparison method is used to determine the octave-band sound power levels of the source. The spatial average (octave-band) sound pressure levels produced by the source under test are compared to the spatial average (octave-band) sound pressure levels produced by a reference sound source of known sound power output. The difference in sound pressure levels is equal to the difference in sound power levels if conditions are the same for both sets of measurements. The A-weighted sound power level is then calculated from the octave-band sound power levels.

The requirements to be fulfilled by the special reverberation test room for measurements in accordance with this document are significantly more restrictive than those placed on the hard-walled test room by the comparison method of ISO 3743-1.