

First edition
2005-10-01

Straight cylindrical involute splines — Metric module, side fit —

Part 3: Inspection

*Cannelures cylindriques droites à flancs en développante — Module
métrique, à centrage sur flancs —*

Partie 3: Vérification



Reference number
ISO 4156-3:2005(E)

© ISO 2005

This is a preview of "ISO 4156-3:2005". [Click here to purchase the full version from the ANSI store.](#)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

This is a preview of "ISO 4156-3:2005". Click here to purchase the full version from the ANSI store.

Contents

Page

| | |
|--|----|
| Foreword..... | iv |
| Introduction | v |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 2 |
| 4 Symbols and abbreviated terms | 2 |
| 5 Reference conditions | 3 |
| 6 Quality features..... | 4 |
| 6.1 General..... | 4 |
| 6.2 Size..... | 4 |
| 6.3 Location | 4 |
| 6.4 Form | 5 |
| 7 Methods of inspection..... | 5 |
| 7.1 Size..... | 5 |
| 7.2 Location | 7 |
| 7.3 Form | 9 |
| 8 Measurements with balls or pins | 9 |
| 8.1 General..... | 9 |
| 8.2 Selection of balls or pins | 10 |
| 8.3 Use and marking of pins..... | 10 |
| 8.4 Statistical actual tolerance limit STA..... | 10 |
| 8.5 Calculation of ball or pin diameter (D_{Re} or D_{Ri})..... | 13 |
| 8.6 Calculation of dimensions for ball or pin inspection (part and gauge inspection) | 15 |
| 9 Measurement over k teeth — External splines (W)..... | 19 |
| 9.1 Calculation of W | 19 |
| 9.2 Choice of k | 20 |
| 10 Gauges | 21 |
| 10.1 Generalities | 21 |
| 10.2 Length of measuring part of gauges | 22 |
| 10.3 Manufacturing tolerances for spline gauges (see Tables 8, 9 and 10)..... | 24 |
| 10.4 Values of deviation allowances of spline gauges | 27 |
| 10.5 Inspection of gauges | 27 |
| 10.6 Dimensions, designation and marking of gauges..... | 29 |
| 11 Measurement of spline deviations | 40 |
| 11.1 General..... | 40 |
| 11.2 Total profile deviation F_{α} | 40 |
| 11.3 Total cumulative pitch deviation F_p | 40 |
| 11.4 Total helix deviation F_{β} | 40 |
| Annex A (informative) Influences of eccentricity and pitch deviation as explained in ISO 4156:1981..... | 41 |

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 4156-3 was prepared by Technical Committee ISO/TC 14, *Shafts for machinery and accessories*.

This first edition of ISO 4156-3, together with ISO 4156-1 and ISO 4156-2, cancels and replaces ISO 4156:1981 and ISO 4156:1981/Amd 1:1992, of which it constitutes a technical revision.

ISO 4156 consists of the following parts, under the general title *Straight cylindrical involute splines — Metric module, side fit*:

- *Part 1: Generalities*
- *Part 2: Dimensions*
- *Part 3: Inspection*

This is a preview of "ISO 4156-3:2005". [Click here to purchase the full version from the ANSI store.](#)

Introduction

ISO 4156 provides the data and indications necessary for the design, manufacture and inspection of straight (non-helical) side-fitting cylindrical involute splines.

Straight cylindrical involute splines manufactured in accordance with ISO 4156 are used for clearance, sliding and interference connections of shafts and hubs. They contain all the necessary characteristics for the assembly, transmission of torque, and economic production.

The nominal pressure angles are 30° , $37,5^\circ$ and 45° . For electronic data processing purposes, the form of expression $37,5^\circ$ has been adopted instead of $37^\circ30'$. ISO 4156 establishes a specification based on the following modules:

— for pressure angles of 30° and $37,5^\circ$ the module increments are

0,5; 0,75; 1; 1,25; 1,5; 1,75; 2; 2,5; 3; 4; 5; 6; 8; 10

— for pressure angle of 45° the module increments are

0,25; 0,5; 0,75; 1; 1,25; 1,5; 1,75; 2; 2,5