

INTERNATIONAL ISO  
This is a preview of "ISO 4548-3:1997". Click here to purchase the full version from the ANSI store.

Second edition  
1997-09-15

---

---

## **Methods of test for full-flow lubricating oil filters for internal combustion engines —**

### **Part 3:**

### **Resistance to high differential pressure and to elevated temperature**

*Méthodes d'essai des filtres à huile de lubrification à passage intégral pour  
moteurs à combustion interne —*

*Partie 3: Résistance aux pressions différentielles élevées et aux hautes  
températures*

This material is reproduced from ISO documents under International Organization for Standardization (ISO) Copyright License number IHS/ICC/1996. Not for resale. No part of these ISO documents may be reproduced in any form, electronic retrieval system or otherwise, except as allowed in the copyright law of the country of use, or with the prior written consent of ISO (Case postale 56, 1211 Geneva 20, Switzerland, Fax +41 22 734 10 79), IHS or the ISO Licensor's members.



Reference number  
ISO 4548-3:1997(E)

This is a preview of "ISO 4548-3:1997". Click here to purchase the full version from the ANSI store.

## Contents

<b>1 Scope .....</b>	<b>1</b>
<b>2 Normative references .....</b>	<b>1</b>
<b>3 Definitions .....</b>	<b>1</b>
<b>4 Graphical symbols.....</b>	<b>1</b>
<b>5 Operational characteristics to be tested .....</b>	<b>1</b>
<b>6 Filter to be tested.....</b>	<b>1</b>
<b>6.1 Filter type.....</b>	<b>2</b>
<b>6.2 Filter element .....</b>	<b>2</b>
<b>7 Test rig.....</b>	<b>2</b>
<b>7.1 Sump.....</b>	<b>2</b>
<b>7.2 Regulating valves .....</b>	<b>2</b>
<b>7.3 Flow meter .....</b>	<b>2</b>
<b>7.4 Filter mounting.....</b>	<b>2</b>
<b>8 Test liquids.....</b>	<b>6</b>
<b>8.1 Test liquids for test of ability to withstand high differential pressure .....</b>	<b>6</b>
<b>8.2 Test liquid for test of ability to withstand elevated temperature .....</b>	<b>6</b>
<b>9 Accuracy of test condition measurements .....</b>	<b>6</b>
<b>10 Test procedure.....</b>	<b>6</b>
<b>10.1 Test for ability to withstand high differential pressure .....</b>	<b>6</b>
<b>10.2 Test for ability to withstand elevated temperature.....</b>	<b>7</b>
<b>11 Report of test results.....</b>	<b>7</b>
<b>11.1 High differential pressure test.....</b>	<b>7</b>
<b>11.2 Elevated temperature test.....</b>	<b>8</b>
<b>Annex A (informative) Bibliography .....</b>	<b>9</b>

© ISO 1997

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization  
Case postale 56 • CH-1211 Genève 20 • Switzerland  
Internet central@iso.ch  
X.400 c=ch; a=400net; p=iso; o=isocs; s=central

Printed in Switzerland

This is a preview of "ISO 4548-3:1997". [Click here to purchase the full version from the ANSI store.](#)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 4548-3 was prepared by Technical Committee ISO/TC 70, *Internal combustion engines*, Subcommittee SC 7, *Tests for lubricating oil filters*.

This second edition cancels and replaces the first edition (ISO 4548-3:1982), which has been technically revised.

ISO 4548 consists of the following parts, under the general title *Methods of test for full-flow lubricating oil filters for internal combustion engines*:

- *Part 1: Differential pressure/flow characteristics*
- *Part 2: Element by-pass valve characteristics*
- *Part 3: Resistance to high differential pressure and to elevated temperature*
- *Part 4: Initial particle retention efficiency, life and cumulative efficiency (gravimetric method)*
- *Part 5: Cold start simulation and hydraulic pulse durability test*
- *Part 6: Static burst pressure test*
- *Part 7: Vibration fatigue test*
- *Part 9: Inlet and outlet anti-drain valve tests*
- *Part 10: Life and cumulative efficiency in the presence of water in oil*
- *Part 11: Self-cleaning filters*
- *Part 12: Particle retention ability and contaminant holding capacity using particle counting*

Annex A of this part of ISO 4548 is for information only.

This is a preview of "ISO 4548-3:1997". [Click here to purchase the full version from the ANSI store.](#)

## Introduction

ISO 4548 establishes standard test procedures for measuring the performance of full-flow lubricating oil filters for internal combustion engines. It has been prepared in separate parts, each part relating to a particular performance characteristic.

Together the tests provide the information necessary to assess the characteristics of a filter, but if agreed between the purchaser and the manufacturer, the tests may be conducted separately.

This revision of this part of ISO 4548 has been undertaken in order to align the presentation with the requirements of the current ISO Directives. The principal changes are editorial, affecting the layout and the text. Minor technical changes comprise the addition of details of a grade of oil to achieve the required viscosity of test liquid for testing the ability of a filter to withstand high differential pressure, and revision of the test rig dimensions to make them consistent with those specified in ISO 3968. In addition, the flow meter on the test rig has been repositioned downstream of the throttle valve.

This is a preview of "ISO 4548-3:1997". [Click here to purchase the full version from the ANSI store.](#)

# Methods of test for full-flow lubricating oil filters for internal combustion engines —

## Part 3: Resistance to high differential pressure and to elevated temperature

### 1 Scope

This part of ISO 4548 specifies tests for measuring the resistance to high differential pressure and the resistance to elevated temperatures of filter elements of full-flow lubricating oil filters for internal combustion engines.

### 2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 4548. At the time of publication, the editions indicated were valid. All standards are subject to revision and parties to agreement based on this part of ISO 4548 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 1219-1:1991, *Fluid power systems and components — Graphic symbols and circuit diagrams — Part 1: Graphic symbols.*

ISO 2942:1994, *Hydraulic fluid power — Filter elements — Verification of fabrication integrity and determination of the first bubble point.*

ISO 11841-1:—1), *Road vehicles and internal combustion engines — Filter vocabulary — Part 1: Definitions of filters and filter components.*

ISO 11841-2:—1), *Road vehicles and internal combustion engines — Filter vocabulary — Part 2: Definitions of characteristics of filters and their components.*

### 3 Definitions

For the purposes of this part of ISO 4548, the definitions given in ISO 11841-1 and ISO 11841-2 apply.

### 4 Graphical symbols

The graphical symbols used in this part of ISO 4548 are in accordance with ISO 1219-1.

### 5 Operational characteristics to be tested

Filters can be subjected to high differential pressures in service, particularly as choking takes place with age. They can also be affected by high operating temperatures. This test confirms the ability of a filter element to withstand a specified differential pressure without failure following conditioning at a simulated operating temperature.

---

1) To be published.