

This is a preview of "ISO 5167-3:2020". [Click here to purchase the full version from the ANSI store.](#)

Second edition
2020-08

Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full —

Part 3: Nozzles and Venturi nozzles

*Mesure de débit des fluides au moyen d'appareils déprimogènes
insérés dans des conduites en charge de section circulaire —*

Partie 3: Tuyères et Venturi-tuyères



Reference number
ISO 5167-3:2020(E)

© ISO 2020



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

This is a preview of "ISO 5167-3:2020". Click here to purchase the full version from the ANSI store.

Contents

	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Principles of the method of measurement and computation	2
5 Nozzles and Venturi nozzles	3
5.1 ISA 1932 nozzle.....	3
5.1.1 General shape.....	3
5.1.2 Nozzle profile.....	3
5.1.3 Downstream face.....	5
5.1.4 Material and manufacture.....	5
5.1.5 Pressure tappings.....	5
5.1.6 Coefficients of ISA 1932 nozzles.....	7
5.1.7 Uncertainties.....	8
5.1.8 Pressure loss, $\Delta\varpi$	8
5.2 Long radius nozzles.....	9
5.2.1 General.....	9
5.2.2 Profile of high-ratio nozzle.....	9
5.2.3 Profile of low-ratio nozzle.....	12
5.2.4 Material and manufacture.....	12
5.2.5 Pressure tappings.....	12
5.2.6 Coefficients of long radius nozzles.....	13
5.2.7 Uncertainties.....	13
5.2.8 Pressure loss, $\Delta\varpi$	14
5.3 Throat-tapped nozzles.....	14
5.3.1 General.....	14
5.3.2 Profile of throat-tapped nozzle.....	14
5.3.3 Material and manufacturing.....	15
5.3.4 Pressure Tappings.....	15
5.3.5 Coefficients.....	16
5.3.6 Uncertainties.....	17
5.3.7 Calibration and extrapolation.....	17
5.3.8 Pressure Loss.....	18
5.4 Venturi nozzles.....	18
5.4.1 General shape.....	18
5.4.2 Material and manufacture.....	21
5.4.3 Pressure tappings.....	21
5.4.4 Coefficients.....	22
5.4.5 Uncertainties.....	23
5.4.6 Pressure loss.....	23
6 Installation requirements	24
6.1 General.....	24
6.2 Minimum upstream and downstream straight lengths for installation between various fittings and the primary device.....	24
6.3 Flow conditioners.....	30
6.4 Circularity and cylindricality of the pipe.....	30
6.5 Location of primary device and carrier rings.....	31
6.6 Method of fixing and gaskets.....	32
7 Flow calibration of nozzles	32
7.1 General.....	32
7.2 Test facility.....	33

This is a preview of "ISO 5167-3:2020". [Click here to purchase the full version from the ANSI store.](#)

7.3	Meter installation.....	33
7.4	Design of the test programme.....	33
7.5	Reporting the calibration results	33
7.6	Uncertainty analysis of the calibration.....	33
7.6.1	General.....	33
7.6.2	Uncertainty of the test facility.....	33
7.6.3	Uncertainty of the nozzle.....	34
Annex A	(informative) Tables of discharge coefficients and expansibility [expansion] factors.....	35
Annex B	(informative) Akashi type (Mitsubishi type) flow conditioner	42
Bibliography	43

This is a preview of "ISO 5167-3:2020". [Click here to purchase the full version from the ANSI store.](#)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 30, *Measurement of fluid flow in closed conduits*, Subcommittee SC 2 *Pressure differential devices*.

This second edition cancels and replaces the first edition (ISO 5167-3:2003), which has been technically revised. The main changes compared to the previous edition are as follows:

— Addition of [Subclause 5.3](#).

A list of all parts in the ISO 5167 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

ISO 5167, consisting of six parts, covers the geometry and method of use (installation and operating conditions) of orifice plates, nozzles, Venturi tubes, cone meters and wedge meters when they are inserted in a conduit running full to determine the flowrate of the fluid flowing in the conduit. It also gives necessary information for calculating the flowrate and its associated uncertainty.

ISO 5167 (all parts) is applicable only to pressure differential devices in which the flow remains subsonic throughout the measuring section and where the fluid can be considered as single-phase, but is not applicable to the measurement of pulsating flow. Furthermore, each of these devices can only be used within specified limits of pipe size and Reynolds number.

ISO 5167 (all parts) deals with devices for which direct calibration experiments have been made, sufficient in number, spread and quality to enable coherent systems of application to be based on their results and coefficients to be given with certain predictable limits of uncertainty.

The devices introduced into the pipe are called "primary devices". The term primary device also includes the pressure tapplings. All other instruments or devices required for the measurement are known as "secondary devices". ISO 5167 (all parts) covers primary devices; secondary devices¹⁾ will be mentioned only occasionally.

ISO 5167 consists of the following six parts.

- a) ISO 5167-1 gives general terms and definitions, symbols, principles and requirements as well as methods of measurement and uncertainty that are to be used in conjunction with ISO 5167-2, ISO 5167-3, ISO 5167-4, ISO 5167-5 and ISO 5167-6.
- b) ISO 5167-2 specifies orifice plates, which can be used with corner pressure tapplings, D and $D/2$ pressure tapplings²⁾, and flange pressure tapplings.
- c) ISO 5167-3 specifies ISA 1932 nozzles³⁾, long radius nozzles, throat-tapped nozzles and Venturi nozzles, which differ in shape and in the position of the pressure tapplings.
- d) ISO 5167-4 specifies classical Venturi tubes⁴⁾.
- e) ISO 5167-5 specifies cone meters.
- f) ISO 5167-6 specifies wedge meters.

Aspects of safety are not dealt within ISO 5167-1 to ISO 5167-6. It is the responsibility of the user to ensure that the system meets applicable safety regulations.

1) See ISO 2186:2007.

2) Orifice plates with "vena contracta" pressure tapplings are not considered in ISO 5167-2.

3) ISA is the abbreviation for the International Federation of the National Standardizing Associations, which was succeeded by ISO in 1946.

4) In the USA the classical Venturi tube is sometimes called the Herschel Venturi tube.