First edition 2003-03-01

# Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full —

Part 4:

# Venturi tubes

Mesure de débit des fluides au moyen d'appareils déprimogènes insérés dans des conduites en charge de section circulaire —

Partie 4: Tubes de Venturi



### PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

### © ISO 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Cont	ents	Page
Forewo	ord	iv
Introdu	uction	v
1	Scope	1
2	Normative references	2
3	Terms and definitions	2
4	Principles of the method of measurement and computation	2
5	Classical Venturi tubes	
5.1 5.2	Field of application	
5.2 5.3	General shape Material and manufacture	
5.4	Pressure tappings	
5.5	Discharge coefficient, C	
5.6	Expansibility [expansion] factor, $\varepsilon$	
5.7 5.8	Uncertainty of the discharge coefficient $C$	
5.6 5.9	Pressure loss	
6	Installation requirements	11
6.1	General	
6.2	Minimum upstream and downstream straight lengths for installation between various	4.4
6.3	fittings and the Venturi tube	
6.4	Additional specific installation requirements for classical Venturi tubes	
Annex	A (informative) Table of expansibility [expansion] factor	17
	B (informative) Classical Venturi tubes used outside the scope of ISO 5167-4	
Annex	C (informative) Pressure loss in a classical Venturi tube	22
	graphy	

Contents

## **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 5167-4 was prepared by Technical Committee ISO/TC 30, *Measurement of fluid flow in closed conduits*, Subcommittee SC 2, *Pressure differential devices*.

This first edition of ISO 5167-4, together with the second edition of ISO 5167-1 and the first editions of ISO 5167-2 and ISO 5167-3, cancels and replaces the first edition of ISO 5167-1:1991, which has been technically revised, and ISO 5167-1:1991/Amd.1:1998.

ISO 5167 consists of the following parts, under the general title Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full:

- Part 1: General principles and requirements
- Part 2: Orifice plates
- Part 3: Nozzles and Venturi nozzles
- Part 4: Venturi tubes

# Introduction

ISO 5167, divided into four parts, covers the geometry and method of use (installation and operating conditions) of orifice plates, nozzles and Venturi tubes when they are inserted in a conduit running full to determine the flowrate of the fluid flowing in the conduit. It also gives necessary information for calculating the flowrate and its associated uncertainty.

ISO 5167 is applicable only to pressure differential devices in which the flow remains subsonic throughout the measuring section and where the fluid can be considered as single-phase, but is not applicable to the measurement of pulsating flow. Furthermore, each of these devices can only be used within specified limits of pipe size and Reynolds number.

ISO 5167 deals with devices for which direct calibration experiments have been made, sufficient in number, spread and quality to enable coherent systems of application to be based on their results and coefficients to be given with certain predictable limits of uncertainty.

The devices introduced into the pipe are called "primary devices". The term primary device also includes the pressure tappings. All other instruments or devices required for the measurement are known as "secondary devices". ISO 5167 covers primary devices; secondary devices<sup>1)</sup> will be mentioned only occasionally.

ISO 5167 is divided into the following four parts.

- a) Part 1 of ISO 5167 gives general terms and definitions, symbols, principles and requirements as well as methods of measurement and uncertainty that are to be used in conjunction with Parts 2 to 4 of ISO 5167.
- b) Part 2 of ISO 5167 specifies orifice plates, which can be used with corner pressure tappings, D and D/2 pressure tappings<sup>2</sup>), and flange pressure tappings.
- c) Part 3 of ISO 5167 specifies ISA 1932 nozzles<sup>3)</sup>, long radius nozzles and Venturi nozzles, which differ in shape and in the position of the pressure tappings.
- d) This part of ISO 5167 specifies classical Venturi tubes<sup>4</sup>).

Aspects of safety are not dealt with in Parts 1 to 4 of ISO 5167. It is the responsibility of the user to ensure that the system meets applicable safety regulations.

<sup>1)</sup> See ISO 2186:1973, Fluid flow in closed conduits — Connections for pressure signal transmissions between primary and secondary elements.

<sup>2)</sup> Orifice plates with "vena contracta" pressure tappings are not considered in ISO 5167.

<sup>3)</sup> ISA is the abbreviation for the International Federation of the National Standardizing Associations, which was succeeded by ISO in 1946.

<sup>4)</sup> In the USA the classical Venturi tube is sometimes called the Herschel Venturi tube.