Second edition 2006-09-15

# Reaction to fire tests — Spread of flame —

Part 2: Lateral spread on building and transport products in vertical configuration

Essais de réaction au feu — Propagation du feu —

Partie 2: Propagation latérale sur les produits de bâtiment et de transport en position verticale



Reference number ISO 5658-2:2006(E)

#### **PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org Published in Switzerland

## Contents

Forewordv			
Introduction			
1	Scope		
2	Normative references	1	
3	Definitions	1	
4	Principle	3	
5	Suitability of a product for testing	4	
5.1 5.2	Surface characteristics		
•	Thermally unstable products		
6 6.1	Exposed surface		
6.2	Number and size of specimens		
6.3 6.4	Construction of specimens		
6.5	Preparation		
7	Test apparatus		
7.1 7.2	General The radiant panel support framework		
7.3	Specimen support framework		
7.4	Specimen holder		
7.5	Pilot flame burner		
8	Test environment		
9 9.1	Additional equipment and instrumentation Heat-flux meter	.15 15	
9.2	Total radiation pyrometer	.16	
9.3 9.4	Recorder Timing devices		
9.5	Dummy specimen		
9.6	Calibration board16		
9.7	Backing boards and spacers		
10 10.1	Setting-up and calibration procedure		
10.2	Verification	.20	
10.3	Adjustment of the pilot flame		
11	Test procedure		
12	Expression of fire performance of a product	.22	
13	Test report	.22	
Annex A (normative) Safety precautions24			
Annex B (informative) Specimen construction			
Annex C (informative) Calibration of the working heat-flux meter			
Annex D (informative) Guidelines for reporting and follow-up of results of fire test procedures			
Annex E (informative) Variability of test results			

Annex F (normative) Test method for flame spread o	f plastic piping
Bibliography	

#### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 5658-2 was prepared by Technical Committee ISO/TC 92, *Fire safety*, Subcommittee SC 1, *Fire initiation and growth*.

This second edition of ISO 5658-2 cancels and replaces the first edition (ISO 5658-2:1996), which has been technically revised.

ISO 5658 consists of the following parts, under the general title Reaction to fire tests — Spread of flame:

- Part 1: Guidance on flame spread [Technical Specification]
- Part 2: Lateral spread on building and transport products in vertical configuration
- Part 4: Intermediate-scale test of vertical spread of flame with vertically oriented specimen

### Introduction

This part of ISO 5658 is based on the method of the International Maritime Organization (IMO) published as IMO Resolution A.653 (16)<sup>[4]</sup>, and has been developed as an International Standard in order to allow its wider use. The major differences between ISO 5658-2 and the IMO test are that ISO 5658-2 is limited in scope to testing the spread of flame over vertical specimens and does not include the stack for estimating heat release rate. The second edition of this part of ISO 5658 avoids the use of acetylene for the pilot flame and uses the propane pilot flame in an impinging mode. The current IMO flame spread procedure is still based on ISO 5658-2:1996.

ISO/TS 5658-1<sup>[2]</sup> describes the development of standard tests for flame spread and explains the theory of flame spread for various orientations. This part of ISO 5658 provides a simple method by which lateral surface spread of flame on a vertical specimen can be determined for comparative purposes. This method is particularly useful for research, development and quality control purposes.

Fire is a complex phenomenon: its behaviour and its effects depend upon a number of interrelated factors. The behaviour of materials and products depends upon the characteristics of the fire, the method of use of the materials and the environment to which they are exposed. The methodology of "reaction-to-fire" tests is explained in ISO/TR 3814<sup>[1]</sup>.

A test such as is specified in this part of ISO 5658 deals only with a simple representation of a particular aspect of the potential fire situation typified by a radiant-heat source and flame; it cannot alone provide any direct guidance on behaviour or safety in fire.

Annexes A and F form integral parts of this part of ISO 5658. Annexes B to E are for information only. A precision statement based on inter-laboratory trials using this test method is given in Annex E.

This test procedure does not rely on the use of asbestos-based materials.

The attention of all users of the test is drawn to the introductory caution statement.