

This is a preview of "ISO 6336-3:2006". [Click here to purchase the full version from the ANSI store.](#)

Second edition
2006-09-01

Corrected version
2007-04-01

Calculation of load capacity of spur and helical gears —

Part 3: Calculation of tooth bending strength

Calcul de la capacité de charge des engrenages cylindriques à dentures droite et hélicoïdale —

Partie 3: Calcul de la résistance à la flexion en pied de dent



Reference number
ISO 6336-3:2006(E)

© ISO 2006

This is a preview of "ISO 6336-3:2006". [Click here to purchase the full version from the ANSI store.](#)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

This is a preview of "ISO 6336-3:2006". Click here to purchase the full version from the ANSI store.

Contents

	Page
Foreword.....	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols and abbreviated terms.....	1
4 Tooth breakage and safety factors	2
5 Basic formulae	2
5.1 Safety factor for bending strength (safety against tooth breakage), S_F.....	2
5.2 Tooth root stress, σ_F	2
5.3 Permissible bending stress, σ_{FP}	4
6 Form factor, Y_F	8
6.1 General.....	8
6.2 Calculation of the form factor, Y_F: Method B.....	9
6.3 Derivations of determinant normal tooth load for spur gears	13
7 Stress correction factor, Y_S	14
7.1 Basic uses	14
7.2 Stress correction factor, Y_S: Method B.....	14
7.3 Stress correction factor for gears with notches in fillets	15
7.4 Stress correction factor, Y_{ST}, relevant to the dimensions of the standard reference test gears.....	15
8 Helix angle factor, Y_β	15
8.1 Graphical value	16
8.2 Determination by calculation.....	16
9 Rim thickness factor, Y_B.....	16
9.1 Graphical values	16
9.2 Determination by calculation.....	17
10 Deep tooth factor, Y_{DT}	18
10.1 Graphical values	18
10.2 Determination by calculation.....	18
11 Reference stress for bending	19
11.1 Reference stress for Method A.....	19
11.2 Reference stress, with values $\sigma_{F\lim}$ and σ_{FE} for Method B	19
12 Life factor, Y_{NT}.....	19
12.1 Life factor, Y_{NT}: Method A.....	19
12.2 Life factor, Y_{NT}: Method B.....	19
13 Sensitivity factor, $Y_{\delta T}$, and relative notch sensitivity factor, $Y_{\delta\text{rel}T}$.....	21
13.1 Basic uses	21
13.2 Determination of the sensitivity factors	21
13.3 Relative notch sensitivity factor, $Y_{\delta\text{rel}T}$: Method B.....	22
14 Surface factors, Y_R, Y_{RT}, and relative surface factor, $Y_{R\text{rel}T}$.....	27
14.1 Influence of surface condition.....	27

This is a preview of "ISO 6336-3:2006". [Click here to purchase the full version from the ANSI store.](#)

14.2	Determination of surface factors and relative surface factors.....	28
14.3	Relative surface factor, $Y_{R\ rel\ T}$: Method B	28
15	Size factor, Y_X	30
15.1	Size factor, Y_X: Method A	30
15.2	Size factor, Y_X: Method B	30
Annex A (normative)	Permissible bending stress, σ_{FP}, obtained from notched, flat or plain polished test pieces	33
Annex B (informative)	Guide values for mean stress influence factor, Y_M.....	40
Bibliography	42

This is a preview of "ISO 6336-3:2006". [Click here to purchase the full version from the ANSI store.](#)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 6336-3 was prepared by Technical Committee ISO/TC 60, *Gears*, Subcommittee SC 2, *Gear capacity calculation*.

This second edition cancels and replaces the first edition (ISO 6336-3:1996), Clauses 5 and Clause 9 of which have been technically revised, with a new Clause 8 having been added to this new edition. It also incorporates the Technical Corrigendum ISO 6336-3:1996/Cor.1:1999.

ISO 6336 consists of the following parts, under the general title *Calculation of load capacity of spur and helical gears*:

- *Part 1: Basic principles, introduction and general influence factors*
- *Part 2: Calculation of surface durability (pitting)*
- *Part 3: Calculation of tooth bending strength*
- *Part 5: Strength and quality of materials*
- *Part 6: Calculation of service life under variable load*

This corrected version incorporates the following corrections:

- Figure 3 has been updated;
- in Equation (17), the missing lines denoting the absolute value, Z_n , have been inserted;
- minus signs missing from Equations (18) and (19) have been inserted;
- Equation (50) has been corrected.

Introduction

The maximum tensile stress at the tooth root (in the direction of the tooth height), which may not exceed the permissible bending stress for the material, is the basis for rating the bending strength of gear teeth. The stress occurs in the "tension fillets" of the working tooth flanks. If load-induced cracks are formed, the first of these often appears in the fillets where the compressive stress is generated, i.e. in the "compression fillets", which are those of the non-working flanks. When the tooth loading is unidirectional and the teeth are of conventional shape, these cracks seldom propagate to failure. Crack propagation ending in failure is most likely to stem from cracks initiated in tension fillets.

The endurable tooth loading of teeth subjected to a reversal of loading during each revolution, such as "idler gears", is less than the endurable unidirectional loading. The full range of stress in such circumstances is more than twice the tensile stress occurring in the root fillets of the loaded flanks. This is taken into consideration when determining permissible stresses (see ISO 6336-5).

When gear rims are thin and tooth spaces adjacent to the root surface narrow (conditions which can particularly apply to some internal gears), initial cracks commonly occur in the compression fillet. Since, in such circumstances, gear rims themselves can suffer fatigue breakage, special studies are necessary. See Clause 1.

Several methods for calculating the critical tooth root stress and evaluating some of the relevant factors have been approved. See ISO 6336-1.