ISO

This is a preview of "ISO 6356:2012". Click here to purchase the full version from the ANSI store.

Second edition 2012-07-15

Textile and laminate floor coverings — Assessment of static electrical propensity — Walking test

Revêtements de sol textiles et laminés — Évaluation de la propension à l'accumulation des charges électrostatiques — Essai du marcheur



Reference number ISO 6356:2012(E)

ISO 6356:2012(E)

This is a preview of "ISO 6356:2012". Click here to purchase the full version from the ANSI store.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

This is a preview of "ISO 6356:2012". Click here to purchase the full version from the ANSI store.

Contents		Page
Forew	ord	iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	
4	Principle	
5	Apparatus	
5.1	Grounded metal base plate	2
5.2	Rubber mat.	
5.3 5.4	Polyethylene foam (PE-foam)Polyethylene foil (PE-foil)	
5.5	Test sandals	
5.6	Means of cleaning the sandals	
5.7	lonizing source	
5.8 5.9	Body voltage measuring system Measuring devices for temperature and relative humidity	
	Sampling and selection of specimens	
6 6.1	Textile floor coverings	
6.2	Laminate	
7	Preconditioning of specimens, PE-foam, PE-foil and rubber mats	3
8	Atmosphere for conditioning and testing	4
9	Test procedures	4
9.1	Preparation	
9.2	Method A: test procedure in laboratory conditions	
9.3	Method B: test procedure in situ	
10	Calculation and expression of results	
11	Test report	
	A (normative) Specification of the sandals	
Annex	B (normative) Standard sole material — Neolite (standard XS-664P)	11
Annex	C (normative) Standard sole material — BAM-rubber	12
Annex D (normative) Method for measuring the electrical resistance of the footwear		13
Annex	E (normative) Example of a hand-held electrode and its use	15
Annex	F (informative) Method of checking calibration of the measuring system	17
Bibliography		18

This is a preview of "ISO 6356:2012". Click here to purchase the full version from the ANSI store.

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 6356 was prepared by Technical Committee ISO/TC 219, Floor coverings.

This second edition cancels and replaces the first edition (ISO 6356:2000), which has been technically revised.

This is a preview of "ISO 6356:2012". Click here to purchase the full version from the ANSI store.

Introduction

This test is a measurement of the electric potential (voltage) due to the accumulation of static charge on a person walking on the surface of a textile and laminate floor covering under controlled conditions. It is important that this measurement is made under carefully controlled conditions to minimize test variability.