Third edition 2018-08

Anodizing of aluminium and its alloys — Determination of the comparative fastness to ultraviolet light and heat of coloured anodic oxidation coatings

Anodisation de l'aluminium et de ses alliages — Détermination de la solidité comparée à la lumière ultraviolette et à la chaleur des couches anodiques colorées



Reference number ISO 6581:2018(E)

ISO 6581:2018(E)

This is a preview of "ISO 6581:2018". Click here to purchase the full version from the ANSI store.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Con	tents	Page
Forew	vord	iv
Introd	duction	
1	Scope	1
2	Normative references	
3	Terms and definitions	1
4	Principle	
5	Apparatus 5.1 General 5.2 Cabinet 5.3 Ultraviolet light source	
6	Test specimen 6.1 Sampling 6.2 Size 6.3 Treatment before testing 6.4 Specimen arrangement	2 2
7	Procedure 7.1 General 7.2 Standard specimens for control purposes 7.3 Effect of ozone production	3 3
8	Expression of results	3
9	Test report	3

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 79, *Light metals and their alloys*, Subcommittee SC 2, *Organic and anodic oxidation coatings on aluminium*.

This third edition cancels and replaces the second edition (ISO 6581:2010), which has been technically revised to add information about the test specimen.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The test described in this document represents severe exposure to ultraviolet light and, because of its severity, provides a very rapid determination of the comparative light-fastness of coloured anodic oxidation coatings.

It has to be realized, however, that the light emitted by the mercury vapour source used in the test has a discontinuous spectrum and a high content of ultraviolet radiation. Therefore, care is taken when comparing the results of this test with the results of exposure to sunlight.

Considerable heat is generated by the light source and so the test is carried out in such a way that the temperature of the test specimens during the test does not exceed 100 °C.