

This is a preview of "ISO 6624-1:2017". [Click here to purchase the full version from the ANSI store.](#)

Third edition  
2017-04

---

---

## **Internal combustion engines — Piston rings —**

### **Part 1: Keystone rings made of cast iron**

*Moteurs à combustion interne — Segments de piston —  
Partie 1: Segments trapézoïdaux en fonte*



Reference number  
ISO 6624-1:2017(E)

© ISO 2017

This is a preview of "ISO 6624-1:2017". Click here to purchase the full version from the ANSI store.



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
copyright@iso.org  
www.iso.org

This is a preview of "ISO 6624-1:2017". [Click here to purchase the full version from the ANSI store.](#)

## Contents

	Page
<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative reference</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Overview</b> .....	<b>1</b>
<b>5 Ring types and designation examples</b> .....	<b>1</b>
5.1 Type T — Straight faced keystone ring 6°.....	1
5.1.1 General features.....	1
5.1.2 Designation.....	2
5.2 Type TB — Symmetrical barrel faced keystone ring 6°.....	2
5.2.1 General features.....	2
5.2.2 Designation.....	4
5.3 Type TBA — Asymmetrical barrel faced keystone ring 6°.....	4
5.3.1 General features.....	4
5.3.2 Designation.....	5
5.4 Type TM — Taper faced keystone ring 6°.....	5
5.4.1 General features.....	5
5.4.2 Designation.....	6
5.5 Type K — Straight faced keystone ring 15°.....	7
5.5.1 General features.....	7
5.5.2 Designation.....	7
5.6 Type KB — Symmetrical barrel faced keystone ring 15°.....	7
5.6.1 General features.....	7
5.6.2 Designation.....	8
5.7 Type KBA — Asymmetrical barrel faced keystone ring 15°.....	8
5.7.1 General features.....	8
5.7.2 Designation.....	9
5.8 Type KM — Taper faced keystone ring 15°.....	9
5.8.1 General features.....	9
5.8.2 Designation.....	10
<b>6 Common features</b> .....	<b>11</b>
6.1 Type T, TB, TBA, TM, K, KB, KBA, KM rings — Inside chamfered edges (KI).....	11
6.2 Type T, TB, TBA, TM, K, KB, KBA, KM rings (positive twist type) internal bevel or internal step top side.....	11
6.3 Type TM or KM rings with partly cylindrical machined (LM) or lapped (LP) peripheral surface.....	12
6.4 Type T, TB, TBA, TM, K, KB, KBA, KM rings — Plating/coating configuration.....	13
6.4.1 Uncoated rings.....	13
6.4.2 Chromium plated, PVD coated or spray coated rings.....	14
<b>7 Force factors</b> .....	<b>16</b>
<b>8 Dimensions</b> .....	<b>16</b>
<b>Bibliography</b> .....	<b>24</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 34, *Propulsion, powertrain and powertrain fluids*.

This third edition cancels and replaces the second edition (ISO 6624-1:2001), which has been technically revised.

The main changes compared to the previous edition are as follows:

- PVD coating thickness has been included with a new [Table 8](#);
- updates have been made regarding technology improvements.

This is a preview of "ISO 6624-1:2017". [Click here to purchase the full version from the ANSI store.](#)

## Introduction

ISO 6624 belongs to the series of International Standards dealing with piston rings for reciprocating internal combustion engines. Others are ISO 6621, ISO 6622, ISO 6623, ISO 6625, ISO 6626 and ISO 6627 (see Bibliography for details).

The common features and dimensional tables presented in this document constitute a broad range of variables and, in selecting a particular ring type, the designer must bear in mind the conditions under which it will be required to operate.

It is also essential that the designer refer to the specifications and requirements of ISO 6621-3<sup>[4]</sup> and ISO 6621-4 before completing a selection.