

This is a preview of "ISO 6696:1989". [Click here to purchase the full version from the ANSI store.](#)

STANDARD

6696

First edition
1989-12-01

Cycles — Screw threads used in bottom bracket assemblies

Cycles — Filetages utilisés dans les ensembles boîtes de pédalier



Reference number
ISO 6696 : 1989 (E)

This is a preview of "ISO 6696:1989". [Click here to purchase the full version from the ANSI store.](#)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 6696 was prepared by Technical Committee ISO/TC 149, *Cycles*.

© ISO 1989

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

This is a preview of "ISO 6696:1989". [Click here to purchase the full version from the ANSI store.](#)

Introduction

Inch screw threads of British Standard Cycle (B.S.C.) thread profile are used extensively throughout the world for various applications on bicycle components, and have been standardized in national standards. The purpose of this document is to provide an International Standard for the particular screw thread used to assemble bottom bracket cups to bottom brackets on bicycles: it is based on the use of the ISO basic thread profile and complies as far as is practicable with existing International Standards for general purpose screw threads.

The change to an ISO system of screw threads will inevitably take a long time to complete in view of the millions of bicycles now in use which employ B.S.C. thread profile inch screw threads and for which replacement spare parts will be required. For this reason, in order to minimize changes in production methods during the change to the International Standard, and also to secure satisfactory interchangeability with the B.S.C. screw threads now used, the ISO screw thread in this International Standard has the same pitch as that of the 1,37 in \times 24 t.p.i. B.S.C. screw thread it is intended to replace; this means that the pitch is in inch units (turns per inch or t.p.i.) but all other dimensions are specified in metric units.

A 1 3/8 (1,375) in \times 24 t.p.i screw thread of ISO basic profile has been adopted in this International Standard. The basic pitch diameter of this thread differs by only 0,003 mm from that of the 1,37 in \times 24 t.p.i. B.S.C. thread, but, due to the smaller crest truncation of the ISO profile (see figure 1) interference may occur at the major diameter when an ISO cup thread made towards its upper limit is assembled with a B.S.C. shell thread made towards its lower limit on major diameter. The possibility of interference occurring in this manner is considered to be unlikely in practice because of the effect of the manufacturing tolerances (negative on the cup and positive on the shell) and the usual practice of using high-crested screwing taps.

Cycles — Screw threads used in bottom bracket assemblies

1 Scope

This International Standard specifies the thread profile and limits and tolerances for the screw threads used to assemble bottom bracket cups to bottom brackets on bicycles (adjustable cups with right-hand thread, fixed cups with left-hand thread). It is based on

- a) the use of the ISO basic thread profile given in ISO 68;
- b) satisfactory interchangeability with the corresponding British Standard Cycle (B.S.C.) thread; this has required the use of an inch pitch (t.p.i.);
- c) the use of screw thread tolerance grades and tolerance positions given in ISO 965-1;
- d) the use of gauges made to ISO 1502.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 68 : 1973, *ISO general purpose screw threads — Basic profile.*

ISO 965-1 : 1980, *ISO general purpose metric screw threads — Tolerances — Part 1: Principles and basic data.*

ISO 1502 : 1978, *ISO general purpose metric screw threads — Gauging.*

3 Basic ISO thread profile and basic sizes

3.1 Basic profile

The basic profile is that given in ISO 68 and is shown in figure 1. It is the theoretical profile associated with the basic sizes of the major, pitch and minor diameters of the screw thread.

3.2 Basic sizes

The basic major diameter, and the basic pitch and minor diameters determined from the basic profile, are given in table 1.

Table 1 — Basic dimensions

Nominal diameter of thread in	t.p.i.	Basic sizes, mm		
		Major diameter	Pitch diameter	Minor diameter
1,375	24	34,925	34,238	33,779

4 Limits and tolerances

4.1 Fundamental deviations and maximum material limits

The fundamental deviations are applied to the basic diameters and establish the maximum material limits.

For the thread on the cups the fundamental (upper) deviations are negative and correspond to tolerance position "g" on the pitch and minor diameters, and to tolerance position "e" on the major diameter.

For the threads on the shell the fundamental (lower) deviations are zero and correspond to tolerance position "H" on the major, pitch and minor diameters.

NOTE — A fundamental deviation of position "e" on the major diameter of the cups is necessary on thin-walled components to be able to form the thread by rolling, without the removal of metal.

4.2 Tolerance grades, tolerances and limits of size

The application of tolerances to the maximum material limits, negative tolerances for the thread on the shell and positive tolerances for the threads on the cups determines the minimum material limits of size.

The tolerances and limits of size are given in tables 2 and 3 respectively for the cups and the shell. The tolerances are grade 6 except for the major diameter of the cups where it is grade 8, in accordance with ISO 965-1.

The fundamental deviations and tolerance zones are shown in figure 2.