



**ISO 7197**

**Neurosurgical implants — Sterile,  
single-use hydrocephalus shunts**

*Implants neurochirurgicaux — Systèmes de dérivation stériles,  
non réutilisables, pour hydrocéphalie*

**Fourth edition  
2024-07**

This is a preview of ISO 7197:2024. Click [here](#) to purchase the full version from the ANSI store.



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

This is a preview of ISO 7197:2024. [Click here to purchase the full version from the ANSI store.](#)

<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 General requirements for shunts</b> .....	<b>2</b>
4.1 General.....	2
4.2 Radiopacity.....	2
4.3 Biocompatibility.....	2
4.4 Resistance to leakage.....	2
4.5 Control of the implanted shunt.....	3
4.6 Pressure-flow characteristics of the valve, the components and the pre-assembled shunt.....	3
4.7 Identification of shunts in vivo.....	3
4.8 Ability to withstand overpressure.....	3
4.9 Dynamic breaking strength.....	3
4.10 Behaviour under magnetic resonance imaging conditions.....	3
4.11 Bursting pressure.....	4
<b>5 Specific requirements for components</b> .....	<b>4</b>
5.1 Valves.....	4
5.1.1 Reflux performance of shunts connecting the ventricle to the blood system.....	4
5.1.2 Long-term stability.....	4
5.1.3 Influence of the changed posture of the patient on the valve performance.....	4
5.2 Resistance of tubing and components.....	5
<b>6 Marking and labelling of shunts</b> .....	<b>5</b>
<b>7 Packaging</b> .....	<b>5</b>
<b>8 Information supplied by the manufacturer</b> .....	<b>5</b>
8.1 General.....	5
8.2 Instructions for use.....	5
8.3 Implant card.....	6
<b>Bibliography</b> .....	<b>7</b>

This is a preview of ISO 7197:2024. [Click here to purchase the full version from the ANSI store.](#)

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at [www.iso.org/patents](http://www.iso.org/patents). ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 150, *Implants for surgery*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 285, *Non-active surgical implants*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This fourth edition cancels and replaces the third edition (ISO 7197:2006) which has been technically revised.

The main changes are as follows:

- [subclause 4.1](#) has been completely revised;
- terminology has been clarified and references have been updated.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

This is a preview of ISO 7197:2024. [Click here to purchase the full version from the ANSI store.](#)

A shunt is defined as an artificial connection of two compartments inside the body. For the treatment of hydrocephalus, the ventriculo-atrial shunt has been introduced initially to control the intraventricular pressure in the brain of the patients. Today ventriculo-peritoneal shunts are preferably implanted. In special cases, a lumbo-peritoneal shunt is implanted. Normally, a hydrocephalus shunt includes a valve which determines the resulting intraventricular pressure in the brain of the patients and influences the flow rate through the shunt.

The following types of valve are currently commercially available.

- a) Conventional differential-pressure valves (DP valves) are designed as ball-in-cone valves, membrane valves or silicone slit valves: They have one characteristic opening pressure. If the difference pressure between inlet and outlet exceeds this opening pressure the device opens. After opening, the different types of DP valve show a wide range of different flow characteristics. Differences due to a changed posture of the patient have no intended impact on the function of the devices.
- b) Adjustable DP valves act like conventional DP valves: In contrast to non-adjustable devices, they introduce the possibility of a non-invasive readjustment of the opening characteristic after implantation. They do not take into account changes due to a changed posture of the patient.
- c) Gravitation valves or hydrostatic devices that take into account the changed physics in a shunt due to a changed posture of the patient: These devices aim to avoid an unphysiological negative intraventricular pressure in the upright position of the patient, which can be the consequence of the hydrostatic pressure in shunts with adjustable or not adjustable DP valves. There are three different hydrostatic devices commercially available:
  - flow-reducing devices,
  - valves with a so-called “anti-siphon-device” or “siphon-control-device”, and
  - gravity-assisted devices.
- d) Other adjustable valves, for example:
  - gravitation valves, which are adjustable hydrostatic devices present in addition to the characteristics of hydrostatic devices (group 4) with the possibility of a non-invasive readjustment of the opening performance of the device;
  - adjustable anti-siphon-device valves;
  - adjustable flow-reducing valves.

Due to the important technical differences, specific testing procedures are necessary to investigate the performance of the different valves.

The benefit of this document for the surgeon and the patient is to understand the information given by the manufacturer and to obtain standardized information about the performance of a well working product with new design characteristics. The benefit for the manufacturer is to specify the important requirements for shunts as a basis for investigations during development as well as for quality control during manufacture.