Second edition 2014-07-01

Fire detection and alarm systems —

Part 15:

Point-type fire detectors using smoke and heat sensors

Systèmes de détection et d'alarme d'incendie —

Partie 15: Détecteurs linéaires de fumée utilisant une transmission par faisceaux lumineux



ISO 7240-15:2014(E)

This is a preview of "ISO 7240-15:2014". Click here to purchase the full version from the ANSI store.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Contents			Page	
Fore	eword		v	
Intr	oductio	n	vii	
1	Scone	e	1	
2	•	native references		
3	Terms, definitions, and abbreviations 3.1 Terms and definitions			
	3.2	Abbreviated terms		
	_			
4	Requirements			
	4.1 4.2	Compliance Design considerations		
	4.2	Smoke-response value of detectors using scattered or transmitted light		
	4.4	Individual alarm indication	3	
	4.5	Indication of other conditions		
	4.6	Connection of ancillary devices		
	4.7	Monitoring of detachable detectors	3	
	4.8	Manufacturer's adjustments		
	4.9	On-site adjustment of response behaviour		
	4.10	Response to slowly developing fires		
	4.11	Protection against ingress of foreign bodies		
	4.12	Software-controlled detectors	4	
5	Tests			
	5.1	General		
	5.2	Repeatability of smoke response		
	5.3	Directional dependence of smoke response		
	5.4	Directional dependence of heat response		
	5.5	Reproducibility of smoke response		
	5.6	Reproducibility of heat response		
	5.7	Lower limit of heat response		
	5.8	Air movement		
	5.9 5.10	DazzlingVariation in supply parameters (voltage)		
	5.10	Dry heat (operational)		
	5.12	Cold (operational)		
	5.13	Damp heat, cyclic (operational)		
	5.14	Damp heat, steady-state (endurance)		
	5.15	Sulfur dioxide (SO ₂) corrosion (endurance)		
	5.16	Shock (operational)	20	
	5.17	Impact (operational)	21	
	5.18	Vibration, sinusoidal (operational)		
	5.19	Vibration, sinusoidal (endurance)		
	5.20	Electromagnetic compatibility (EMC)		
	5.21	Detectors with more than one smoke sensor — Optional test		
	5.22	Fire sensitivity		
6	Test report			
7	Mark	Marking		
8	Data		29	
Ann	ex A (no	rmative) Compensation for detector drift	30	
Ann	ex B (no	rmative) Smoke tunnel for smoke-response value measurements	35	
Ann	ex C (no	rmative) Heat tunnel for heat-response value measurements	40	

ISO 7240-15:2014(E)

This is a preview of "ISO 7240-15:2014". Click here to purchase the full version from the ANSI store.

Annex D (normative) Apparatus for the dazzling test	41	
Annex E (normative) Apparatus for the impact test	42	
Annex F (normative) Fire test room	44	
Annex G (normative) Open cellulosic (wood) fire (TF1)	46	
Annex H (normative) Smouldering (pyrolysis) wood fire (TF2)	48	
Annex I (normative) Glowing smouldering cotton fire (TF3)	51	
Annex J (normative) Flaming plastics (polyurethane) fire (TF4)	53	
Annex K (normative) Flaming liquid (n-heptane) fire (TF5)	56	
Annex L (normative) Low-temperature black-smoke liquid (decalin) fire (TF8)	58	
Annex M (informative) Construction of the measuring ionization chamber		
Annex N (informative) Construction of the heat tunnel	63	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 21, *Equipment for fire protection and fire fighting*, Subcommittee SC 3, *Fire detection and alarm systems*.

This second edition cancels and replaces the first edition (ISO 7240-15:2004), which has been technically revised.

ISO 7240 consists of the following parts, under the general title *Fire detection and alarm systems*:

- Part 1: General and definitions
- Part 2: Control and indicating equipment
- Part 3: Audible alarm devices
- Part 4: Power supply equipment
- Part 5: Point-type heat detectors
- Part 6: Carbon monoxide fire detectors using electro-chemical cells
- Part 7: Point-type smoke detectors using scattered light, transmitted light or ionization
- Part 8: Carbon monoxide fire detectors using an electro-chemical cell in combination with a heat sensor
- Part 9: Test fires for fire detectors [Technical Specification]
- Part 10: Point-type flame detectors
- Part 11: Manual call points
- Part 12: Line type smoke detectors using a transmitted optical beam
- Part 13: Compatibility assessment of system components

ISO 7240-15:2014(E)

This is a preview of "ISO 7240-15:2014". Click here to purchase the full version from the ANSI store.

- Part 14: Design, installation, commissioning and service of fire detection and fire alarm systems in and around buildings
- Part 15: Point-type fire detectors using smoke and heat sensors
- Part 16: Sound system control and indicating equipment
- Part 17: Short-circuit isolators
- Part 18: Input/output devices
- Part 19: Design, installation, commissioning and service of sound systems for emergency purposes
- Part 20: Aspirating smoke detectors
- Part 21: Routing equipment
- Part 22: Smoke-detection equipment for ducts
- Part 23: Visual alarm devices
- Part 24: Sound-system loudspeakers
- Part 25: Components using radio transmission paths
- Part 27: Point-type fire detectors using a scattered-light, transmitted-light or ionization smoke sensor, an electrochemical-cell carbon-monoxide sensor and a heat sensor
- Part 28: Fire protection control equipment

The following part is under preparation:

Part 29: Video fire detectors

Introduction

This part of ISO 7240 is prepared by ISO/TC 21/SC 3, the secretariat of which is held by SA, and is based on ISO 7240-15:2004.

Point-type fire detectors using smoke and heat sensors are general purpose fire detectors for installation in and around buildings. Multi-sensor detectors respond to a broad range of fires and can be designed to achieve high stability against deceptive phenomena that can result in unwanted alarms.

A fire detection and alarm system is required to function satisfactorily not only in the event of fire, but also during and after exposure to conditions it is likely to meet in practice, including corrosion, vibration, direct impact, indirect shock and electromagnetic interference. Specific tests are intended to assess the performance of detectors under such conditions.

This edition introduces a requirement that smoke sensors that operate on the principle of scattered or transmitted light to be marked with one of two possible nominal response threshold bands. The availability of two of response threshold bands provides installation designers with a detector selection choice to further reduce the risk of unwanted alarms in installations where unfavourable environmental conditions are present.

This edition introduces additional requirements for smoke detectors with more than one smoke sensor.