

This is a preview of "ISO 7870-6:2016". [Click here to purchase the full version from the ANSI store.](#)

First edition
2016-02-15

Control charts — Part 6: EWMA control charts

Cartes de contrôle —

Partie 6: Cartes de contrôle de EWMA



Reference number
ISO 7870-6:2016(E)

© ISO 2016



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

This is a preview of "ISO 7870-6:2016". Click here to purchase the full version from the ANSI store.

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Symbols and abbreviated terms	1
4 EWMA for inspection by variables	2
4.1 General.....	2
4.2 Weighted average explained.....	3
4.3 Control limits for EWMA control chart.....	4
4.4 Construction of EWMA control chart.....	4
4.5 Example.....	6
5 Choice of the control chart	9
5.1 Shewhart control chart versus EWMA control chart.....	9
5.2 Average run length.....	10
5.3 Choice of parameters for EWMA control chart.....	10
5.3.1 Choice of λ	10
5.3.2 Choice of L_z	11
5.3.3 Calculation for n	11
5.3.4 Example.....	12
6 Procedure for implementing the EWMA control chart	12
7 Sensitivity of the EWMA to non-normality	13
8 Advantages and limitations	13
8.1 Advantages.....	13
8.2 Limitations.....	13
Annex A (informative) Application of the EWMA control chart	14
Annex B (normative) EWMA control chart for controlling a proportion of nonconforming units ...18	18
Annex C (normative) EWMA control charts for a number of nonconformities	20
Annex D (informative) Control chart effectiveness	22
Bibliography	26

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT), see the following URL: [Foreword — Supplementary information](#).

The committee responsible for this document is ISO/TC 69, *Applications of statistical methods*, Subcommittee SC 4, *Applications of statistical methods in process management*.

ISO 7870 consists of the following parts, under the general title *Control charts*:

- *Part 1: General guidelines*
- *Part 2: Shewhart control charts*
- *Part 3: Acceptance control charts*
- *Part 4: Cumulative sum charts*
- *Part 5: Specialized control charts*
- *Part 6: EWMA control charts*

A future part on charting techniques for short runs and small mixed batches is planned.

This is a preview of "ISO 7870-6:2016". [Click here to purchase the full version from the ANSI store.](#)

Introduction

Shewhart control charts are the most widespread statistical control methods used for controlling a process, but they are slow in signalling shifts of small magnitude in the process parameters. The exponentially weighted moving average^[10] (EWMA) control chart makes possible faster detection of small to moderate shifts.

The Shewhart control chart is simple to implement and it rapidly detects shifts of major magnitude. However, it is fairly ineffective for detecting shifts of small or moderate magnitude. It happens quite often that the shift of the process is slow and progressive (in case of continuous processes in particular); this shift has to be detected very early in order to react before the process deviates seriously from its target value. There are two possibilities for improving the effectiveness of the Shewhart control charts with respect to small and moderate shifts.

- The simplest, but not the most economical possibility is to increase the subgroup size. This may not always be possible due to low production rate; time consuming or too costly testing. As a result, it may not be possible to draw samples of size more than 1 or 2.
- The second possibility is to take into account the results preceding the control under way in order to try to detect the existence of a shift in the production process. The Shewhart control chart takes into account only the information contained in the last sample observation and it ignores any information given by the entire sequence of points. This feature makes the Shewhart control chart relatively insensitive to small process shifts. Its effectiveness may be improved by taking into account the former results.

Where it is desired to detect slow, progressive shifts, it is preferable to use specific charts which take into account the past data and which are effective with a moderate control cost. Two very effective alternatives to the Shewhart control chart in such situations are

- a) Cumulative Sum (CUSUM) control chart. This chart is described in ISO 7870-4. The CUSUM control chart reacts more sensitively than the X-bar chart to a shift of the mean value in the range of half or two sigma. If one plots the cumulative sum of deviations of successive sample means from a specified target, even minor, permanent shifts in the process mean will eventually lead to a sizable cumulative sum of deviations. Thus, this chart is particularly well-suited for detecting such small permanent shifts that may go undetected when using the X-bar chart.
- b) Exponentially Weighted Moving Average (EWMA) control chart which is covered by this document. This chart is presented like the Shewhart control chart; however, instead of placing on the chart the successive averages of the samples, one monitors a weighted average of the current average and of the previous averages.

EWMA control charts are generally used for detecting small shifts in the process mean. They will detect shifts of half sigma to two sigma much faster. They are, however, slower in detecting large shifts in the process mean. EWMA control charts may also be preferred when the subgroups are of size $n = 1$.

The joint use of an EWMA control chart with a small value of lambda and a Shewhart control chart has been recommended as a means of guaranteeing fast detection of both small and large shifts. The EWMA control chart monitors only the process mean; monitoring the process variability requires the use of some other technique.