

This is a preview of "ISO 80000-8:2007". [Click here to purchase the full version from the ANSI store.](#)

First edition
2007-06-01

Corrected version
2007-08-15

Quantities and units — Part 8: Acoustics

*Grandeurs et unités —
Partie 8: Acoustique*

Reference number
ISO 80000-8:2007(E)



This is a preview of "ISO 80000-8:2007". [Click here to purchase the full version from the ANSI store.](#)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

This is a preview of "ISO 80000-8:2007". [Click here to purchase the full version from the ANSI store.](#)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 80000-8 was prepared by Technical Committee ISO/TC 12, *Quantities, units, symbols, conversion factors*, in collaboration with IEC/TC 25, *Quantities and units, and their letter symbols*.

This first edition cancels and replaces the second edition of ISO 31-7:1992 and ISO 31-7:1992/Amd.1:1998. The major technical changes from the previous standards are the following:

- the presentation of *numerical statements* has been changed;
- the *special remarks* in the Introduction have been changed;
- the *normative references* have been changed;
- some quantities have been added to the list of quantities and some quantities have been deleted.

This corrected version of ISO 80000-8:2007 incorporates the following corrections.

- 0.3.1 e) The sentence was reworded.
- 8-3.b In the definition, the sign “=” was replaced by the sign “:=” after “dec”.
- 8-18 In the definition and in the remarks, the subscript “*f*” was deleted.
In the definition, “frequency-weighted” was deleted.
- 8-22 In the definition and in the remarks, the subscript “*ft*” was deleted.
In the definition, “frequency- and time-weighted” was deleted.
In the remarks, “, or both” was added at the end of the first line.
In the remarks, “and/or specific frequency bands” was changed to “or specific frequency bands or both” in the second line.
- 8-23 In the definition, “is” was added after “reference value”.
- 8-24 In the definition, “is” was added after “reference value”.

ISO 80000 consists of the following parts, under the general title *Quantities and units*:

- *Part 1: General*
- *Part 2: Mathematical signs and symbols to be used in the natural sciences and technology*
- *Part 3: Space and time*
- *Part 4: Mechanics*

This is a preview of "ISO 80000-8:2007". [Click here to purchase the full version from the ANSI store.](#)

- *Part 5: Thermodynamics*
- *Part 7: Light*
- *Part 8: Acoustics*
- *Part 9: Physical chemistry and molecular physics*
- *Part 10: Atomic and nuclear physics*
- *Part 11: Characteristic numbers*
- *Part 12: Solid state physics*

IEC 80000 consists of the following parts, under the general title *Quantities and units*:

- *Part 6: Electromagnetism*
- *Part 13: Information science and technology*
- *Part 14: Telebiometrics related to human physiology*

This is a preview of "ISO 80000-8:2007". [Click here to purchase the full version from the ANSI store.](#)

Introduction

0.1 Arrangements of the tables

The tables of quantities and units in this International Standard are arranged so that the quantities are presented on the left-hand pages and the units on the corresponding right-hand pages.

All units between two full lines on the right-hand pages belong to the quantities between the corresponding full lines on the left-hand pages.

Where the numbering of an item has been changed in the revision of a part of ISO 31, the number in the preceding edition is shown in parentheses on the left-hand page under the new number for the quantity; a dash is used to indicate that the item in question did not appear in the preceding edition.

0.2 Tables of quantities

The names in English and in French of the most important quantities within the field of this International Standard are given together with their symbols and, in most cases, their definitions. These names and symbols are recommendations. The definitions are given for identification of the quantities in the International System of Quantities (ISQ), listed on the left hand pages of the table; they are not intended to be complete.

The scalar, vectorial or tensorial character of quantities is pointed out, especially when this is needed for the definitions.

In most cases only one name and only one symbol for the quantity are given; where two or more names or two or more symbols are given for one quantity and no special distinction is made, they are on an equal footing. When two types of italic letters exist (for example as with ϑ and θ ; φ and ϕ ; a and α ; g and g) only one of these is given. This does not mean that the other is not equally acceptable. It is not recommended to give such variants different meanings. A symbol within parentheses implies that it is a reserve symbol, to be used when, in a particular context, the main symbol is in use with a different meaning.

In this English edition, the quantity names in French are printed in an italic font, and are preceded by *fr.* The gender of the French name is indicated by (m) for masculine and (f) for feminine, immediately after the noun in the French name.

0.3 Tables of units

0.3.1 General

The names of units for the corresponding quantities are given together with the international symbols and the definitions. These unit names are language-dependent, but the symbols are international and the same in all languages. For further information, see the SI Brochure (8th edition 2006) from BIPM and ISO 80000-1¹⁾.

The units are arranged in the following way:

- a) The coherent SI units are given first. The SI units have been adopted by the General Conference on Weights and Measures (Conférence Générale des Poids et Mesures, CGPM). The use of coherent SI units

1) To be published.

This is a preview of "ISO 80000-8:2007". [Click here to purchase the full version from the ANSI store.](#)

is recommended; decimal multiples and submultiples formed with the SI prefixes are recommended, even though not explicitly mentioned.

- b) Some non-SI units are then given, being those accepted by the International Committee for Weights and Measures (Comité International des Poids et Mesures, CIPM), or by the International Organization of Legal Metrology (Organisation Internationale de Métrologie Légale, OIML), or by ISO and IEC, for use with the SI. Such units are separated from the SI units in the item by use of a broken line between the SI units and the other units.
- c) Non-SI units currently accepted by the CIPM for use with the SI are given in small print (smaller than the text size) in the "Conversion factors and remarks" column.
- d) Non-SI units that are not recommended are given only in annexes in some parts of this International Standard. These annexes are informative, in the first place for the conversion factors, and are not integral parts of the standard. These deprecated units are arranged in two groups:
 - 1) units in the CGS system with special names;
 - 2) units based on the foot, pound, second, and some other related units.
- e) Other non-SI units are given for information, especially regarding the conversion factors, in informative annexes in some parts of this International Standard.

0.3.2 Remark on units for quantities of dimension one, or dimensionless quantities

The coherent unit for any quantity of dimension one, also called a dimensionless quantity, is the number one, symbol 1. When the value of such a quantity is expressed, the unit symbol 1 is generally not written out explicitly.

EXAMPLE 1 Refractive index $n = 1,53 \times 1 = 1,53$

Prefixes shall not be used to form multiples or submultiples of this unit. Instead of prefixes, powers of 10 are recommended.

EXAMPLE 2 Reynolds number $Re = 1,32 \times 10^3$

Considering that plane angle is generally expressed as the ratio of two lengths and solid angle as the ratio of two areas, in 1995 the CGPM specified that, in the SI, the radian, symbol rad, and steradian, symbol sr, are dimensionless derived units. This implies that the quantities plane angle and solid angle are considered as derived quantities of dimension one. The units radian and steradian are thus equal to one; they may either be omitted, or they may be used in expressions for derived units to facilitate distinction between quantities of different kinds but having the same dimension.

0.4 Numerical statements in this International Standard

The sign = is used to denote "is exactly equal to", the sign \approx is used to denote "is approximately equal to", and the sign := is used to denote "is by definition equal to".

Numerical values of physical quantities that have been experimentally determined always have an associated measurement uncertainty. This uncertainty should always be specified. In this International Standard, the magnitude of the uncertainty is represented as in the following example.

EXAMPLE $l = 2,347\ 82(32)\ \text{m}$

In this example, $l = a(b)\ \text{m}$, the numerical value of the uncertainty b indicated in parentheses is assumed to apply to the last (and least significant) digits of the numerical value a of the length l . This notation is used when b represents the standard uncertainty (estimated standard deviation) in the last digits of a . The numerical example given above may be interpreted to mean that the best estimate of the numerical value of the length l (when l is expressed in the unit metre) is 2,347 82, and that the unknown value of l is believed to lie between $(2,347\ 82 - 0,000\ 32)\ \text{m}$ and $(2,347\ 82 + 0,000\ 32)\ \text{m}$, with a probability determined by the standard uncertainty 0,000 32 m and the normal probability distribution of the values of l .

This is a preview of "ISO 80000-8:2007". [Click here to purchase the full version from the ANSI store.](#)

0.5 Special remarks

0.5.1 General

In the explanations in the "Definition" column for quantities, it is assumed that systems are linear and that non-linear effects and effects due to anisotropy and superimposed flow are sufficiently small, that they may be neglected. Root-mean-square values may be indicated by the subscript "eff".

0.5.2 Remark on logarithmic quantities and their units

Quantities are independent of the choice of units in which the values of the quantities are expressed. Derived units are expressed in terms of base units according to the equations between the corresponding quantities. In strict quantity calculus, it is therefore a circular definition if a unit is included in the definition of a quantity. This could, however, be done if the unit is defined elsewhere. In most practical applications in acoustics, logarithmic quantities are defined as expressed in the unit decibel, dB. This practice is applied in ISO 80000-8. For the fundamental definitions of logarithmic quantities, see ISO 80000-3:2006, items 3-21 and 3-22.

This is a preview of "ISO 80000-8:2007". [Click here to purchase the full version from the ANSI store.](#)