First edition 2003-12-01

# Glass-reinforced thermosetting plastics (GRP) pipes and fittings — Test methods to prove the design of bolted flange joints

Tubes et raccords en plastiques thermodurcissables renforcés de verre (PRV) — Méthodes d'essai pour confirmer la conception des assemblages à brides boulonnées



Reference number ISO 8483:2003(E)

#### **PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org Published in Switzerland

## Contents

Forewordiv		
Introductionv		
1	Scope	1
2	Principle	1
3 3.1 3.2 3.3 3.4 3.5	Apparatus End-sealing devices Supports Source of hydrostatic pressure Means of measuring the gauge pressure Vacuum pump or equivalent	2 2 2 2 2 2 2
3.6 4 4.1 4.2	Bolt torque test apparatus Test pieces Test arrangement Number of test pieces	2 3 3 4
5	Conditioning	4
6	Test temperature	4
7 7.1 7.2 7.3	Procedures General Leaktightness when subjected to an external pressure differential Initial leakage	4 4 5 5
7.4 7.5 7.6 7.7 7.8	Resistance to internal pressure Resistance of the joint to bending and pressure including hydrostatic end thrust Short-duration resistance to internal pressure including hydrostatic end thrust Resistance to bolt-tightening torque Testing excluding hydrostatic end thrust (see 7.1)	- 7 7 8 9 9
8	Test report	9
Annex	A (normative) Equations for calculating the additional force, <i>F</i> , and limiting deflection, <i>Δ</i> , for the bending test described in 7.5	1

### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 8483 was prepared by Technical Committee ISO/TC 138, *Plastics pipes, fittings and valves for the transport of fluids*, Subcommittee SC 6, *Reinforced plastics pipes and fittings for all applications*.

#### Introduction

In a pipework system, pipes and fittings of different nominal pressures and stiffness may be used.

A joint may be made between pipes and/or fittings and should be designed such that its performance is equal to or better than the requirements of the pipeline, but not necessarily of the components being joined.

The requirements for the assembly of the joint are not included in this standard, but they should be in accordance with the manufacturer's recommendations.