Third edition 2012-05-15

## Corrosion tests in artificial atmospheres — Salt spray tests

Essais de corrosion en atmosphères artificielles — Essais aux brouillards salins



Reference number ISO 9227:2012(E)



## **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

| Cont         | <b>ents</b> Pag  | е |  |
|--------------|--|---|--|
| Forewordiv   |  |   |  |
| Introdu      | Introductionv  |   |  |
| 1            | Scope  | 1 |  |
| 2            | Normative references   | 1 |  |
| 3            | Test solutions   | 2 |  |
| 3.1          | Preparation of the sodium chloride solution  |   |  |
| 3.2<br>3.3   | pH adjustment Filtration   |   |  |
| 4            | Apparatus  |   |  |
| 4.1          | Component protection   | 3 |  |
| 4.2<br>4.3   | Spray cabinet Heater and temperature control   |   |  |
| 4.4          | Spraying device  |   |  |
| 4.5<br>4.6   | Collecting devices Re-use  |   |  |
| -            | Method for evaluating cabinet corrosivity  |   |  |
| 5<br>5.1     | General  |   |  |
| 5.2          | NSS test   |   |  |
| 5.3<br>5.4   | AASS test  |   |  |
| 6            | Test specimens   |   |  |
| 7            | Arrangement of the test specimens  |   |  |
| 8            | Operating conditions   |   |  |
| 9            | Duration of tests  |   |  |
| 10           | Treatment of specimens after test  |   |  |
| 11           | Evaluation of results  |   |  |
| 12           | Test report  |   |  |
|              | A (informative) Schematic diagram of one possible design of spray cabinet with means for               | Ü |  |
| AIIIICA      | treating fog exhaust and drain   | 2 |  |
| Annex        | B (informative) Complementary method for evaluating cabinet corrosivity using zinc reference specimens | 4 |  |
| Annex        | C (normative) Preparation of panels with organic coatings for testing1                                 | 6 |  |
| Annex        | D (normative) Required supplementary information for testing test panels with organic coatings 1       | 7 |  |
| Bibliography |  |   |  |

## **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 9227 was prepared by Technical Committee ISO/TC 156, Corrosion of metals and alloys.

This third edition cancels and replaces the second edition (ISO 9227:2006), of which it constitutes a minor revision.

## Introduction

There is seldom a direct relation between resistance to the action of salt spray and resistance to corrosion in other media, because several factors influencing the progress of corrosion, such as the formation of protective films, vary greatly with the conditions encountered. Therefore, the test results should not be regarded as a direct guide to the corrosion resistance of the tested metallic materials in all environments where these materials might be used. Also, the performance of different materials during the test should not be taken as a direct guide to the corrosion resistance of these materials in service.

Nevertheless, the method described gives a means of checking that the comparative quality of a metallic material, with or without corrosion protection, is maintained.

Salt spray tests are generally suitable as corrosion protection tests for rapid analysis for discontinuities, pores and damage in organic and inorganic coatings. In addition, for quality control purposes, comparison can be made between specimens coated with the same coating. As comparative tests, however, salt spray tests are only suitable if the coatings are sufficiently similar in nature.

It is often not possible to use results gained from salt spray testing as a comparative guide to the long-term behaviour of different coating systems, since the corrosion stress during these tests differs significantly from the corrosion stresses encountered in practice.