

Third edition
2016-07-15

Identification cards — Contactless integrated circuit cards — Proximity cards —

Part 2: Radio frequency power and signal interface

*Cartes d'identification — Cartes à circuit(s) intégré(s) sans contact —
Cartes de proximité —*

Partie 2: Interface radiofréquence et des signaux de communication



Reference number
ISO/IEC 14443-2:2016(E)

© ISO/IEC 2016



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

This is a preview of "ISO/IEC 14443-2:2016". Click here to purchase the full version from the ANSI store.

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	2
5 General considerations	4
5.1 Initial dialogue.....	4
5.2 Compliance.....	4
5.2.1 PICC compliance.....	4
5.2.2 PCD compliance.....	4
6 Power transfer	5
6.1 Frequency.....	5
6.2 Operating field strength.....	5
7 Signal interface	7
8 Communication signal interface Type A	8
8.1 Communication PCD to PICC.....	8
8.1.1 Bit rate.....	8
8.1.2 Modulation.....	9
8.1.3 Bit representation and coding.....	16
8.2 Communication PICC to PCD.....	17
8.2.1 Bit rate.....	17
8.2.2 Load modulation.....	17
8.2.3 Subcarrier.....	21
8.2.4 Subcarrier modulation.....	21
8.2.5 Bit representation and coding.....	22
9 Communication signal interface Type B	22
9.1 Communication PCD to PICC.....	22
9.1.1 Bit rate.....	22
9.1.2 Modulation.....	23
9.1.3 Bit representation and coding.....	31
9.2 Communication PICC to PCD.....	31
9.2.1 Bit rate.....	31
9.2.2 Load modulation.....	31
9.2.3 Subcarrier.....	31
9.2.4 Subcarrier modulation.....	31
9.2.5 Bit representation and coding.....	31
10 Electromagnetic disturbance levels	32
10.1 PCD limits.....	32
10.2 PICC limits.....	32
Annex A (normative) Bit rates of $3fc/4$, fc, $3fc/2$ and $2fc$ from PCD to PICC	34
Annex B (informative) Complex envelope and constellation diagram	42
Annex C (informative) Inter Symbol Interference	43

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/IEC JTC 1, *Information technology*, Subcommittee SC 17, *Cards and personal identification*.

This third edition cancels and replaces the second edition (ISO/IEC 14443-2:2010), which has been technically revised.

It also incorporates the Amendments ISO/IEC 14443-2:2010/Amd 1:2011, ISO/IEC 14443-2:2010/Amd 2:2012 and ISO/IEC 14443-2:2010/Amd 3:2012.

ISO/IEC 14443 consists of the following parts, under the general title *Identification cards — Contactless integrated circuit cards — Proximity cards*:

- *Part 1: Physical characteristics*
- *Part 2: Radio frequency power and signal interface*
- *Part 3: Initialization and anticollision*
- *Part 4: Transmission protocol*

This is a preview of "ISO/IEC 14443-2:2016". [Click here to purchase the full version from the ANSI store.](#)

Introduction

ISO/IEC 14443 is one of a series of International Standards describing the parameters for identification cards as defined in ISO/IEC 7810 and the use of such cards for international interchange.

This part of ISO/IEC 14443 describes the electrical characteristics of two types of contactless interface between a proximity card and a proximity coupling device. The interface includes both power and bi-directional communication. It is intended to be used in conjunction with other parts of ISO/IEC 14443.

Contactless card standards cover a variety of types as embodied in ISO/IEC 10536 (close-coupled cards), ISO/IEC 14443 (proximity cards) and ISO/IEC 15693 (vicinity cards). These are intended for operation when very near, nearby and at a longer distance from associated coupling devices, respectively.