

ISO/IEC 15444-1**Information technology — JPEG
2000 image coding system —****Part 1:
Core coding system**

*Technologies de l'information — Système de codage d'images
JPEG 2000 —*

Partie 1: Système de codage de noyau

**Fifth edition
2024-11**

This is a preview of ISO/IEC 15444-1:2024. Click [here](#) to purchase the full version from the ANSI store.



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted.

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and <https://patents.iec.ch>. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by ITU-T (as ITU-T T.800) and drafted in accordance with its editorial rules, in collaboration with Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

This fifth edition cancels and replaces the fourth edition (ISO/IEC 15444-1:2019), which has been technically revised.

The main changes are as follows:

- addition of Annex N, which lists a registration request for media type image/j2c
- specify that the Mastering Display Metadata Box of Annex M is optional and has no defaults, reflecting industry practice
- remove obsolete and erroneous reference to IETF RFC 2279
- clarify semantics of CE_{poc}ⁱ
- update reference to ISO/CIE 11664-1, Rec. ITU-R BT.601 and Rec. ITU-R BT.709
- remove unused JPEG Utilities Registration Authority (JURA) term
- specify the value of Rsiz when extended capabilities are present but no profile is signalled.

A list of all parts in the ISO/IEC 15444 series can be found on the ISO and IEC websites.

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

Information technology – JPEG 2000 image coding system: Core coding system

Summary

This Recommendation | International Standard defines a set of lossless (bit-preserving) and lossy compression methods for coding bi-level, continuous-tone grey-scale, palletized colour, or continuous-tone colour digital still images.

This Recommendation | International Standard:

- specifies decoding processes for converting compressed image data to reconstructed image data;
- specifies a codestream syntax containing information for interpreting the compressed image data;
- specifies a file format;
- provides guidance on encoding processes for converting source image data to compressed image data;
- provides guidance on how to implement these processes in practice.

This edition includes the following changes relative to the previous edition:

- addition of Annex N, which lists a registration request for media type image/jpeg
- specify that the Mastering Display Metadata Box of Annex M is optional and has no defaults, reflecting industry practice
- remove obsolete and erroneous reference to IETF RFC 2279
- clarify semantics of CEpicⁱ
- update reference to ISO/CIE 11664-1, Rec. ITU-R BT.601 and Rec. ITU-R BT.709
- remove unused JPEG Utilities Registration Authority (JURA) term
- specify the value of Rsiz when extended capabilities are present but no profile is signalled

NOTE – As this specification was first published as common text only after ISO/IEC JTC1 had approved the first edition in 2000, edition numbers in the ITU and ISO/IEC versions are offset by one. This is the fourth edition of ITU-T T.800 and the fifth edition of ISO/IEC 15444-1.

History *

Edition	Recommendation	Approval	Study Group	Unique ID
1.0	ITU-T T.800	2002-08-29	16	11.1002/1000/5281
1.1	ITU-T T.800 (2002) Amd. 1	2005-09-13	16	11.1002/1000/8576
1.2	ITU-T T.800 (2002) Cor. 1	2007-01-13	16	11.1002/1000/9048
1.3	ITU-T T.800 (2002) Cor. 2	2007-08-29	16	11.1002/1000/9231
1.4	ITU-T T.800 (2002) Amd. 2	2009-03-16	16	11.1002/1000/9719
1.5	ITU-T T.800 (2002) Amd. 3	2010-06-22	16	11.1002/1000/11002
1.6	ITU-T T.800 (2002) Amd. 4	2011-05-14	16	11.1002/1000/11313
1.7	ITU-T T.800 (2002) Amd. 5	2012-01-13	16	11.1002/1000/11469
1.8	ITU-T T.800 (2002) Amd. 6	2013-03-16	16	11.1002/1000/11882
1.9	ITU-T T.800 (2002) Cor. 3	2014-10-14	16	11.1002/1000/12301
1.10	ITU-T T.800 (2002) Cor. 4	2014-10-14	16	11.1002/1000/12302
1.11	ITU-T T.800 (2002) Amd. 7	2014-10-14	16	11.1002/1000/12300
2.0	ITU-T T.800	2015-11-29	16	11.1002/1000/12682
3.0	ITU-T T.800 (V3)	2019-06-13	16	11.1002/1000/13911
4.0	ITU-T T.800 (V4)	2024-07-14	16	11.1002/1000/15939

* To access the Recommendation, type the URL <https://handle.itu.int/> in the address field of your web browser, followed by the Recommendation's unique ID.

This is a preview of ISO/IEC 15444-1:2024. Click here to purchase the full version from the ANSI store.

telecommunications, and information and communication technologies (ICTs). The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure, e.g., interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had received notice of intellectual property, protected by patents/software copyrights, which may be required to implement this Recommendation. However, implementers are cautioned that this may not represent the latest information and are therefore strongly urged to consult the appropriate ITU-T databases available via the ITU-T website at <http://www.itu.int/ITU-T/ipr/>.

© ITU 2024

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

1	Scope	1
2	References	1
	2.1 Identical Recommendations International Standards	1
	2.2 Additional references	1
3	Definitions	2
4	Abbreviations and symbols	6
	4.1 Abbreviations	6
	4.2 Symbols	7
5	General description	8
	5.1 Purpose	8
	5.2 Codestream	8
	5.3 Coding principles	8
6	Encoder requirements	10
7	Decoder requirements	10
	7.1 Codestream syntax requirements	10
	7.2 Optional file format requirements	11
8	Implementation requirements	11
Annex A	Codestream syntax	12
	A.1 Markers, marker segments and headers	12
	A.1.1 Types of markers and marker segments	12
	A.1.2 Syntax similarity with Rec. ITU-T T.81 ISO/IEC 10918-1	12
	A.1.3 Marker and marker segment and codestream rules	13
	A.1.4 Key to graphical descriptions (informative)	13
	A.2 Information in the marker segments	14
	A.3 Construction of the codestream	15
	A.4 Delimiting markers and marker segments	19
	A.4.1 Start of codestream (SOC)	19
	A.4.2 Start of tile-part (SOT)	19
	A.4.3 Start of data (SOD)	20
	A.4.4 End of codestream (EOC)	20
	A.5 Fixed information marker segment	20
	A.5.1 Image and tile size (SIZ)	21
	A.5.2 Extended Capabilities (CAP)	24
	A.5.3 Profile (PRF)	25
	A.6 Functional marker segments	26
	A.6.1 Coding style default (COD)	26
	A.6.2 Coding style component (COC)	29
	A.6.3 Region of interest (RGN)	31
	A.6.4 Quantization default (QCD)	32
	A.6.5 Quantization component (QCC)	33
	A.6.6 Progression order change (POC)	34
	A.7 Pointer marker segments	36
	A.7.1 Tile-part lengths (TLM)	36
	A.7.2 Packet length, main header (PLM)	37
	A.7.3 Packet length, tile-part header (PLT)	38
	A.7.4 Packed packet headers, main header (PPM)	39
	A.7.5 Packed packet headers, tile-part header (PPT)	40
	A.8 In-bit-stream marker and marker segments	40
	A.8.1 Start of packet (SOP)	40
	A.8.2 End of packet header (EPH)	41
	A.9 Informational marker segments	41
	A.9.1 Component registration (CRG)	42
	A.9.2 Comment (COM)	42
	A.10 Codestream restrictions conforming to this Recommendation International Standard	43
	A.10.1 Codestream restrictions for digital cinema applications including archiving	44

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

Annex B Image and compressed image data ordering.....	59
B.1 Introduction to image data structure concepts.....	59
B.2 Component mapping to the reference grid.....	59
B.3 Image area division into tiles and tile-components.....	61
B.4 Example of the mapping of components to the reference grid (informative).....	62
B.5 Transformed tile-component division into resolution levels and sub-bands.....	65
B.6 Division of resolution levels into precincts.....	66
B.7 Division of the sub-bands into code-blocks.....	67
B.8 Layers.....	68
B.9 Packets.....	69
B.10 Packet header information coding.....	70
B.10.1 Bit-stuffing routine.....	71
B.10.2 Tag trees.....	71
B.10.3 Zero length packet.....	72
B.10.4 Code-block inclusion.....	72
B.10.5 Zero bit-plane information.....	72
B.10.6 Number of coding passes.....	72
B.10.7 Length of the compressed image data from a given code-block.....	73
B.10.8 Order of information within packet header.....	73
B.11 Tile and tile-parts.....	75
B.12 Progression order.....	76
B.12.1 Progression order determination.....	76
B.12.2 Progression order volumes.....	78
B.12.3 Progression order change signalling.....	79
Annex C Arithmetic entropy coding.....	80
C.1 Binary encoding (informative).....	80
C.1.1 Recursive interval subdivision (informative).....	80
C.1.2 Coding conventions and approximations (informative).....	80
C.2 Description of the arithmetic encoder (informative).....	81
C.2.1 Encoder code register conventions (informative).....	82
C.2.2 Encoding a decision (ENCODE) (informative).....	83
C.2.3 Encoding a 1 or a 0 (CODE1 and CODE0) (informative).....	83
C.2.4 Encoding an MPS or LPS (CODEMPS and CODELPS) (informative).....	84
C.2.5 Probability estimation.....	86
C.2.6 Renormalization in the encoder (RENORME) (informative).....	87
C.2.7 Compressed image data output (BYTEOUT) (informative).....	88
C.2.8 Initialization of the encoder (INITENC) (informative).....	89
C.2.9 Termination of coding (FLUSH) (informative).....	90
C.3 Arithmetic decoding procedure.....	92
C.3.1 Decoder code register conventions.....	93
C.3.2 Decoding a decision (DECODE).....	93
C.3.3 Renormalization in the decoder (RENORMD).....	96
C.3.4 Compressed image data input (BYTEIN).....	97
C.3.5 Initialization of the decoder (INITDEC).....	98
C.3.6 Resetting arithmetic coding statistics.....	98
C.3.7 Saving arithmetic coding statistics.....	98
Annex D Coefficient bit modelling.....	99
D.1 Code-block scan pattern within code-blocks.....	99
D.2 Coefficient bits and significance.....	99
D.2.1 General case notations.....	99
D.2.2 Notation in the case with ROI.....	100
D.3 Decoding passes over the bit-planes.....	100
D.3.1 Significance propagation decoding pass.....	100
D.3.2 Sign bit decoding.....	101
D.3.3 Magnitude refinement pass.....	102
D.3.4 Cleanup pass.....	102
D.3.5 Example of coding passes and significance propagation (informative).....	103
D.4 Initializing and terminating.....	104

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

D.4.2	Arithmetic coder termination	104
D.4.3	Length computation (informative)	105
D.5	Error resilience segmentation symbol	105
D.6	Selective arithmetic coding bypass	105
D.7	Vertically causal context formation	106
D.8	Flow diagram of the code-block coding	107
Annex E	Quantization	109
E.1	Inverse quantization procedure	109
E.1.1	Irreversible transformation	109
E.1.2	Reversible transformation	110
E.2	Scalar coefficient quantization (informative)	110
Annex F	Discrete wavelet transformation of tile-components	112
F.1	Tile-component parameters	112
F.2	Discrete wavelet transformations	112
F.2.1	Low-pass and high-pass filtering (informative)	112
F.2.2	Decomposition levels	112
F.2.3	Discrete wavelet filters (informative)	112
F.3	Inverse discrete wavelet transformation	112
F.3.1	The IDWT procedure	112
F.3.2	The 2D_SR procedure	114
F.3.3	The 2D_INTERLEAVE procedure	115
F.3.4	The HOR_SR procedure	117
F.3.5	The VER_SR procedure	118
F.3.6	The 1D_SR procedure	120
F.3.7	The 1D_EXTR procedure	120
F.3.8	The 1D_FILTR procedure	121
F.4	Forward transformation (informative)	123
F.4.1	The FDWT procedure (informative)	123
F.4.2	The 2D_SD procedure (informative)	125
F.4.3	The VER_SD procedure (informative)	126
F.4.4	The HOR_SD procedure (informative)	127
F.4.5	The 2D_DEINTERLEAVE procedure (informative)	128
F.4.6	The 1D_SD procedure (informative)	130
F.4.7	The 1D_EXTD procedure (informative)	130
F.4.8	The 1D_FILTD procedure (informative)	131
Annex G	DC level shifting and multiple component transformations	133
G.1	DC level shifting of tile-components	133
G.1.1	DC level shifting of tile-components (informative)	133
G.1.2	Inverse DC level shifting of tile-components	133
G.2	Reversible multiple component transformation (RCT)	134
G.2.1	Forward RCT (informative)	134
G.2.2	Inverse RCT	134
G.3	Irreversible multiple component transformation (ICT)	134
G.3.1	Forward ICT (informative)	134
G.3.2	Inverse ICT	135
G.4	Chrominance component sub-sampling and the reference grid	135
Annex H	Coding of images with regions of interest	136
H.1	Decoding of ROI	136
H.2	Description of the Maxshift method	136
H.2.1	Encoding of ROI (informative)	136
H.2.2	Selection of scaling value, s, at encoder side (informative)	137
H.3	Remarks on region of interest coding (informative)	137
H.3.1	Region of interest mask generation (informative)	137
H.3.2	Multi-component remark (informative)	139
H.3.3	Disjoint regions remark (informative)	139
H.3.4	Implementation precision remark (informative)	139
H.3.5	An example of the usage of the Maxshift method (informative)	139

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

Annex I JP2 file format syntax	140
I.1 File format scope.....	140
I.2 Introduction to the JP2 file format	140
I.2.1 File identification	140
I.2.2 File organization	140
I.2.3 Greyscale, colour, palette, multi-component specification	141
I.2.4 Inclusion of opacity channels.....	142
I.2.5 Metadata.....	142
I.2.6 Conformance with the file format.....	142
I.3 Greyscale/Colour/Palettized/multi-component specification architecture	142
I.3.1 Enumerated method	142
I.3.2 Restricted ICC profile method	142
I.3.3 Using multiple methods	143
I.3.4 Palettized images	143
I.3.5 Interactions with the decorrelating multiple component transform.....	143
I.3.6 Key to graphical descriptions (informative).....	143
I.4 Box definition	144
I.5 Defined boxes	146
I.5.1 JPEG 2000 Signature box	146
I.5.2 File Type box	146
I.5.3 JP2 Header box (superbox).....	147
I.5.4 Contiguous Codestream box	161
I.6 Adding intellectual property rights information in JP2.....	161
I.7 Adding vendor-specific information to the JP2 file format.....	161
I.7.1 XML boxes	161
I.7.2 UUID boxes	162
I.7.3 UUID Info boxes (superbox)	162
I.8 Dealing with unknown boxes.....	164
Annex J Examples and guidelines	165
J.1 Software conventions adaptive entropy decoder.....	165
J.2 Selection of quantization step sizes for irreversible transformations	166
J.3 Filter impulse responses corresponding to lifting-based irreversible filtering procedures.....	167
J.4 Example of discrete wavelet transformation	168
J.4.1 Example of 9-7 irreversible wavelet transformation.....	168
J.4.2 Example of 5-3 reversible wavelet transformation	170
J.5 Row-based wavelet transform.....	171
J.5.1 The FDWT_ROW procedure.....	171
J.5.2 The INIT procedure	173
J.5.3 The START_VERT procedure	174
J.5.4 OUTPUT_ROW procedure.....	180
J.6 Scan-based coding.....	180
J.7 Error resilience	180
J.8 Implementing the Restricted ICC method outside of a full ICC colour management engine	181
J.8.1 Extracting the colour transformation from an ICC profile.....	181
J.8.2 Colour processing equations for three-component RGB images	182
J.8.3 Converting images to sRGB	183
J.8.4 Converting images to other colourspaces.....	184
J.8.5 Input and output ranges and quantization	184
J.8.6 Taking advantage of multiple colour specifications.....	185
J.9 An example of the interpretation of multiple components	185
J.10 An example of decoding showing intermediate steps	185
J.10.1 Main header	186
J.10.2 Tile-part header	187
J.10.3 Packet headers.....	187
J.10.4 Arithmetic-coded compressed data	188
J.10.5 Wavelet and level shift.....	189
J.11 Visual frequency weighting	189
J.11.1 Modify quantization step size	190
J.11.2 Modify the embedded coding order	190

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

J.11.4	Recommended frequency weighting tables.....	190
J.12	Encoder sub-sampling of components	191
J.13	Rate control.....	192
J.13.1	Introduction to key concepts for rate control	192
J.13.2	Layered bit-stream abstraction.....	192
J.13.3	Rate-distortion optimization	193
J.13.4	Efficient distortion estimation for R-D optimal truncation.....	194
J.14	Guidelines on handling YCC codestream	196
J.14.1	Use of multiple component transformation.....	196
J.14.2	Using the JP2 format.....	196
J.14.3	Chrominance offset.....	196
J.15	Guidelines for digital cinema applications.....	197
J.15.1	Reliable multicast transmission of JPEG 2000 codestreams.....	198
J.15.2	Implementation guidelines for digital cinema distribution	207
J.15.3	Implementation guidelines for the use of JPEG 2000 in film archive applications	210
Annex K	Additional reading.....	213
K.1	General.....	213
K.2	Quantization and entropy coding	213
K.3	Wavelet transformation.....	213
K.4	Region of interest coding	214
K.5	Visual frequency weighting	214
K.6	Error resilience.....	214
K.7	Guidelines for digital cinema applications.....	214
Annex L	Patent statement.....	216
Annex M	Elementary stream for broadcast applications.....	217
M.1	Introduction.....	217
M.2	Definitions.....	217
M.3	Access unit construction	217
M.4	Elementary stream marker box (superbox)	218
M.4.1	Frame Rate Coding box (required)	218
M.4.2	Maximum Bit Rate box (required).....	219
M.4.3	Field Coding box (optional).....	219
M.4.4	Time Code box (required).....	220
M.4.5	Broadcast Colour Specification box (required).....	220
M.4.6	Mastering Display Metadata Box (optional).....	221
Annex N	Media type registrations.....	223
N.1	Introduction.....	223
N.2	References.....	223
N.3	image/j2c.....	223
N.3.1	Semantics.....	223
N.3.2	Registration.....	223
Bibliography	225

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

Table A.1 – Marker definitions	13
Table A.2 – List of markers and marker segments	14
Table A.3 – Information in the marker segments	15
Table A.4 – Start of codestream parameter values	19
Table A.5 – Start of tile-part parameter values.....	20
Table A.6 – Number of tile-parts, TNsot, parameter value	20
Table A.7 – Start of data parameter values.....	20
Table A.8 – End of codestream parameter values	20
Table A.9 – Image and tile size parameter values	22
Table A.10 – Capability Rsiz parameter.....	23
Table A.11 – Component Ssiz parameter.....	24
Table A.11 <i>bis</i> – Extended capabilities parameter values	24
Table A.11 <i>ter</i> – Definition of the value of Pcap ⁱ parameters.....	25
Table A.11 <i>quater</i> – Profile parameter values.....	26
Table A.12 – Coding style default parameter values.....	27
Table A.13 – Coding style parameter values for the Scod parameter.....	27
Table A.14 – Coding style parameter values of the SGcod parameter	27
Table A.15 – Coding style parameter values of the SPcod and SPcoc parameters.....	28
Table A.16 – Progression order for the SGcod, SPcoc and Ppoc parameters.....	28
Table A.17 – Multiple component transformation for the SGcod parameters.....	28
Table A.18 – Width or height exponent of the code-blocks for the SPcod and SPcoc parameters	29
Table A.19 – Code-block style for the SPcod and SPcoc parameters	29
Table A.20 – Transformation for the SPcod and SPcoc parameters.....	29
Table A.21 – Precinct width and height for the SPcod and SPcoc parameters.....	29
Table A.22 – Coding style component parameter values	31
Table A.23 – Coding style parameter values for the Scoc parameter	31
Table A.24 – Region-of-interest parameter values	31
Table A.25 – Region-of-interest parameter values for the Srgn parameter	32
Table A.26 – Region-of-interest values from SPRgn parameter (Srgn = 0)	32
Table A.27 – Quantization default parameter values.....	33
Table A.28 – Quantization default values for the Sqcd and Sqcc parameters	33
Table A.29 – Reversible step size values for the SPqcd and SPqcc parameters (reversible transform only).....	33
Table A.30 – Quantization values for the SPqcd and SPqcc parameters (irreversible transformation only).....	33
Table A.31 – Quantization component parameter values.....	34
Table A.32 – Progression order change, tile parameter values.....	35
Table A.33 – Tile-part length parameter values	37
Table A.34 – Size parameters for Stlm.....	37
Table A.35 – Packets length, main header parameter values.....	38

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

Table A.36 – Ipm, Ipit list of packet lengths	38
Table A.37 – Packet length, tile-part headers parameter values	39
Table A.38 – Packed packet headers, main header parameter values.....	40
Table A.39 – Packet header, tile-part headers parameter values	40
Table A.40 – Start of packet parameter values	41
Table A.41 – End of packet header parameter values	41
Table A.42 – Component registration parameter values	42
Table A.43 – Comment parameter values	43
Table A.44 – Registration values for the Rcom parameter.....	43
Table A.45 – Codestream restrictions.....	43
Table A.46 – Codestream restrictions for digital cinema applications	45
Table A.47 – Example file size limitations for digital cinema applications including archiving	52
Table A.48 – Codestream restrictions for broadcast application profiles	53
Table A.49 – Operating levels for the broadcast contribution single tile and multi-tile profiles.....	54
Table A.50 – Operating levels for broadcast contribution multi-tile reversible profile.....	54
Table A.51 – Codestream restrictions for interoperable master format (IMF) single tile profiles.....	55
Table A.52 – Codestream restrictions for interoperable master format (IMF) single tile/multi-tile reversible profiles ..	56
Table A.53 – Operating levels for IMF profiles	57
Table A.54 – Operating sublevels for IMF profiles.....	58
Table A.55 – Profile PRFnum parameter	58
Table B.1 – Quantities (x_{ob} , y_{ob}) for sub-band b.....	66
Table B.2 – Example of layer formation (only one component shown).....	69
Table B.3 – Example of packet formation.....	70
Table B.4 – Codewords for the number of coding passes for each code-block.....	72
Table B.5 – Example packet header bit stream.....	74
Table C.1 – Encoder register structures.....	82
Table C.2 – Q_e values and probability estimation.....	85
Table C.3 – Decoder register structures.....	93
Table D.1 – Contexts for the significance propagation and cleanup coding passes	100
Table D.2 – Contributions of the vertical (and the horizontal) neighbours to the sign context	101
Table D.3 – Sign contexts from the vertical and horizontal contributions	102
Table D.4 – Contexts for the magnitude refinement coding passes.....	102
Table D.5 – Run-length decoder for cleanup passes.....	103
Table D.6 – Example of sub-bit-plane coding order and significance propagation.....	103
Table D.7 – Initial states for all contexts.....	104
Table D.8 – Arithmetic coder termination patterns	104
Table D.9 – Selective arithmetic coding bypass.....	105
Table D.10 – Decisions in the context model flow chart.....	108
Table D.11 – Decoding in the context model flow chart.....	108

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

Table E.1 – Sub-band gains	109
Table F.1 – Decomposition level n_b for sub-band b	113
Table F.2 – Extension to the left.....	121
Table F.3 – Extension to the right	121
Table F.4 – Definition of lifting parameters for the 9-7 irreversible filter.....	122
Table F.5 – Definition of coefficients g_n	123
Table F.6 – Intermediate expressions (r_0, r_1, s_0, t_0)	123
Table F.7 – Intermediate expressions	123
Table F.8 – Extension to the left.....	130
Table F.9 – Extension to the right	131
Table I.1 – Binary structure of a box.....	145
Table I.2 – Defined boxes.....	145
Table I.3 – Legal Brand values.....	147
Table I.4 – Format of the contents of the File Type box	147
Table I.5 – Format of the contents of the Image Header box	150
Table I.6 – BPC values 150	
Table I.7 – Format of the contents of the Bits Per Component box.....	151
Table I.8 – BPC ⁱ values 151	
Table I.9 – Legal METH values	152
Table I.10 – Legal EnumCS values	153
Table I.11 – Format of the contents of the Colour Specification box.....	153
Table I.12 – Format of the contents of the Palette box.....	154
Table I.13 – B ⁱ values 155	
Table I.14 – MTyp ⁱ field values.....	155
Table I.15 – Format of the contents of the Component Mapping box.....	155
Table I.16 – Typ ⁱ field values	156
Table I.17 – Assoc ⁱ field values	157
Table I.18 – Colours indicated by the Assoc ⁱ field.....	157
Table I.19 – Format of the Channel Definition box.....	158
Table I.20 – Format of the contents of the Capture Resolution box.....	159
Table I.21 – Format of the contents of the Default Display Resolution box	161
Table I.22 – Format of the contents of the Contiguous Codestream box	161
Table I.23 – Format of the contents of a UUID box.....	162
Table I.24 – UUID List box contents data structure values.....	163
Table I.25 – Data Entry URL box contents data structure values.....	163
Table J.1 – Definition of impulse responses for the 9-7 irreversible analysis filter bank.....	167
Table J.2 – Definition of impulse responses for the 9-7 irreversible synthesis filter band.....	167
Table J.3 – Source tile component samples.....	168
Table J.4 – 2LL sub-band coefficients (9-7 irreversible wavelet transformation).....	168

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

Table J.5 – 2HL sub-band coefficients (9-7 irreversible wavelet transformation)	168
Table J.6 – 2LH sub-band coefficients (9-7 irreversible wavelet transformation)	169
Table J.7 – 2HH sub-band coefficients (9-7 irreversible wavelet transformation)	169
Table J.8 – 1HL sub-band coefficients (9-7 irreversible wavelet transformation)	169
Table J.9 – 1LH sub-band coefficients (9-7 irreversible wavelet transformation)	169
Table J.10 – 1HH sub-band coefficients (9-7 irreversible wavelet transformation)	169
Table J.11 – 2LL sub-band coefficients (5-3 reversible wavelet transformation)	170
Table J.12 – 2HL sub-band coefficients (5-3 reversible wavelet transformation)	170
Table J.13 – 2LH sub-band coefficient (5-3 reversible wavelet transformation)	170
Table J.14 – 2HH sub-band coefficients (5-3 reversible wavelet transformation)	170
Table J.15 – 1HL sub-band coefficients (5-3 reversible wavelet transformation)	170
Table J.16 – 1LH sub-band coefficients (5-3 reversible wavelet transformation)	171
Table J.17 – 1HH sub-band coefficients (5-3 reversible wavelet transformation)	171
Table J.18 – Error resilience tools	180
Table J.19 – Processing tags used by a Restricted ICC profile	181
Table J.20 – Decoding first packet header	187
Table J.21 – Decoding second packet header	188
Table J.22 – Arithmetic decode of first code-block	188
Table J.23 – Arithmetic decode of second code-block	189
Table J.24 – Recommended frequency weighting	191
Table J.25 – Recommended frequency weighting for multiple component (colour) images	191
Table J.26 – CRG (Component registration) values	197
Table J.27 – Quantization steps for 2K visually lossless compression	207
Table J.28 – Recommended frequency weighting for digital cinema environment	210
Table M.1 – Definitions of elementary stream boxes	218
Table M.2 – Code for identifying video specification	220
Table M.3 – Colorimetric parameters and related characteristics	220
Table M.4 – Real-valued intermediate luminance and chrominance equations	221
Table M.5 – Equations for integer luminance and chrominance representation using n bits for D'_L and m bits for D'_u and D'_v (where ε denotes a vanishingly small positive number)	221
Table M.6 – Example values for mastering display parameters for Rec. ITU-R BT.709	222

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

Figure 5-1 – Specification block diagram.....	9
Figure A.1 – Example of the marker segment description figures	13
Figure A.2 – Construction of the codestream	16
Figure A.3 – Construction of the main header.....	17
Figure A.4 – Construction of the first tile-part header of a given tile.....	18
Figure A.5 – Construction of a non-first tile-part header	18
Figure A.6 – Start of tile-part syntax	19
Figure A.7 – Image and tile size syntax.....	21
Figure A.7bis – Extended capabilities syntax.....	24
Figure A.7ter – Profile syntax	25
Figure A.8 – Coding style default syntax	26
Figure A.9 – Coding style parameter diagram of the SGcod and SPcod parameters.....	28
Figure A.10 – Coding style component syntax.....	30
Figure A.11 – Coding style parameter diagram of the SPcoc parameters	30
Figure A.12 – Region-of-interest syntax	31
Figure A.13 – Quantization default syntax.....	32
Figure A.14 – Quantization component syntax	34
Figure A.15 – Progression order change tile syntax	35
Figure A.16 – Tile-part lengths	36
Figure A.17 – Tile-part length syntax.....	36
Figure A.18 – Packets length, main header syntax.....	37
Figure A.19 – Packet length, tile-part header syntax.....	38
Figure A.20 – Packed packet headers, main header syntax	39
Figure A.21 – Packed packet headers, tile-part header syntax	40
Figure A.22 – Start of packet syntax	41
Figure A.23 – Component registration syntax.....	42
Figure A.24 – Comment syntax.....	42
Figure A.25 – Compressed data ordering showing the relative position of the 4K tile-parts relative to the basic 2K tile-parts	50
Figure A.26 – Codestream structure for 4K digital cinema profile	50
Figure A.27 – Extended tile-parts for the scalable 4K digital cinema profile	50
Figure A.28 – Codestream structure for the scalable 4K digital cinema profile.....	50
Figure A.29 – Codestream structure for the scalable 2K digital cinema profile.....	50
Figure B.1 – Reference grid diagram.....	60
Figure B.2 – Component sample locations on the reference grid for different XRsiz and YRsiz values	60
Figure B.3 – Example of upper left component sample locations	61
Figure B.4 – Tiling of the reference grid diagram	61
Figure B.5 – Reference grid example	63

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

Figure B.6 – Example tile sizes and locations for component 0	64
Figure B.7 – Example tile sizes and locations for component 1	65
Figure B.8 – Precincts of one reduced resolution	66
Figure B.9 – Code-blocks and precincts in sub-band <i>b</i> from four different tiles	68
Figure B.10 – Diagram of precincts of one resolution level of one component	69
Figure B.11 – Diagram of code-blocks within precincts at one resolution level	70
Figure B.12 – Example of a tag tree representation	71
Figure B.13 – Example of the information known to the encoder	74
Figure B.14 – Example of progression order volume in two dimensions	78
Figure B.15 – Example of the placement of POC marker segments	79
Figure C.1 – Arithmetic encoder inputs and outputs	80
Figure C.2 – Encoder for the MQ-coder	82
Figure C.3 – ENCODE procedure	83
Figure C.4 – CODE1 procedure	83
Figure C.5 – CODE0 procedure	84
Figure C.6 – CODELPS procedure with conditional MPS/LPS exchange	85
Figure C.7 – CODEMPS procedure with conditional MPS/LPS exchange	87
Figure C.8 – Encoder renormalization procedure	88
Figure C.9 – BYTEOUT procedure for encoder	89
Figure C.10 – Initialization of the encoder	90
Figure C.11 – FLUSH procedure	91
Figure C.12 – Setting the final bits in the C register	92
Figure C.13 – Arithmetic decoder inputs and outputs	92
Figure C.14 – Decoder for the MQ-coder	93
Figure C.15 – Decoding an MPS or an LPS	94
Figure C.16 – Decoder MPS path conditional exchange procedure	95
Figure C.17 – Decoder LPS path conditional exchange procedure	96
Figure C.18 – Decoder renormalization procedure	97
Figure C.19 – BYTEIN procedure for decoder	97
Figure C.20 – Initialization of the decoder	98
Figure D.1 – Example scan pattern of a code-block bit-plane	99
Figure D.2 – Neighbours states used to form the context	100
Figure D.3 – Flow chart for all coding passes on a code-block bit-plane	107
Figure F.1 – Inputs and outputs of the IDWT procedure	112
Figure F.2 – The IDWT ($N_L = 2$)	113
Figure F.3 – The IDWT procedure	114
Figure F.4 – Inputs and outputs of the 2D_SR procedure	114
Figure F.5 – One level of reconstruction from four sub-bands (2D_SR procedure) into sub-bands	114
Figure F.6 – The 2D_SR procedure	115

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

Figure F.7 – Parameters of 2D_INTERLEAVE procedure	115
Figure F.8 – The 2D_INTERLEAVE procedure.....	116
Figure F.9 – Inputs and outputs of the HOR_SR procedure.....	117
Figure F.10 – The HOR_SR procedure	118
Figure F.11 – Inputs and outputs of the VER_SR procedure	119
Figure F.12 – The VER_SR procedure.....	119
Figure F.13 – Parameters of the 1D_SR procedure	120
Figure F.14 – The 1D_SR procedure.....	120
Figure F.15 – Periodic symmetric extension of signal	120
Figure F.16 – Parameters of the 1D_FILTR procedure.....	121
Figure F.17 – Inputs and outputs of the FDWT procedure.....	124
Figure F.18 – The FDWT ($N_L = 2$).....	124
Figure F.19 – The FDWT procedure	124
Figure F.20 – Inputs and outputs of the 2D_SD procedure	125
Figure F.21 – One-level decomposition into four sub-bands (2D_SD procedure)	125
Figure F.22 – The 2D_SD procedure	125
Figure F.23 – Inputs and outputs of the VER_SD procedure	126
Figure F.24 – The VER_SD procedure	126
Figure F.25 – Inputs and outputs of the HOR_SD procedure.....	127
Figure F.26 – The HOR_SD procedure.....	127
Figure F.27 – Parameters of 2D_DEINTERLEAVE procedure.....	128
Figure F.28 – The 2D_DEINTERLEAVE procedure.....	129
Figure F.29 – Parameters of the 1D_SD procedure.....	130
Figure F.30 – The 1D_SD procedure	130
Figure F.31 – Parameters of the 1D_FILTD procedure.....	131
Figure G.1 – Placement of the DC level shifting with component transformation.....	133
Figure G.2 – Placement of the DC level shifting without component transformation.....	133
Figure H.1 – The inverse wavelet transformation with the 5-3 reversible filter	138
Figure H.2 – The inverse wavelet transformation with the 9-7 irreversible filter	138
Figure I.1 – Conceptual structure of a JP2 file	141
Figure I.2 – Example of the box description figures	144
Figure I.3 – Example of the superbox description figures.....	144
Figure I.4 – Organization of a box.....	144
Figure I.5 – Illustration of box lengths	145
Figure I.6 – Organization of the contents of a File Type box.....	147
Figure I.7 – Organization of the contents of a JP2 Header box.....	148
Figure I.8 – Organization of the contents of an Image Header box.....	148
Figure I.9 – Organization of the contents of a Bits Per Component box.....	151
Figure I.10 – Organization of the contents of a Colour Specification box	152

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

Figure I.11 – Organization of the contents of the Palette box	154
Figure I.12 – Organization of the contents of a Component Mapping box	155
Figure I.13 – Organization of the contents of a Channel Definition box.....	156
Figure I.14 – Organization of the contents of the Resolution box.....	158
Figure I.15 – Organization of the contents of the Capture Resolution box	159
Figure I.16 – Organization of the contents of the Default Display Resolution box.....	160
Figure I.17 – Organization of the contents of the Contiguous Codestream box.....	161
Figure I.18 – Organization of the contents of the XML box	162
Figure I.19 – Organization of the contents of the UUID box	162
Figure I.20 – Organization of the contents of a UUID Info box.....	162
Figure I.21 – Organization of the contents of a UUID List box	163
Figure I.22 – Organization of the contents of a Data Entry URL box	163
Figure J.1 – Initialization of the software-conventions decoder.....	165
Figure J.2 – Decoding an MPS or an LPS in the software-conventions decoder	166
Figure J.3 – Inserting a new byte into the C register in the software-conventions decoder.....	166
Figure J.4 – The FDWT_ROW procedure.....	172
Figure J.5 – The GET_ROW procedure	173
Figure J.6 – The INIT procedure	174
Figure J.7 – The START_VERT procedure	175
Figure J.8 – The RB_VERT_1 procedure	176
Figure J.9 – The RB_VERT_2 procedure	177
Figure J.10 – The END_1 procedure.....	178
Figure J.11 – The END_2 procedure.....	179
Figure J.12 – Illustration of code-block contributions to bit-stream layers	193
Figure J.13 – 4:2:2 format (co-sited).....	196
Figure J.14 – 4:2:2 format (centred).....	196
Figure J.15 – 4:2:0 format (co-sited).....	197
Figure J.16 – 4:2:0 format (centred).....	197
Figure J.17 – Distribution scenario for D-Cinema and live events.....	198
Figure J.18 – Sender and receiver sequence of operations	200
Figure J.19 – J2K codestream and network packets.....	201
Figure J.20 – Attribute numbering (Layer-Resolution).....	202
Figure J.21 – Attribute numbering (Resolution-Layer).....	202
Figure J.22 – Network packet and attribute number.....	203
Figure J.23 – Format of the header used for JPEG 2000 packetization.....	203
Figure J.24 – Attribute header value.....	204
Figure J.25 – Example of forwarding network packets.....	205
Figure J.26 – Packet forwarding in intermediate distributor	205
Figure J.27 – Packet forwarding ("Resolution-Layer" type)	206

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

Figure J.28 – Packet forwarding (Layer-Resolution type)	207
Figure J.29 – Experience of Campbell and Robson for the construction of the CSF: modulation of a sine-wave grating for luminance	208
Figure J.30 – CSF of luminance	209
Figure M.1 – Elementary stream structure for broadcast application profiles – boxes with dashed borders are optional	217
Figure M.2 – Frame Rate Coding box content	219
Figure M.3 – Maximum Bit Rate box content.....	219
Figure M.4 – Field Coding box content.....	219
Figure M.5 – Time Code box content.....	220
Figure M.6 – Broadcast Colour Specification box content.....	220
Figure M.7 – Mastering Display Metadata.....	221

Information technology – JPEG 2000 image coding system: Core coding system

1 Scope

This Recommendation | International Standard defines a set of lossless (bit-preserving) and lossy compression methods for coding bi-level, continuous-tone grey-scale, palletized colour, or continuous-tone colour digital still images.

This Recommendation | International Standard:

- specifies decoding processes for converting compressed image data to reconstructed image data;
- specifies a codestream syntax containing information for interpreting the compressed image data;
- specifies a file format;
- provides guidance on encoding processes for converting source image data to compressed image data;
- provides guidance on how to implement these processes in practice.

NOTE – As this specification was first published as common text only after ISO/IEC JTC1 had approved the first edition in 2000, edition numbers in the ITU and ISO/IEC versions are offset by one. This is the fourth edition of ITU-T T.800 and the fifth edition of ISO/IEC 15444-1.

2 References

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The Telecommunication Standardization Bureau of the ITU maintains a list of currently valid ITU-T Recommendations.

2.1 Identical Recommendations | International Standards

- Recommendation ITU-T T.81 (1992) | ISO/IEC 10918-1:1994, *Information technology – Digital compression and coding of continuous-tone still images: Requirements and guidelines.*
- Recommendation ITU-T T.84 (1996) | ISO/IEC 10918-3:1997, *Information technology – Digital compression and coding of continuous-tone still images: Extensions.*
- Recommendation ITU-T T.84 (1996)/Amd.1 (1999) | ISO/IEC 10918-3:1997/Amd.1:1999, *Information technology – Digital compression and coding of continuous-tone still images: Extensions – Amendment 1: Provisions to allow registration of new compression types and versions in the SPIFF header.*
- Recommendation ITU-T T.86 (1998) | ISO/IEC 10918-4:1999, *Information technology – Digital compression and coding of continuous-tone still images: Registration of JPEG Profiles, SPIFF Profiles, SPIFF Tags, SPIFF colour Spaces, APPn Markers, SPIFF Compression types and Registration Authorities (REGAUT).*
- Recommendation ITU-T T.87 (1998) | ISO/IEC 14495-1:2000, *Lossless and near-lossless compression of continuous-tone still images – Baseline.*
- Recommendation ITU-T T.88 (2000) | ISO/IEC 14492:2001, *Information technology – Lossy/lossless coding of bi-level images.*
- Recommendation ITU-T T.810 (2006) | ISO/IEC 15444-11:2007, *Information technology – JPEG 2000 image coding system: Wireless.*
- ISO/IEC 646:1991, *Information technology – ISO 7-bit coded character set for information interchange.*
- ISO 8859-15:1999, *Information technology – 8-bit single-byte coded graphic character sets – Part 15: Latin alphabet No. 9.*

2.2 Additional references

- Recommendation ITU-R BT.601 (latest), *Studio encoding parameters of digital television for standard 4:3 and wide screen 16:9 aspect ratios.*

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

- IEC 61966-2-1:1999, *Multimedia systems and equipment – Colour measurement and management – Part 2-1: Colour management – Default RGB colour space – sRGB*.
- IEC 61966-2-1:1999/Amd.1:2003, *Multimedia systems and equipment – Colour measurement and management – Part 2-1: Colour management – Default RGB colour space – sRGB*.
- ISO/CIE 11664-1: (latest), *Colorimetry – Part 1: CIE standard colorimetric observers*.
- ISO 15076-1: (latest), *Image technology colour management – Architecture, profile format and data structure – Part 1: Based on ICC.1:2010*.
- ISO 26428-1:2008, *Digital cinema (D-cinema) distribution master – Part 1: Image characteristics*.
- ISO/IEC 11578:1996, *Information technology – Open Systems Interconnection – Remote Procedure Call (RPC)*.

3 Definitions

For the purposes of this Recommendation | International Standard, the following definitions apply:

- 3.1** $\lfloor x \rfloor$, **floor function**: This indicates the largest integer not exceeding x .
- 3.2** $\lceil x \rceil$, **ceiling function**: This indicates the smallest integer not exceeded by x .
- 3.3** **5-3 reversible filter**: A particular filter pair used in the wavelet transformation. This reversible filter pair has 5 taps in the low-pass and 3 taps in the high-pass.
- 3.4** **9-7 irreversible filter**: A particular filter pair used in the wavelet transformation. This irreversible filter pair has 9 taps in the low-pass and 7 taps in the high-pass.
- 3.5** **access unit**: A coded representation of one video frame.
- 3.6** **AND**: Bit wise AND logical operator.
- 3.7** **arithmetic coder**: An entropy coder that converts variable length strings to variable length codes (encoding) and vice versa (decoding).
- 3.8** **auxiliary channel**: A channel that is used by the application outside the scope of colourspace conversion. For example, an opacity channel or a depth channel would be an auxiliary channel.
- 3.9** **bit**: A contraction of the term "binary digit"; a unit of information represented by a zero or a one.
- 3.10** **bit-plane**: A two-dimensional array of bits. In this Recommendation | International Standard a bit-plane refers to all the bits of the same magnitude in all coefficients or samples. This could refer to a bit-plane in a component, tile-component, code-block, region of interest, or other.
- 3.11** **bit stream**: The actual sequence of bits resulting from the coding of a sequence of symbols. It does not include the markers or marker segments in the main and tile-part headers or the EOC marker. It does include any packet headers and in-stream markers and marker segments not found within the main or tile-part headers.
- 3.12** **big-endian**: The bits of a value representation occur in order from the most significant to the least significant.
- 3.13** **box**: A portion of the file format defined by a length and unique box type. Boxes of some types may contain other boxes.
- 3.14** **box contents**: Refers to the data wrapped within the box structure. The contents of a particular box are stored within the DBox field within the box data structure.
- 3.15** **box type**: Specifies the kind of information that shall be stored with the box. The type of a particular box is stored within the TBox field within the box data structure.
- 3.16** **byte**: Eight bits.
- 3.17** **channel**: One logical component of the image. A channel may be a direct representation of one component from the codestream, or may be generated by the application of a palette to a component from the codestream.
- 3.18** **cleanup pass**: A coding pass performed on a single bit-plane of a code-block of coefficients. The first pass and only coding pass for the first significant bit-plane is a cleanup pass; the third and the last pass of every remaining bit-plane is a cleanup pass.

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

signalling needed to decode.

- 3.20 code-block:** A rectangular grouping of coefficients from the same sub-band of a tile-component.
- 3.21 code-block scan:** The order in which the coefficients within a code-block are visited during a coding pass. The code-block is processed in stripes, each consisting of four rows (or all remaining rows if less than four) and spanning the width of the code-block. Each stripe is processed column by column from top to bottom and from left to right.
- 3.22 coder:** An embodiment of either an encoding or decoding process.
- 3.23 coding pass:** A complete pass through a code-block where the appropriate coefficient values and context are applied. There are three types of coding passes: significance propagation pass, magnitude refinement pass and cleanup pass. The result of each pass (after arithmetic coding, if selective arithmetic coding bypass is not used) is a stream of compressed image data.
- 3.24 coefficient:** The values that are the result of a transformation.
- 3.25 colour channel:** A channel that functions as an input to a colour transformation system. For example, a red channel or a greyscale channel would be a colour channel.
- 3.26 component:** A two-dimensional array of samples. An image typically consists of several components, for instance, representing red, green and blue.
- 3.27 compressed image data:** Part or all of a bit stream. It can also refer to a collection of bit streams in part or all of a codestream.
- 3.28 conforming reader:** An application that reads and interprets a JP2 file correctly.
- 3.29 context:** Function of coefficients previously decoded and used to condition the decoding of the present coefficient.
- 3.30 context label:** The arbitrary index used to distinguish different context values. The labels are used as a convenience of notation rather than being normative.
- 3.31 context vector:** The binary vector consisting of the significance states of the coefficients included in a context.
- 3.32 decoder:** An embodiment of a decoding process, and optionally a colour transformation process.
- 3.33 decoding process:** A process which takes as its input all or part of a codestream and outputs all or part of a reconstructed image.
- 3.34 decomposition level:** A collection of wavelet sub-bands where each coefficient has the same spatial impact or span with respect to the source component samples. These include the HL, LH and HH sub-bands of the same two-dimensional sub-band decomposition. For the last decomposition level, the LL sub-band is also included.
- 3.35 delimiting markers and marker segments:** Markers and marker segments that give information about beginning and ending points of structures in the codestream.
- 3.36 discrete wavelet transformation (DWT):** A transformation that iteratively transforms one signal into two or more filtered and decimated signals corresponding to different frequency bands. This transformation operates on spatially discrete samples.
- 3.37 encoder:** An embodiment of an encoding process.
- 3.38 encoding process:** A process that takes as its input all or part of the source image data and outputs a codestream.
- 3.39 file format:** A codestream and additional support data and information not explicitly required for the decoding of codestream. Examples of such support data include text fields providing titling, security and historical information, data to support placement of multiple codestreams within a given data file, and data to support exchange between platforms or conversion to other file formats.
- 3.40 fixed information markers and fixed information marker segments:** Markers and marker segments that offer information about the original image.
- 3.41 functional markers and functional marker segments:** Markers and marker segments that offer information about coding procedures.
- 3.42 grid resolution:** The spatial resolution of the reference grid, specifying the distance between neighbouring points on the reference grid.
- 3.43 guard bits:** Additional most significant bits that have been added to sample data.

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

- 3.45 HH sub-band:** The sub-band obtained by forward horizontal high-pass filtering and vertical high-pass filtering. This sub-band contributes to reconstruction with inverse vertical high-pass filtering and horizontal high-pass filtering.
- 3.46 HL sub-band:** The sub-band obtained by forward horizontal high-pass filtering and vertical low-pass filtering. This sub-band contributes to reconstruction with inverse vertical low-pass filtering and horizontal high-pass filtering.
- 3.47 image:** The set of all components.
- 3.48 image area:** A rectangular part of the reference grid, registered by offsets from the origin and the extent of the reference grid.
- 3.49 image area offset:** The number of reference grid points down and to the right of the reference grid origin where the origin of the image area can be found.
- 3.50 image data:** The components and component samples making up an image. Image data can refer to either the source image data or the reconstructed image data.
- 3.51 in-bit-stream markers and in-bit-stream marker segments:** Markers and marker segments that provide error resilience functionality.
- 3.52 informational markers and informational marker segments:** Markers and marker segments that offer ancillary information.
- 3.53 instantaneous bit rate:** For each frame, this corresponds to the size of the contiguous codestream for the frame in bits multiplied by the frame rate.
- 3.54 irreversible:** A transformation, progression, system, quantization, or other process that, due to a systemic or quantization error, disallows lossless recovery. An irreversible process can only lead to lossy compression.
- 3.55 JP2 file:** The name of a file in the file format described in this Recommendation | International Standard. Structurally, a JP2 file is a contiguous sequence of boxes.
- 3.56 JPEG:** Used to refer globally to the encoding and decoding process of the following Recommendations | International Standards:
- Rec. ITU-T T.81 | ISO/IEC 10918-1;
 - Rec. ITU-T T.83 | ISO/IEC 10918-2;
 - Rec. ITU-T T.84 | ISO/IEC 10918-3;
 - Rec. ITU-T T.86 | ISO/IEC 10918-4.
- 3.57 JPEG 2000:** Used to refer globally to the encoding and decoding processes in this Recommendation | International Standard and their embodiment in applications.
- 3.58 LH sub-band:** The sub-band obtained by forward horizontal low-pass filtering and vertical high-pass filtering. This sub-band contributes to reconstruction with inverse vertical high-pass filtering and horizontal low-pass filtering.
- 3.59 LL sub-band:** The sub-band obtained by forward horizontal low-pass filtering and vertical low-pass filtering. This sub-band contributes to reconstruction with inverse vertical low-pass filtering and horizontal low-pass filtering.
- 3.60 layer:** A collection of compressed image data from coding passes of one or more code-blocks of a tile-component. Layers have an order for encoding and decoding that must be preserved.
- 3.61 lossless:** A descriptive term for the effect of the overall encoding and decoding processes in which the output of the decoding process is identical to the input to the encoding process. Distortion-free restoration can be assured. All of the coding processes or steps used for encoding and decoding are reversible.
- 3.62 lossy:** A descriptive term for the effect of the overall encoding and decoding processes in which the output of the decoding process is not identical to the input to the encoding process. There is distortion (measured mathematically). At least one of the coding processes or steps used for encoding and decoding is irreversible.
- 3.63 magnitude refinement pass:** A type of coding pass.
- 3.64 main header:** A group of markers and marker segments at the beginning of the codestream that describe the image parameters and coding parameters that can apply to every tile and tile-component.
- 3.65 marker:** A two-byte code in which the first byte is hexadecimal FF (0xFF) and the second byte is a value between 1 (0x01) and hexadecimal FE (0xFE).

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

- 3.68 packet:** A part of the bit stream comprising a packet header and the compressed image data from one layer of one precinct of one resolution level of one tile-component.
- 3.69 packet header:** Portion of the packet that contains the signalling necessary for decoding that packet.
- 3.70 pointer markers and pointer marker segments:** Markers and marker segments that offer information about the location of structures in the codestream.
- 3.71 precinct:** A one rectangular region of a transformed tile-component, within each resolution level, used for limiting the size of packets.
- 3.72 precision:** Number of bits allocated to a particular sample, coefficient or other binary numerical representation.
- 3.73 progression:** The order of a codestream where the decoding of each successive bit contributes to a "better" reconstruction of the image. What metrics make the reconstruction "better" is a function of the application. Some examples of progression are increasing resolution or improved sample fidelity.
- 3.74 quantization:** A method of reducing the precision of the individual coefficients to reduce the number of bits used to entropy-code them. This is equivalent to division while compressing and multiplying while decompressing. Quantization can be achieved by an explicit operation with a given quantization value or by dropping (truncating) coding passes from the codestream.
- 3.75 raster order:** A particular sequential order of data of any type within an array. The raster order starts with the top left data point and moves to the immediate right data point, and so on, to the end of the row. After the end of the row is reached the next data point in the sequence is the left-most data point immediately below the current row. This order is continued to the end of the array.
- 3.76 reconstructed image:** An image that is the output of a decoder.
- 3.77 reconstructed sample:** A sample reconstructed by the decoder. This always equals the original sample value in lossless coding but may differ from the original sample value in lossy coding.
- 3.78 reference grid:** A regular rectangular array of points used as a reference for other rectangular arrays of data. Examples include components and tiles.
- 3.79 reference tile:** A rectangular sub-grid of any size associated with the reference grid.
- 3.80 region of interest (ROI):** A collections of coefficients that are considered of particular relevance by some user-defined measure.
- 3.81 resolution level:** Equivalent to the decomposition level with one exception: the LL sub-band is also a separate resolution level.
- 3.82 reversible:** A transformation, progression, system or other process that does not suffer a systemic or quantization error and therefore, allows lossless signal recovery.
- 3.83 sample:** One element in the two-dimensional array that comprises a component.
- 3.84 segmentation symbol:** A special symbol coded with a uniform context at the end of each coding pass for error resilience.
- 3.85 selective arithmetic coding bypass:** A coding style where some of the code-block passes are not coded by the arithmetic coder. Instead, the bits to be coded are appended directly to the bit stream without coding.
- 3.86 shift:** Multiplication or division of a number by powers of two.
- 3.87 sign bit:** A bit that indicates whether a number is positive (zero value) or negative (one value).
- 3.88 sign-magnitude notation:** A binary representation of an integer where the distance from the origin is expressed with a positive number and the direction from the origin (positive or negative) is expressed with a separate single sign bit.
- 3.89 significance propagation pass:** A coding pass performed on a single bit-plane of a code-block of coefficients.
- 3.90 significance state:** State of a coefficient at a particular bit-plane. If a coefficient, in sign-magnitude notation, has the first magnitude 1 bit at or before the given bit-plane, it is considered "significant". If not, it is considered "insignificant".
- 3.91 source image:** An image used as input to an encoder.

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

- 3.93 sub-band coefficient:** A transform coefficient within a given sub-band.
- 3.94 sub-band decomposition:** A transformation of an image tile-component into sub-bands.
- 3.95 superbox:** A box that itself contains a contiguous sequence of boxes (and only a contiguous sequence of boxes). As the JP2 file contains only a contiguous sequence of boxes, the JP2 file is itself considered a superbox. When used as part of a relationship between two boxes, the term "superbox" refers to the box which directly contains the other box.
- 3.96 tile:** A rectangular array of points on the reference grid, registered with and offset from the reference grid origin and defined by a width and height. The tiles which overlap are used to define tile-components.
- 3.97 tile-component:** All the samples of a given component in a tile.
- 3.98 tile index:** The index of the current tile ranging from zero to the number of tiles minus one.
- 3.99 tile-part:** A portion of the codestream with compressed image data for some, or all of a tile. The tile-part includes at least one, and up to all of the packets that make up the coded tile.
- 3.100 tile-part header:** A group of markers and marker segments at the beginning of each tile-part in the codestream that describe the tile-part coding parameters.
- 3.101 tile-part index:** The index of the current tile-part ranging from zero to the number of tile-parts minus one in a given tile.
- 3.102 transformation:** A mathematical mapping from one signal space to another.
- 3.103 transform coefficient:** A value that is the result of a transformation.
- 3.104 XOR:** Exclusive OR logical operator.

4 Abbreviations and symbols

4.1 Abbreviations

For the purposes of this Recommendation | International Standard, the following abbreviations apply:

1D-DWT	One-dimensional Discrete Wavelet Transformation
CCITT	International Telegraph and Telephone Consultative Committee, now ITU-T
CPRL	Component, Position, Resolution and Layer data packet progression order within a tile
CSF	Contrast Sensitivity Function
DCP	Digital Cinema Package
FDWT	Forward Discrete Wavelet Transformation
FEC	Forward Error Correction
ICC	International Color Consortium
ICT	Irreversible Component Transform
IDWT	Inverse Discrete Wavelet Transformation
IEC	International Electrotechnical Commission
ISO	International Organization for Standardization
ITTF	Information Technology Task Force
ITU	International Telecommunication Union
ITU-T	International Telecommunication Union – Telecommunication Standardization Sector (formerly the CCITT)
JPEG	Joint Photographic Experts Group – The joint ISO/ITU committee responsible for developing standards for continuous-tone still picture coding. It also refers to the standards produced by this committee: Rec. ITU-T T.81 ISO/IEC 10918-1, Rec. ITU-T T.83 ISO/IEC 10918-2, Rec. ITU-T T.84 ISO/IEC 10918-3 and Rec. ITU-T T.87 ISO/IEC 14495.
LRCP	Layer, Resolution, Component and Position data packet progression order within a tile
LSB	Least Significant Bit

This is a preview of ISO/IEC 15444-1:2024. [Click here to purchase the full version from the ANSI store.](#)

PCRL	Position, Component, Resolution and Layer data packet progression order within a tile
PCS	Profile Connection Space
RCT	Reversible Component Transform
RLCP	Resolution, Layer, Component and Position data packet progression order within a tile
ROI	Region Of Interest
RPCL	Resolution, Position, Component and Layer data packet progression order within a tile
SNR	Signal-to-Noise Ratio
TCP	Transmission Control Protocol
UCS	Universal Character Set
URI	Uniform Resource Identifier
URL	Uniform Resource Locator
UUID	Universal Unique Identifier
XML	Extensible Markup Language
W3C	Worldwide web Consortium

4.2 Symbols

For the purposes of this Recommendation | International Standard, the following symbols apply:

$0x----$	Denotes a hexadecimal number
$\backslash mnn$	A three-digit number preceded by a backslash indicates the value of a single byte within a character string, where the three digits specify the octal value of that byte
ϵ_b	Exponent of the quantization value for a sub-band defined in QCD and QCC
μ_b	Mantissa of the quantization value for a sub-band defined in QCD and QCC
M_b	Maximum number of bit-planes coded in a given code-block
N_L	Number of decomposition levels as defined in COD and COC
R_b	Dynamic range of a component sample as defined in SIZ
CAP	Extended Capabilities marker
COC	Coding style component marker
COD	Coding style default marker
COM	Comment marker
CRG	Component registration marker
EPH	End of packet header marker
EOC	End of codestream marker
PLM	Packet length, main header marker
PLT	Packet length, tile-part header marker
POC	Progression order change marker
PPM	Packed packet headers, main header marker
PPT	Packed packet headers, tile-part header marker
PRF	Profile marker
PRFnum	Profile number as defined in PRF
QCC	Quantization component marker
QCD	Quantization default marker
RGN	Region-of-interest marker
SIZ	Image and tile size marker
SOC	Start of codestream marker