

This is a preview of "ISO/IEC 15962:2013". Click here to purchase the full version from the ANSI store.

Second edition
2013-03-15

Information technology — Radio frequency identification (RFID) for item management — Data protocol: data encoding rules and logical memory functions

Technologies de l'information — Identification par radiofréquence (RFID) pour la gestion d'objets — Protocole de données: règles d'encodage des données et fonctions logiques de mémoire

Reference number
ISO/IEC 15962:2013(E)



© ISO/IEC 2013

This is a preview of "ISO/IEC 15962:2013". Click here to purchase the full version from the ANSI store.



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

This is a preview of "ISO/IEC 15962:2013". Click here to purchase the full version from the ANSI store.

Contents

	Page
Foreword	vii
Introduction.....	viii
1 Scope.....	1
2 Normative references.....	1
3 Terms, definitions and conventions.....	2
3.1 Terms and definitions	2
3.2 Conventions	2
4 Conformance	2
4.1 Conformance with the air interface	2
4.2 Conformance with the application interface.....	2
4.3 Conformance with the Access-Method	3
5 Protocol model	4
5.1 Overview.....	4
5.2 Layered protocol	4
5.3 Flexible implementation configurations	6
5.4 Functional processes – interrogator implementation	6
5.5 ISO/IEC 15962 and the Data Processor.....	9
6 Data and presentation conventions	9
6.1 Data types in ISO/IEC 15961-1 commands and responses.....	10
6.2 Extensible bit vector (EBV)	10
6.3 Object Identifier presentation in the application interface.....	10
6.4 The Object	12
6.5 The 8-bit byte	12
6.6 N-bit encoding	12
7 Data Processor – high level processing	12
8 Data Processor and the application interface	13
8.1 Application commands – overview	13
8.2 Application commands and responses– write	15
8.3 Application commands and responses– read.....	31
8.4 Application commands and responses– other	40
8.5 Air interface support for application commands	49
9 Data Processor and the air interface.....	49
9.1 Air interface services	49
9.2 Defining the system information	50
9.3 Configuring the Logical Memory	58
10 The Command/Response Unit: processing of command and response arguments	58
10.1 Process arguments	59
10.2 Completion-Codes.....	71
10.3 Execution-Codes	74
11 Access-Method	74
11.1 No-Directory structure	75
11.2 Directory structure	77
11.3 Packed-Objects structure	79
11.4 Tag Data Profile	80
11.5 Multiple-Records	80

This is a preview of "ISO/IEC 15962:2013". Click here to purchase the full version from the ANSI store.

12	ISO/IEC 15434 direct encoding and transmission method using Access-Method 0 and Data-Format 3	86
12.1	General rules for ISO/IEC 15434 direct encoding	86
12.2	Specific support for ISO TC122 standards	87
13	Monomorphic-UII encoding	87
13.1	6-bit encoding	88
13.2	7-bit encoding	88
13.3	URN Code 40 encoding	88
13.4	8859-1 octet encoding	89
13.5	Application-defined 8-bit coding	89
Annex A (informative) Air interface support for application commands.....		90
A.1	Overview	90
A.2	ISO/IEC 18000-3 Mode 1 support.....	90
A.3	ISO/IEC 18000-6 Type C support	91
A.4	ISO/IEC 18000-6 Type D support	93
Annex B (normative) Pro forma description for the Tag Driver		96
B.1	Defining the Singulation-Id	96
B.2	System information : AFI	96
B.3	System information: DSFID	96
B.4	Memory-related parameters.....	96
B.5	Support for commands	97
Annex C (normative) ISO/IEC 18000 Tag Driver Descriptions		98
C.1	Tag Driver for ISO/IEC 18000-2: Parameters for air interface communications below 135 kHz.....	98
C.2	Tag Driver for Mode 1 of ISO/IEC 18000-3: Parameters for air interface communications at 13,56 MHz.....	99
C.3	Tag Driver for Mode 2 of ISO/IEC 18000-3: Parameters for air interface communications at 13,56 MHz.....	101
C.4	Tag Driver for ISO/IEC 18000-4: Parameters for air interface communications at 2,45 GHz - Mode 1.....	102
C.5	Tag Driver for ISO/IEC 18000-4: Parameters for air interface communications at 2,45 GHz - Mode 2.....	104
C.6	Tag Driver for ISO/IEC 18000-6 Type A: Parameters for air Interface Communications at 860 MHz to 960 MHz.....	104
C.7	Tag Driver for ISO/IEC 18000-6 Type B: Parameters for air Interface Communications at 860 MHz to 960 MHz.....	105
C.8	Tag Driver for ISO/IEC 18000-6 Type C: Parameters for air Interface Communications at 860 MHz to 960 MHz.....	107
C.9	Tag Driver for ISO/IEC 18000-6 Type D: Parameters for air Interface Communications at 860 MHz to 960 MHz.....	108
Annex D (normative) Encoding rules for No-Directory Access-Method		112
D.1	Object processing.....	112
D.2	Encoding the length of the compacted Object	114
D.3	Processing the Object-Identifier	114
D.4	Processing the Relative-OID.....	116
D.5	Encoding the length and Object-Identifier or Relative-OID	119
D.6	The Precursor.....	120
D.7	The Offset byte	121
D.8	The Precursor expansion byte	121
D.9	Decoding the Logical Memory.....	122
Annex E (normative) Basic Data Compaction Schemes		125
E.1	Integer compaction	125
E.2	Numeric compaction	125
E.3	5-bit compaction	126
E.4	6-bit compaction	126
E.5	7-bit compaction	127
E.6	Octet encodation.....	129

This is a preview of "ISO/IEC 15962:2013". Click here to purchase the full version from the ANSI store.

Annex F (normative) ISO/IEC 646 Characters Supported by the Compaction Schemes	130
Annex G (informative) Encoding example for No-Directory structure	133
G.1 Starting position	133
G.2 Encoding the Object-Identifiers	133
G.3 The initial state of the entry for the Logical Memory	133
G.4 The Logical Memory after data compaction	134
G.5 The Logical Memory after formatting for a No-Directory Access-Method	134
Annex H (informative) Encoding example for Directory structure.....	136
H.1 The base data.....	136
H.2 Encoding the first Directory entry	136
H.3 Encoding the second Directory entry	137
H.4 Encoding the remaining Directory entries.....	137
H.5 Decoding the Directory and reading the target Object-Identifier	138
Annex I (normative) Packed-Objects structure.....	139
I.1 Overview.....	139
I.2 Overview of associated Annexes	139
I.3 High-level Packed-Objects format design	139
I.4 Format Flags section	142
I.5 Object Info section	144
I.6 Secondary ID Bits section	150
I.7 Aux Format section	150
I.8 Data section	152
I.9 ID Map and Directory encoding options	155
Annex J (normative) Packed Objects ID Tables	161
J.1 Packed Objects Data Format registration file structure.....	161
J.2 Mandatory and Optional ID Table columns	163
J.3 Syntax of OIDs, IDString, and FormatString columns.....	166
J.4 OID input/output representation	168
Annex K (normative) Packed Objects Encoding tables.....	170
Annex L (informative) Encoding example for Packed Objects.....	175
Annex M (informative) Decoding Packed Objects	179
M.1 Overview.....	179
M.2 Decoding Alphanumeric data.....	180
Annex N (normative) Tag Data Profile encoding	183
N.1 Scope	183
N.2 The Registered Table	183
N.3 Encoding the Tag Data Profile on the RFID tag	184
N.4 Decoding the Tag Data Profile	186
N.5 Modifying Data.....	187
Annex O (normative) Tag Data Profile ID tables	188
O.1 Tag-Data-Profile Data-Format registration file structure.....	188
O.2 File Header section.....	189
O.3 Table Header section	189
O.4 Table Trailer section.....	190
O.5 Mandatory ID Table columns	190
Annex P (informative) Encoding example for Tag Data Profile.....	192
P.1 Encoded data segment	192
P.2 Encoding the header segment	195
Annex Q (normative) Basic encoding rules for Multiple-Records Access-Method	196
Q.1 Overview.....	196
Q.2 Encoding the Multiple-Records header.....	196
Q.3 Encoding the preamble of an individual record that is not part of a hierarchical structure	200
Q.4 The record	203
Q.5 The directory	203

This is a preview of "ISO/IEC 15962:2013". Click here to purchase the full version from the ANSI store.

Q.6	Appending a new record	207
Q.7	Modifying an existing record	208
Q.8	Deleting an existing record	208
Q.9	Constructing the Object-Identifier from the MR-header, preamble and individual record	209
Annex R (normative) Multiple-Records encoding rules for hierarchical records		212
R.1	Overview	212
R.2	Encoding the Multiple-Records header	213
R.3	Encoding the preamble of hierarchical record	214
R.4	The hierarchical record	216
R.5	Data element list	216
R.6	The directory	218
R.7	Appending a new record	218
R.8	Modifying an existing record	218
R.9	Deleting a record.....	218
Annex S (informative) Encoding example for the Multiple-Records Access-Method		219
S.1	The heterogeneous multiple record example	219
S.2	An encoding example of a homogeneous multiple record	226
S.3	An encoding example of a hierarchical multiple record.....	229
Annex T (normative) ISO/IEC 15434 Direct Encoding and Transmission		232
T.1	DSFID	232
T.2	Precursor byte.....	232
T.3	Data byte-count indicator	232
T.4	Encoding and Decoding.....	233
T.5	Encoding and Decoding Example using Data Identifiers	234
T.6	Additional Code Values and other Precursor features	236
Annex U (informative) ISO/IEC 15434 Direct DI Encoding and Transmission for ISO TC122 Standards		238
U.1	DSFID	238
U.2	Precursor byte.....	238
U.3	Data byte-count indicator	238
U.4	Encoding and Decoding.....	239
U.5	Encoding and Decoding Example.....	241
Annex V (normative) URN Code 40 encoding		243
V.1	Basic Character Set	243
V.2	Extended Encoding	244
V.3	Encoding Example.....	245
V.4	Resolver Example	245
Bibliography		246

This is a preview of "ISO/IEC 15962:2013". Click here to purchase the full version from the ANSI store.

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 15962 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 31, *Automatic identification and data capture techniques*.

This second edition cancels and replaces the first edition (ISO/IEC 15962:2004), which has been technically revised.

Introduction

The technology of radio frequency identification (RFID) is based on non-contact electronic communication across an air interface. The structure of the bits stored on the memory of the RFID tag is invisible and accessible between the RFID tag and the interrogator only by the use of an air interface protocol, as specified in the appropriate part of ISO/IEC 18000. The result of the transfer of data between an application and an interrogator in open systems requires data to be encoded in a consistent manner on any RFID tag that is part of that open system. This is not only to allow equipment to be interoperable, but in the special case of data carriers, for the data to be encoded on the RFID tag in one systems implementation for it to be read at a later time in a completely different and unknown systems implementation. The data bits stored on each RFID tag must be formatted in such a way as to be reliably read at the point of use if the RFID tag is to fulfil its basic objective. This reliability is achieved through the specification of a data protocol using the application-defined arguments defined in ISO/IEC 15961-1 and the data encoding rules of this International Standard. Additionally, ISO/IEC 24791-1 specifies a software system infrastructure architecture that enables RFID system operations between business applications and RFID interrogators. Specific parts of ISO/IEC 24791 address data management requirements (ISO/IEC 24791-2) and device interface requirements (ISO/IEC 24791-5). These support defined implementations that incorporate the encoding rules of this International Standard and the functional rules of the commands and responses in ISO/IEC 15961-1.

Manufacturers of RFID equipment (interrogators, RFID tags, etc.) and the users of RFID technology require a standards-based data protocol for RFID for item management. ISO/IEC 15961-1 to ISO/IEC 15961-3, this International Standard, and ISO/IEC 24791 specify this protocol, which is layered above the air interface standards defined in ISO/IEC 18000.

The transfer of data to and from an application, supported by appropriate application commands, is the subject of ISO/IEC 15961-1. This International Standard specifies the overall process and the methodologies developed to format the application data into a structure to store on the RFID tag.