International

ISO/IEC 18004

Information technology — Automatic identification and data capture techniques — QR code bar code symbology specification

Technologies de l'information — Technologie d'identification automatique et de capture des données — Spécification de la symbologie de code à barres code QR

Fourth edition
2024-08

Reference number
ISO/IEC 18004:2024(en)

COPYRIGHT PROTECTED DOCUMENT

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and https://patents.iec.ch. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 31, *Automatic identification and data capture techniques*.

This fourth edition cancels and replaces the third edition (ISO/IEC 18004:2015), which has been technically revised.

The main changes are as follows:

— continuous grading according to ISO/IEC 15415 has been adopted for grade fixed pattern damage;

— the reference decoding algorithm has been clarified.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

There are four technically different, but closely related members of the QR code family, which represent an evolutionary sequence.

— QR code model 1 is the original specification for QR code and is described in AIM ITS 97-001[21].

— QR code model 2 is an enhanced form of the symbology with additional features (primarily, the addition of alignment patterns to assist navigation in larger symbols) and is the basis of the first edition of this document (i.e. ISO/IEC 18004:2000).

— QR code [the basis of the second edition of this document (i.e. ISO/IEC 18004:2006)] is very similar to QR code model 2; its QR code format differs only in the addition of the facility for symbols to appear in a mirror image orientation for reflectance reversal (light symbols on dark backgrounds) and the option for specifying alternative character is set to the default.

— The micro QR code format [also specified in the second edition of this document (i.e. ISO/IEC 18004:2006)], is a variant of QR code with a reduced number of overhead modules and a restricted range of sizes, which enables small to moderate amount of data to be represented in a small symbol, particularly suited to direct marking on parts and components, and to applications where the space available for the symbol is severely restricted.

QR code is a matrix symbology. The symbols consist of an array of nominally square modules arranged in an overall square pattern, including a unique finder pattern located at three corners of the symbol (in micro QR code symbols, at a single corner) and intended to assist in easy location of its position, size and inclination. A wide range of sizes of symbol is provided for, together with four levels of error correction. Module dimensions are user-specific to enable symbol production by a wide variety of techniques.

QR code model 2 symbols are fully compatible with QR code reading systems.

QR code model 1 symbols are recommended only to be used in closed system applications. Equipment complying with this document are not required to support QR code model 1 symbols. Since QR code is the recommended model for new, open system application of QR code, this document describes QR code fully. This document also lists the features in which QR code model 1 differs from QR code in Annex N.