

Third edition
2009-04-15

**Information technology —
Telecommunications and information
exchange between systems — Corporate
telecommunication networks —
Tunnelling of QSIG over SIP**

*Technologies de l'information — Télécommunications et échange
d'information entre systèmes — Réseaux de télécommunications
d'entreprise — Tunnellisation de QSIG sur SIP*

Reference number
ISO/IEC 22535:2009(E)



This is a preview of "ISO/IEC 22535:2009". [Click here to purchase the full version from the ANSI store.](#)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

This is a preview of "ISO/IEC 22535:2009". Click here to purchase the full version from the ANSI store.

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Abbreviated terms	3
5 Background and architecture.....	3
5.1 Architecture.....	3
5.2 Basic operation	4
5.3 QSIG connectionless transport.....	5
5.4 Late availability of SDP parameters at the egress gateway	5
6 Procedures	5
6.1 General.....	5
6.2 Encapsulation of QSIG messages in SIP messages.....	5
6.3 QSIG SETUP message handling at an ingress gateway.....	6
6.3.1 Sending a SIP INVITE request	6
6.3.2 Receipt of responses to the INVITE request.....	6
6.4 QSIG SETUP message handling at an egress gateway.....	7
6.4.1 Receiving a SIP INVITE request	7
6.4.2 Rejecting a QSIG message in an INVITE request.....	8
6.5 Subsequent QSIG messages.....	8
6.6 Terminating the SIP dialog	8
6.7 QSIG connectionless message handling at an ingress gateway	9
6.7.1 Sending a SIP INVITE request	9
6.7.2 Receipt of responses to the INVITE request.....	9
6.8 QSIG connectionless message handling at an egress gateway.....	10
7 Example message sequences	10
7.1 Call establishment	10
7.2 Call clearing.....	11
7.3 QSIG connectionless message	12
7.4 Call establishment with port=0 in first SDP answer.....	13
7.5 Backwards compatibility with early editions	14
8 Security considerations	16
Annex A (informative) Changes from early editions.....	17
Bibliography	19

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 22535 was prepared by Ecma International (as ECMA-355) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

This third edition cancels and replaces the second edition (ISO/IEC 22535:2006), which has been technically revised.

This is a preview of "ISO/IEC 22535:2009". [Click here to purchase the full version from the ANSI store.](#)

Introduction

This International Standard is one of a series of Standards defining the interworking of services and signalling protocols deployed in corporate telecommunication networks (CNs) (also known as enterprise networks). The series uses telecommunication concepts as developed by ITU-T and conforms to the framework of International Standards on Open Systems Interconnection as defined by ISO/IEC.

"QSIG" is a signalling protocol that operates between Private Integrated services Network eXchanges (PINX) within a Private Integrated Services Network (PISN). A PISN provides circuit-switched basic services and supplementary services to its users. QSIG is specified in Standards, in particular ISO/IEC 11572, ISO/IEC 11582 and a number of Standards specifying individual supplementary services.

NOTE The name QSIG was derived from the fact that it is used for signalling at the Q reference point. The Q reference point is a point of demarcation between two PINXs (ISO/IEC 11572).

SIP is an application layer protocol for establishing, terminating and modifying multimedia sessions. It is typically carried over IP (RFC 791), (RFC 2460). Telephone calls are considered as a type of multimedia session where just audio is exchanged. SIP is defined in RFC 3261.

Often a CN comprises both PISNs employing QSIG and IP networks employing SIP. A call or call independent signalling can originate at a user connected to a PISN and terminate at a user connected to an IP network or vice versa. In either case, a gateway provides interworking between QSIG and SIP at the boundary between the PISN and the IP network. Basic call interworking at a gateway is specified in ISO/IEC 17343. Another case is where a call or call independent signalling originates at a user connected to a PISN, traverses an IP network using SIP, and terminates at a user connected to another (or another part of the same) PISN. This document addresses this last case in a way that preserves all QSIG capabilities across the IP network. It achieves this by tunnelling QSIG messages within SIP requests and responses in the context of a SIP dialog.

This International Standard specifies tunnelling of QSIG over the Session Initiation Protocol (SIP). This enables calls between "islands" of circuit switched networks that use QSIG signalling to be interconnected by an IP network that uses SIP signalling without loss of QSIG functionality. This International Standard facilitates the introduction of enhanced SIP and SDP functionality that was specified after publication of the early editions of this International Standard. These enhancements include payload encryption and mechanisms to negotiate SDP capabilities.

The changes in this International Standard comprise a mandatory payload renegotiation with reversed direction of the offer/answer exchange compared with early editions. In order to achieve backward compatibility with early editions an indicator for the changed signalling procedures is introduced. This indicator is used to dynamically detect if fallback to signalling procedures compliant to early editions is necessary.

This International Standard is based upon the practical experience of Ecma member companies and the results of their active and continuous participation in the work of ISO/IEC JTC 1, ITU-T, IETF, ETSI and other international and national standardization bodies. It represents a pragmatic and widely based consensus.