

ISO/IEC 24791-5

Information technology — Radio frequency identification for item management software system infrastructure —

Part 5: Device interface

Technologies de l'information — Identification de radiofréquence (RFID) pour la gestion d'élément — Infrastructure de systèmes logiciels —

Partie 5: Interface de dispositif

Second edition
2025-10

This is a preview of ISO/IEC 24791-5:2025. Click [here](#) to purchase the full version from the ANSI store.



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2025

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

This is a preview of ISO/IEC 24791-5:2025. [Click here to purchase the full version from the ANSI store.](#)

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Abbreviated terms	2
5 Conformance	2
6 Software system infrastructure architecture overview	3
7 UML modelling	3
8 Device interface	4
8.1 General.....	4
8.2 Architecture.....	4
9 LLRP extensions abstract definitions	4
9.1 General.....	4
9.2 LLRP data types.....	5
9.3 ObjectIdentifier field type.....	6
9.4 ISO15962Read parameter.....	6
9.4.1 General.....	6
9.4.2 Conformance requirement.....	6
9.5 OID parameter.....	7
9.5.1 General.....	7
9.5.2 Conformance requirement.....	7
9.6 ISO15962ReadResult parameter.....	8
9.6.1 General.....	8
9.6.2 Conformance requirement.....	8
9.7 ISO15962OIDReadResult parameter.....	9
9.7.1 General.....	9
9.7.2 Conformance requirement.....	9
9.8 ISO15962RawDataReadResult parameter.....	10
9.8.1 General.....	10
9.8.2 Conformance requirement.....	10
10 LLRP extensions binary encoding	11
10.1 General.....	11
10.2 ISO15962Read parameter.....	11
10.3 OID parameter.....	11
10.4 ISO15962ReadResult parameter.....	12
10.5 ISO15962OIDReadResult parameter.....	12
10.6 ISO15962RawDataReadResult parameter.....	13
Annex A (informative) LLRP open source project references	14
Annex B (informative) UTF-8 and 8859-1 conversion algorithms	15
Bibliography	18

This is a preview of ISO/IEC 24791-5:2025. [Click here to purchase the full version from the ANSI store.](#)

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and <https://patents.iec.ch>. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 31, *Automatic identification and data capture techniques*.

This second edition cancels and replaces the first edition (ISO/IEC 24791-5:2012), which has been technically revised.

The main change is as follows: references to ISO/IEC 19762 and Type C of ISO/IEC 18000-63:2021 have been corrected.

A list of all parts in the ISO/IEC 24791 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

This is a preview of ISO/IEC 24791-5:2025. [Click here to purchase the full version from the ANSI store.](#)

Radio frequency identification (RFID) air interface technology is based on non-contact electro-magnetic communication among interrogators and tags. RFID software systems are composed of RFID interrogators, intermediate software systems, and applications that provide control and coordination of air interface operation, tag information exchange, and health and performance management of system components. RFID technology is expected to increase effectiveness in many aspects of business by further advancing the capabilities of automatic identification and data capture (AIDC). To achieve this goal through the successful adoption of RFID technology into real business environments, RFID devices, software systems and business applications must provide secure and interoperable services, interfaces and technologies. This is the goal of the ISO/IEC 24791 series, which cover RFID software system infrastructure (SSI). The composition and operations of SSI exist in systems that implement other RFID standards, such as the ISO/IEC 18000 series which describes air interfaces, and ISO/IEC 15962, the ISO/IEC 15963 series and ISO/IEC 24753 which describe data and interface functions.

The goal of this document is to define a device interface that provides RFID controlling software with low-level access to RFID air interface hardware. This low-level access gives programmers a degree of control over the sequencing of air protocol commands and direct access to air protocol command parameter. Using this low-level interface, programmers can optimize RFID data access and control operations.

The interface defined by this document supports the following features:

- efficient, binary transfer syntax over transmission control protocol/internet protocol (TCP/IP);
- access to RFID air protocol commands and command parameters;
- support for optimized RFID tag access operations whereby multiple operations can be performed on a tag with minimal tag state changes;
- direct read or write access to all data on an RFID tag;
- read one or more individual tag data items (encoded as defined by ISO/IEC 15962) as specified by their '0 object identifier (OID) using uniform resource name (URN) notation;
- [optional] decode data items (encoded as defined by ISO/IEC 15962) into their Unicode representation (UTF-8 encoded) – encoding data items is not supported;
- support for RFID air protocol type defined by Type C of ISO/IEC 18000-63:2021.

The interface defined in this document provides access to RFID air protocol commands and their respective command parameters. Therefore, using this interface, tag memory banks can be locked, tags can be killed, and raw-binary RFID tag data can be accessed directly on a tag for both reading and writing. In addition, individual data items (encoded as defined by ISO/IEC 15962) can be read by specifying each data item's OID. Optionally, the interrogator can decode data items read into their character string representation. If the interrogator cannot decode a data item, then it will return the entire encoded package within which the data item resides. In this case, it is the responsibility of higher-level software to further decode the data item. The interface does not support RFID tag data encoding. It is the responsibility of higher-level software (i.e. software outside the interface defined by this document) to perform data encoding (e.g. by binary tag data representation as defined by ISO/IEC 15962) that is stored on RFID tags.

This document is an extension to GS1™ LLRP. As does GS1™ LLRP, this document defines both the abstract functional capabilities of the interrogator interface and the binary transfer syntax between the interrogator and a controlling system device. The transfer syntax is defined to be communicated over TCP/IP.