

This is a preview of "ISO/IEC 29164:2011". [Click here to purchase the full version from the ANSI store.](#)

First edition  
2011-10-01

---

---

## Information technology — Biometrics — Embedded BioAPI

*Technologies de l'information — Biométrie — BioAPI incorporé*

---

---

Reference number  
ISO/IEC 29164:2011(E)



This is a preview of "ISO/IEC 29164:2011". [Click here to purchase the full version from the ANSI store.](#)



**COPYRIGHT PROTECTED DOCUMENT**

© ISO/IEC 2011

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

This is a preview of "ISO/IEC 29164:2011". Click here to purchase the full version from the ANSI store.

## Contents

Page

Foreword .....	iv
Introduction.....	v
1 Scope .....	1
2 Conformance .....	1
3 Normative references .....	2
4 Terms and definitions .....	2
5 Symbols and abbreviated terms .....	3
6 Embedded BioAPI environment.....	4
6.1 Operating environment of Embedded BioAPI .....	4
6.2 Security in Embedded BioAPI.....	6
7 Embedded BioAPI general architecture.....	6
8 Frames structure .....	9
9 Patron format for Embedded BioAPI.....	10
10 Security block format for Embedded BioAPI .....	10
10.1 Security Block format owner.....	10
10.2 Security Block format owner identifier .....	10
10.3 Security Block format name .....	10
10.4 Security Block format identifier .....	10
10.5 ASN.1 object identifier for this security Block format.....	11
10.6 Domain of use.....	11
10.7 Version identifier .....	11
10.8 CBEFF version.....	11
10.9 General .....	11
10.10 Specification .....	11
11 Data types, formats and coding.....	12
11.1 Slave ID field [S] .....	12
11.2 Command field [C].....	12
11.3 Status/Error field [E].....	13
11.4 Biometric modalities coding .....	13
12 Commands definition.....	14
12.1 Management commands.....	15
12.2 Template management commands .....	18
12.3 Enrolment commands.....	20
12.4 Biometric process commands .....	22
Annex A (normative) Conformance Requirements .....	29
Annex B (informative) Examples of frame implementations .....	31
Annex C (informative) Command exchange examples for several scenarios.....	33

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 29164 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 37, *Biometrics*.

This is a preview of "ISO/IEC 29164:2011". [Click here to purchase the full version from the ANSI store.](#)

## Introduction

The environment for embedded systems differs in many ways from that of a more general computing environment. One difference is that the amount of processing power and/or memory/storage can be more limited in the embedded environment and operating system support and resources can also be more constrained. As a result, implementation of more general purpose interfaces might not be appropriate. In the case of embedded biometric technology, the algorithms and sensors are frequently packaged into hardware/firmware modules.

It can also be the case that the designer of the embedded system is not concerned with details of the biometric technology within its software and firmware and prefers to just integrate an external module that deals with some or all biometric functionalities.

This International Standard is not meant for applications where the integration of biometric functionality is going to be done within the software or firmware of the application. In such cases BioAPI (ISO/IEC 19784-1) is to be used, or its Frameworkless version (see ISO/IEC 19784-1 with Amd.2).

The interface defined in this International Standard provides a direct connection with such biometric modules. The definition of this interface is given by the services to be provided, as well as the message formats for commands to be sent to biometric modules and responses expected from them.

This International Standard is intended to provide a common interface for all those biometric systems where BioAPI (ISO/IEC 19784-1) cannot be implemented. From the historical point of view, as BioAPI does imply relatively large requirements both in processing power and memory capacity, some different approaches have been developed. One of those approaches is the use of BioAPI without the need of using the BioAPI framework, which is one of the most consuming parts of BioAPI. That version is called Framework free BioAPI, and is standardized in the 2<sup>nd</sup> Amendment to BioAPI. But even that approach, which can be of great help for several applications, such as Biometric Applets or Biometric services in mobile devices which run an Operating System, can be too demanding for embedded systems. Therefore a new approach is standardized in this International Standard, under the name of Embedded BioAPI, which should never be confused with the Framework free version of BioAPI.

Examples of applications where Embedded BioAPI might be used include remote controls, garage door openers, auto ignitions, physical access devices, memory sticks, authentication tokens, and handheld weapons. The utility of a standard interface in this environment is less obvious than for more general purpose processing environments, but addresses two important situations:

- It allows a device (unit into which the data capture device is embedded, e.g. a remote control device) manufacturer to use the same code base for multiple devices/units in his product line that differ only in embedded data capture device/biometric technology (e.g. Device A comes with a built-in fingerprint data capture device/algorithm and Device B comes with a built-in facial recognition camera/capability). This is a configuration management (CM) and efficiency issue (the single code base simplifying CM).
- It allows an OEM data capture device manufacturer who wants to build a single OEM unit/firmware to support multiple device vendors (the same firmware regardless of what device the data capture device unit is embedded within).

Throughout the text of this International Standard, devices suitable to be using Embedded BioAPI will be referred as "Embedded BioAPI subcomponents". Noting that other kind of devices can also use this International Standard, this notation has been used for improving understanding of the standard. This International Standard does not state any requirement for those devices (e.g. Embedded BioAPI subcomponents) but those needed as to implement Embedded BioAPI.