



# TECHNICAL REPORT

---

**Information technology – Fibre channel –  
Part 312: Avionics environment upper layer protocol (FC-AE 1553)**





**THIS PUBLICATION IS COPYRIGHT PROTECTED**

**Copyright © 2009 ISO/IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland  
Email: [inmail@iec.ch](mailto:inmail@iec.ch)  
Web: [www.iec.ch](http://www.iec.ch)

### **About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### **About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: [www.iec.ch/online\\_news/justpub](http://www.iec.ch/online_news/justpub)

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: [www.iec.ch/webstore/custserv](http://www.iec.ch/webstore/custserv)

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: [csc@iec.ch](mailto:csc@iec.ch)  
Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00



# TECHNICAL REPORT

---

**Information technology – Fibre channel –  
Part 312: Avionics environment upper layer protocol (FC-AE 1553)**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE



## CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references .....	8
3 Terms, definitions and conventions.....	8
3.1 General considerations.....	8
3.2 Terms and definitions .....	9
3.3 Conventions .....	10
3.3.1 General .....	10
3.3.2 Binary notation .....	11
3.3.3 Hexadecimal notation .....	11
3.3.4 Abbreviations and acronyms.....	11
3.4 Applicability and use of this document.....	11
4 FC-AE-1553 profile.....	12
4.1 General.....	12
4.2 FC-AE-1553 elements .....	12
4.3 Mapping legacy 1553 applications to FC-AE-1553.....	13
4.3.1 General .....	13
4.3.2 NT address.....	14
4.3.3 NT subaddress .....	14
4.3.4 Byte Count/Mode code .....	15
4.4 FC-AE-1553 ULP features .....	15
4.4.1 Information units.....	15
4.4.2 Exchange formats.....	20
4.4.3 FC-AE-1553 ULP profile .....	40
4.4.4 MIL-STD-1553 ULP mapping to FC-AE-1553 .....	44
Annex A (normative) FC-AE-1553 process login .....	72
A.1 Overview of process login and process logout .....	72
A.2 PRLI.....	73
A.2.1 Use of PRLI by FC-AE-1553.....	73
A.2.2 Process_Associator requirements .....	73
A.2.3 New or repeated process login .....	73
A.2.4 PRLI payload page length and payload length fields.....	73
A.2.5 PRLI request FC-AE-1553 service parameter page format.....	74
A.2.6 Operation of PRLI service parameters which are common to NC and NT.....	78
A.3 A.3 PRLO .....	79
Annex B (informative) FC-AE-1553 Fibre Channel profile.....	80
B.1 General .....	80
B.2 FC-FS-2 and FC-AL-2 features for FC-AE-1553.....	80
B.3 Point-to-point and link protocols .....	83
B.4 Arbitrated loop-specific features .....	83
B.5 Fabric login .....	84
B.5.1 Introduction .....	84

B.5.2 Fabric login – Common service parameters .....	84
B.5.3 Fabric login – Class specific service parameters .....	85
B.6 Port login.....	85
B.6.1 General .....	85
B.6.2 Classes of service supported.....	85
B.6.3 N_Port Login – Common service parameters.....	85
B.6.4 N_Port login – Class 3 service parameters .....	86
B.7 Basic link services .....	86
B.8 Broadcast and multicast support.....	86
B.9 FC-FS header fields .....	86
B.9.1 R_CTL field .....	86
B.9.2 TYPE field .....	86
B.9.3 Optional headers .....	86
B.9.4 Frame control (F_CTL) .....	86
B.9.5 Sequence identifier (SEQ_ID).....	87
B.9.6 Data field control (DF_CTL).....	87
B.9.7 Sequence count (SEQ_CNT).....	87
B.9.8 Originator exchange identifier (OX_ID).....	87
B.9.9 Responder exchange identifier (RX_ID).....	87
B.10 Extended link services.....	87
B.11 Well known address support.....	88
Annex C (informative) Bridging from FC-AE-1553 networks to MIL-STD-1553 buses.....	89
Bibliography.....	91
Figure 1 – Network Controller To Network Terminal transfers: NT Burst Size Request = '0'b, Delayed NT Burst Size Request = '0'b.....	21
Figure 2 – Network Controller To Network Terminal Transfers: NT Burst Size Request = '1'b, Delayed NT Burst Size Request = '0'b.....	22
Figure 3 – Network Controller to Network Terminal transfers: NT Burst Size Request = '0'b, Delayed NT Burst Size Request = '1'b.....	23
Figure 4 – Network Terminal-to-Network Controller .....	25
Figure 5 – NT-to-NT Transfers: NT Burst Size Request = '0'b, Delayed <i>NT Burst Size Request</i> = '0'b .....	26
Figure 6 – NT-to-NT transfers: NT Burst Size Request = '1'b, Delayed NT Burst Size Request = '0'b .....	28
Figure 7 – NT-to-NT Transfers: Originating NC is also receiving NT, with NT Burst Size Request = '1'b, Delayed NT Burst Size Request = '0'b .....	29
Figure 8 – NT-to-NT transfers: Delayed NT Burst Size Request = '1'b, NT Burst Size Request = '0'b .....	31
Figure 9 – NT-to-NT transfers: originating NC is also receiving NT, with delayed NT Burst Size Request = '1'b, NT Burst Size Request = '0'b.....	33
Figure 10 – Mode command without Data Word .....	35
Figure 11 – Transmit Mode Command with Data Word.....	35
Figure 12 – Receive Mode command with Data Word .....	36
Figure 13 – NC-to-NTs transfers (broadcast or multicast) .....	36
Figure 14 – Network Terminal to Multiple Network Terminals .....	38
Figure 15 – Transmit mode command without Data Word to Multiple Network Terminals.....	39

Figure 16 – Receive mode command with Data Word to Multiple Network Terminals .....	40
Figure 17 – FC-AE-1553 ULP timers: (a) NT_C/S_TOV and NT_C-D/S_BURST_TOV; (b) NC_C/S_TOV and NC_C-D/S_BURST_TOV; (c) C-S/D_TX_TOV (shown for NC and NT); (d) C-S/D_RX_TOV (shown for NC and NT) .....	62
Figure C.1 – FC-AE-1553 network to MIL-STD-1553 bus bridge.....	89
Table 1 – Summary and use of features.....	12
Table 2 – Terminology equivalents between MIL-STD-1553 and FC-AE-1553 .....	13
Table 3 – Comparison of MIL-STD-1553 and FC-AE-1553 Command Field Sizes.....	14
Table 4 – Information units transmitted by the Network Controller to Network Terminal, and transmissions by the transmitting NT for NT-to-NT or NT-to-NTs transfers .....	16
Table 5 – Information Units Initiated from the Network Terminal, Excluding Transmissions by the Transmitting NT for NT-to-NT or NT-to-NTs Transfers.....	19
Table 6 – FC-4 profile for FC-AE-1553.....	41
Table 7 – FC-AE-1553 command sequence header .....	46
Table 8 – Multicast address or other Port_ID Field.....	52
Table 9 – FC-AE-1553 status sequence header .....	57
Table 10 – Correct values for F_CTL field bits .....	64
Table 11 – Values for D_ID field (for broadcast); NT-to-NT Transfer, T/R*, Tx RDMA, and RDMA bits; subaddress, byte Count/Mode code, and other subaddress fields.....	65
Table 12 – Correct values for fourth word of FC-AE-1553 header extension.....	69
Table 13 – Correct Values for multicast address or other Port_ID field.....	69
Table A.1 – FC-AE-1553 PRLI service parameter page, PRLI request and accept .....	74
Table A.2 – FC-AE-1553 PRLI service parameters – corresponding words/bits for PRLI parameters which are common to NC and NT operation.....	79
Table B.1 – FC-FS and FC-AL-2 Features for FC-AE-1553 .....	80
Table C.1 – Use of FC-AE-1553 subaddress and/or other subaddress field for command sequences involving bridging to MIL-STD-1553 RTs .....	89

## INFORMATION TECHNOLOGY – FIBRE CHANNEL –

### Part 312: Avionics environment upper layer protocol (FC-AE 1553)

#### FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 10) Attention is drawn to the possibility that some of the elements of this Technical Report, type XX may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC and ISO technical committees is to prepare International Standards. In exceptional circumstances, ISO/IEC JTC 1 or a subcommittee may propose the publication of a technical report of one of the following types:

- type 1, when the required support cannot be obtained for the publication of an International Standard, despite repeated efforts;
- type 2, when the subject is still under technical development or where, for any other reason, there is the future but not immediate possibility of an agreement on an International Standard;
- type 3, when the technical committee has collected data of a different kind from that which is normally published as an International Standard, for example 'state of the art'.

Technical reports of types 1 and 2 are subject to review within three years of publication to decide whether they can be transformed into International Standards. Technical reports of

type 3 do not necessarily have to be reviewed until the data they provide are considered to be no longer valid or useful.

ISO/IEC TR 14165-312, which is a technical report of type 2, was prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

This document is issued in the type 2 technical report series of publications (according to 16.2.2 of the Procedures for the technical work of ISO/IEC JTC 1 (5<sup>th</sup> edition, 2004)) as a prospective standard for provisional application in the field of avionics, because there is an urgent requirement for guidance on how standards in this field should be used.

This document is not to be regarded as an International Standard. It is proposed for provisional application so that information and experience of its use in practice may be gathered. Comments on the content of this document should be sent to IEC Central Office.

A review of this type 2 technical report will be carried out not later than three years after its publication with the option of extension for a further three years, conversion into an International Standard or withdrawal.

This Technical Report has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

## INTRODUCTION

This part of ISO/IEC 14165 defines a set of features necessary to implement a real-time Fibre Channel network (point-to-point, switched fabric, or arbitrated loop) supporting the FC-AE-1553 Upper Level Protocol.

FC-AE-1553 is intended to support bi-directional communication between two or more N\_Ports in a constrained and carefully defined environment, typical of avionics applications. The intended usage is avionic command, control, instrumentation, simulation, signal processing, file distribution, and sensor/video data distribution. These application areas are characterized by a variety of requirements, among them a need for high reliability, fault tolerance, and deterministic behavior to support real-time command/response.

The FC-AE-1553 protocol is based on MIL-STD-1553B Notice 2 with extensions in bandwidth, address space, and data transfer size in order to support low-latency, low overhead communication between elements of a mission-critical avionics system. Some of the key features of FC-AE-1553 are its command/response protocol; options for acknowledged or unacknowledged messaging, RDMA transfers, file transfers; along with the capability to bridge to legacy MIL-STD-1553 terminals.

This part of ISO/IEC 14165 is divided into 4 clauses:

Clause 1 is the scope of this part of ISO/IEC 14165.

Clause 2 enumerates the normative references that apply to this part of ISO/IEC 14165.

Clause 3 describes the definitions, abbreviations, and conventions used in this part of ISO/IEC 14165.

Clause 4 defines the FC-AE-1553 Upper Level Protocol. This clause indicates whether features are Required, Prohibited, Allowed, or Invocable in FC-AE-1553.

This part of ISO/IEC 14165 has three annexes:

Annex A is a normative annex which defines Process Login for the FC-AE-1553 upper layer protocol.

Annex B is an informative annex that contains a profile of the FC-FS and FC-AL-2 standards as an example for avionics Fibre Channel network which uses FC-AE-1553.

Annex C is an informative annex providing information regarding bridging between FC-AE-1553 Fibre Channel networks and MIL-STD-1553 buses.

## INFORMATION TECHNOLOGY – FIBRE CHANNEL –

### Part 312: Avionics environment upper layer protocol (FC-AE 1553)

#### 1 Scope

This part of ISO/IEC 14165 is intended to serve as an implementation guide to maximize the likelihood of interoperability between conforming implementations. This part of ISO/IEC 14165 Prohibits or Requires features that are optional, and Prohibits the use of some non-optional features in the referenced specifications (see Clause 2).

In addition, this part of ISO/IEC 14165 simplifies implementations and their associated documentation, testing, and support requirements.

This Technical Report does not define internal characteristics of conformant implementations. This part of ISO/IEC 14165 incorporates features from the normative references in Clause 2.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

The provisions of the referenced specifications other than ISO/IEC, IEC, ISO and ITU documents, as identified in this clause, are valid within the context of this document. The reference to such a specification within this document does not give it any further status within ISO or IEC. In particular, it does not give the referenced specification the status of an International Standard.

ISO/IEC 14165-122, *Information technology – Fibre channel – Part 122: Arbitrated loop–2 (FC-AL-2)* [INCITS 332-1999]

ISO/IEC 14165-251, *Information technology – Fibre channel – Part 251: Framing and signalling (FC-FS)* [ANSI INCITS 373:2003]

ISO/IEC 14165-261, *Information technology – Fibre Channel – Part 261: Link Services (FC-LS)* (in preparation)

ANSI INCITS 424, *Information technology – Fibre channel – Framing and Signaling-2 (FC-FS-2)*

#### 3 Terms, definitions and conventions

##### 3.1 General considerations

For FC-AE-1553 (this document), the following terms and definitions, conventions, abbreviations, and acronyms apply. Words used that are defined in referenced standards shall use that definition. Words not defined here or in the referenced standards shall have the standard technical English meaning. See 3.3 for typographical conventions in order to distinguish words or phrases that have special definitions.