

First edition
2002-12-15

Gas cylinders — Refillable seamless steel — Performance tests —

Part 3:

Fracture performance tests — Cyclical burst tests

Bouteilles à gaz — Rechargeables en acier sans soudure — Essais de performance —

Partie 3: Essais de mode de rupture — Essais de rupture cyclique



Reference number
ISO/TR 12391-3:2002(E)

© ISO 2002

This is a preview of "ISO/TR 12391-3:2002". [Click here to purchase the full version from the ANSI store.](#)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2002

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

This is a preview of "ISO/TR 12391-3:2002". [Click here to purchase the full version from the ANSI store.](#)

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 References	1
3 Symbols	2
4 Background information	2
5 Experimental test programme	4
5.1 Types of cylinder tested	4
5.2 Material properties tests	5
5.3 Description of the flawed-cylinder cyclical burst test	6
6 Flawed-cylinder cyclical burst test results	8
6.1 Flawed-cylinder burst test procedure	8
6.2 Flawed-cylinder cyclical burst test results for group B materials	9
6.3 Flawed-cylinder cyclical burst test results for group C materials	10
6.4 Flawed-cylinder cyclical burst test results for group D materials	11
7 Discussion	13
7.1 Background	13
7.2 ISO 9809-2 flawed-cylinder cyclical burst test procedures and acceptance criteria	13
7.3 Comparison of the flawed-cylinder cyclical burst test with the flawed-cylinder burst test with monotonic pressurization to evaluate fracture performance	14
8 Summary and conclusions	15
Bibliography	47

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In exceptional circumstances, when a technical committee has collected data of a different kind from that which is normally published as an International Standard ("state of the art", for example), it may decide by a simple majority vote of its participating members to publish a Technical Report. A Technical Report is entirely informative in nature and does not have to be reviewed until the data it provides are considered to be no longer valid or useful.

Attention is drawn to the possibility that some of the elements of this part of ISO/TR 12391 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/TR 12391-3 was prepared by Technical Committee ISO/TC 58, *Gas cylinders*, Subcommittee SC 3, *Cylinder design*.

ISO/TR 12391 consists of the following parts, under the general title *Gas cylinders — Refillable seamless steel — Performance tests*:

- *Part 1: Philosophy, background and conclusions*
- *Part 2: Fracture performance tests — Monotonic burst tests*
- *Part 3: Fracture performance tests — Cyclical burst tests*
- *Part 4: Flawed-cylinder cycle test*

This is a preview of "ISO/TR 12391-3:2002". [Click here to purchase the full version from the ANSI store.](#)

Introduction

Gas cylinders as specified in ISO 9809-1 have been constructed of steel with a maximum tensile strength of less than 1 100 MPa. With the technical changes in steel-making using a two-stage process, referred to as ladle metallurgy or secondary refining, significant improvement in mechanical properties have been achieved. These improved mechanical properties provide the opportunity of producing gas cylinders with higher tensile strength and which achieve a lower ratio of steel to gas weight. The major concern in using steels of higher tensile strength with correspondingly higher design wall stress is safety throughout the life of the gas cylinder.

When ISO/TC 58/SC 3 began drafting ISO 9809-2, Working Group 14 was formed to study the need for additional controls for the manufacture of steel gas cylinders having a tensile strength greater than 1 100 MPa.

This part of ISO/TR 12391 presents all of the specific test results of the monotonic, flawed-cylinder burst tests that were conducted in order to evaluate the fracture performance of cylinders ranging in tensile strength from less 750 MPa to greater than 1 210 MPa.