

This is a preview of "ISO/TR 22676:2006". [Click here to purchase the full version from the ANSI store.](#)

First edition  
2006-10-01

---

---

## **Prosthetics — Testing of ankle-foot devices and foot units — Guidance on the application of the test loading conditions of ISO 22675 and on the design of appropriate test equipment**

*Prothèses — Essais de mécanismes cheville-pied et unités de pied — Directives d'application des conditions de force d'essai selon l'ISO 22675 et de la conception d'équipement d'essai approprié*



Reference number  
ISO/TR 22676:2006(E)

© ISO 2006

This is a preview of "ISO/TR 22676:2006". [Click here to purchase the full version from the ANSI store.](#)

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

This is a preview of "ISO/TR 22676:2006". [Click here to purchase the full version from the ANSI store.](#)

## Contents

Page

Foreword.....	vi
Introduction .....	vii
<b>1 Scope .....</b>	<b>1</b>
<b>2 Guidance on the specification of the test loading conditions of ISO 22675 .....</b>	<b>1</b>
<b>2.1 General.....</b>	<b>1</b>
<b>2.2 Directions of static and maximum cyclic heel and forefoot reference loading .....</b>	<b>1</b>
<b>2.2.1 Basic relationships and conditions .....</b>	<b>1</b>
<b>2.2.2 Lines of action of the resultant reference forces <math>F_{R1}</math> and <math>F_{R2}</math> .....</b>	<b>2</b>
<b>2.2.3 Position of the top load application point <math>P_T</math>.....</b>	<b>3</b>
<b>2.3 Magnitudes of static and maximum cyclic heel and forefoot reference loading .....</b>	<b>6</b>
<b>2.4 Reference test loading conditions of static and cyclic tests .....</b>	<b>7</b>
<b>2.4.1 Static tests.....</b>	<b>7</b>
<b>2.4.2 Cyclic test .....</b>	<b>8</b>
<b>3 Guidance on the design of appropriate test equipment for the application of ISO 22675.....</b>	<b>20</b>
<b>3.1 Background statement.....</b>	<b>20</b>
<b>3.2 Basic design for test equipment .....</b>	<b>20</b>
<b>3.3 Design variants for load application.....</b>	<b>24</b>
<b>3.3.1 General.....</b>	<b>24</b>
<b>3.3.2 Design variant A.....</b>	<b>24</b>
<b>3.3.3 Design variant B.....</b>	<b>24</b>
<b>3.3.4 Main differences between design variants A and B.....</b>	<b>25</b>
<b>3.4 Examples of crank gear designs.....</b>	<b>25</b>
<b>3.4.1 General.....</b>	<b>25</b>
<b>3.4.2 Asymmetrical (60:40) crank gear .....</b>	<b>25</b>
<b>3.4.3 Symmetrical (50:50) crank gear.....</b>	<b>26</b>
<b>3.5 Effect of deviations of the tilting angle <math>\gamma(t)</math> from the specified profile (curve), addressed in 3.4, on the test loading conditions of ISO 22675.....</b>	<b>30</b>
<b>3.6 Effect of the position of the tilting axis TA of the foot platform on the elevation <math>E</math> and the A-P displacement <math>\Delta_f</math> of the test sample at the foot.....</b>	<b>35</b>
<b>3.6.1 General.....</b>	<b>35</b>
<b>3.6.2 Position of the tilting axis TA of the foot platform .....</b>	<b>36</b>
<b>3.6.3 Values of elevation <math>E</math> .....</b>	<b>36</b>
<b>3.6.4 Values of A-P displacement <math>\Delta_f</math> .....</b>	<b>37</b>
<b>3.6.5 Conclusions .....</b>	<b>39</b>
<b>3.7 Effect of the elevation <math>E</math> and A-P displacement <math>\Delta_f</math> of the test sample, caused by the tilting of the foot platform, on the test loading conditions of ISO 22675.....</b>	<b>43</b>
<b>3.8 Transposition of the top load application point <math>P_T</math> for compensation of the dependence of the position of the tilting axis TA of the foot platform on the foot length <math>L</math> .....</b>	<b>49</b>
<b>3.8.1 General.....</b>	<b>49</b>
<b>3.8.2 Possibilities of transposing the top load application point <math>P_T</math> .....</b>	<b>49</b>
<b>3.8.3 Practicality .....</b>	<b>50</b>
<b>3.9 Effect of the position of the tilting axis TA of the foot platform on the tilting moment and the driving torque .....</b>	<b>53</b>
<b>3.10 Alternative design of foot platform .....</b>	<b>58</b>
<b>Annex A (informative) Information on ISO 22675.....</b>	<b>61</b>
<b>Bibliography .....</b>	<b>62</b>

This is a preview of "ISO/TR 22676:2006". [Click here to purchase the full version from the ANSI store.](#)

Figure 1 — Illustration of different components of loading .....	10
Figure 2 — Profiles (curves) of force components and tilting angle for test loading level P5, based on gait analysis data representative of normal level walking.....	11
Figure 3 — Profiles (curves) of force components and angles for test loading level P5, establishing the basis from which to specify the test loading conditions of ISO 22675.....	12
Figure 4 — Illustration of different test loading conditions for test loading level P5.....	13
Figure 5 — Illustration of different test loading conditions for test loading levels P5, P4 and P3.....	15
Figure 6 — Illustration of the dependence of the position of the top load application point $P_T$ on the foot length $L$ (see 2.2.3).....	17
Figure 7 — Illustration of the progression of the line of action of the resultant force $F_R$ from heel contact to toe-off in 30 ms time increments for related values of angle $\alpha$ shown in Figure 3 .....	19
Figure 8 — Diagrammatic view of test equipment with test sample.....	22
Figure 9 — Parameters of a crank gear capable of driving the foot platform of the test equipment to generate the profile (curve) $\chi(t)$ .....	23
Figure 10 — Asymmetrical (60:40) crank gear according to 3.4.2 — Tilting range – 20° (heel contact) to + 40° (toe-off).....	27
Figure 11 — Symmetrical (50:50) crank gear according to 3.4.3 — Tilting range — 20° (heel contact) via + 40° (toe-off) to + 50° .....	28
Figure 12 — Tilting characteristics of asymmetrical (60:40) crank gear according to 3.4.2 and Figure 10 and symmetrical (50:50) crank gear according to 3.4.3 and Figure 11 .....	29
Figure 13 — Profiles (curves) of angles $\alpha$ , $\beta$ and $\gamma$ as specified and as produced by crank gear 60:40.....	31
Figure 14 — Illustration of angular deviations produced by crank gear 60:40 .....	32
Figure 15 — Profiles (curves) of force components $F_P$ and $F_T$ , as specified and as produced by crank gear 60:40.....	33
Figure 16 — Illustration of force deviations produced by crank gear 60:40.....	34
Figure 17 — Illustration of distortion of time base of test force $F$ produced by crank gear 60:40.....	35
Figure 18 — Effect of $f$ -position of tilting axis TA of foot platform on the elevation $E$ of the foot at the instants of heel contact and toe-off.....	40
Figure 19 — Effect of $u$ -position of tilting axis TA of foot platform on the A/P displacement $\Delta f$ of the foot at the instant of toe-off.....	41
Figure 20 — Values of elevation $E$ and A-P displacement $\Delta f$ at specific positions of tilting axis TA.....	42
Figure 21 — Illustration of the effect of A-P displacement $\Delta f$ on the angular movement $\Delta\phi$ of the test sample about the "internal" top load application point $P_T$ in an arrangement according to 3.3.2.....	46
Figure 22 — Illustration of the effect of A-P displacement $\Delta f$ on the angular movement $\Delta\phi$ of the test sample about the "external" top load application point $P_{TE}$ in an arrangement according to 3.3.3.....	47
Figure 23 — Illustration of possibilities of transposing the top load application point $P_T$ for compensating the dependence of the position of the tilting axis TA of the foot platform on the foot length $L$ .....	51
Figure 24 — Illustration of the effect of a fixed compromise offset $u_{TA, C}$ of the tilting axis TA of the foot platform on the A-P displacement $\Delta f$ at the foot for different foot lengths $L$ [see 3.8.2 c) 2)] .....	52

This is a preview of "ISO/TR 22676:2006". [Click here to purchase the full version from the ANSI store.](#)

<b>Figure 25 — Illustration of effective lever arms.....</b>	<b>55</b>
<b>Figure 26 — Force transmission by asymmetrical (60:40) crank gear drive according to 3.4.2 and Figure 10.....</b>	<b>56</b>
<b>Figure 27 — Force transmission by symmetrical (50:50) crank gear drive according to 3.4.3 and Figure 11.....</b>	<b>57</b>
<b>Figure 28 — Tilting characteristic of foot platform of polycentric (four-bar-linkage) design.....</b>	<b>59</b>
<b>Figure 29 — Horizontal displacement of instantaneous centre IC of foot platform of polycentric (four-bar-linkage) design.....</b>	<b>60</b>
<b>Table 1 — Magnitudes of resultant reference forces <math>F_{R1x}</math> and <math>F_{R2x}</math>.....</b>	<b>7</b>
<b>Table 2 — Coordinates <math>f_{TA}</math> and <math>u_{TA}</math> of the tilting axis TA of the foot platform and related values of elevation <math>E</math> and A-P displacement <math>\Delta f</math> for foot length <math>L = 30</math> cm.....</b>	<b>43</b>
<b>Table 3 — Specific values demonstrating the effect of A-P displacement <math>\Delta f</math> on the angular movement <math>\Delta\varphi</math> of the test sample about the top load application point <math>P_T</math> for foot length <math>L = 30</math> cm.....</b>	<b>48</b>
<b>Table 4 — Possibilities of transposing the top load application point <math>P_T</math> for compensating the dependence of the position of the tilting axis TA of the foot platform on the foot length <math>L</math>.....</b>	<b>53</b>
<b>Table 5 — Moments at tilting axis TA and crankshaft CS, generated by test force <math>F(t)</math> at test loading level P5, applied to test sample of foot length <math>L = 30</math> cm.....</b>	<b>58</b>
<b>Table A.1 — Excerpt from contents of Annexes A and E of ISO 22675:2006 and list of corresponding clause/s of this Technical Report, in which selected items are dealt with.....</b>	<b>61</b>

This is a preview of "ISO/TR 22676:2006". [Click here to purchase the full version from the ANSI store.](#)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In exceptional circumstances, when a technical committee has collected data of a different kind from that which is normally published as an International Standard ("state of the art", for example), it may decide by a simple majority vote of its participating members to publish a Technical Report. A Technical Report is entirely informative in nature and does not have to be reviewed until the data it provides are considered to be no longer valid or useful.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/TR 22676 was prepared by Technical Committee ISO/TC 168, *Prosthetics and orthotics*.

This is a preview of "ISO/TR 22676:2006". [Click here to purchase the full version from the ANSI store.](#)

## Introduction

This Technical Report is exclusively intended for use in connection with ISO 22675.

This Technical Report offers information that is closely related to the above International Standard but is not necessarily required for its application.

In order to confine the volume of ISO 22675 to the necessary, information with guidance character has been separated from it and compiled in this Technical Report.