

This is a preview of "ISO/TS 25377:2007". [Click here to purchase the full version from the ANSI store.](#)

First edition
2007-10-01

Hydrometric uncertainty guidance (HUG)

Lignes directrices relatives à l'incertitude en hydrométrie



Reference number
ISO/TS 25377:2007(E)

© ISO 2007

This is a preview of "ISO/TS 25377:2007". [Click here to purchase the full version from the ANSI store.](#)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

This is a preview of "ISO/TS 25377:2007". Click here to purchase the full version from the ANSI store.

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	1
4 Symbols and abbreviations	2
5 ISO/IEC Guide 98 (GUM) — Basic definitions and rules	4
5.1 General.....	4
5.2 The uncertainty of sets of measurements.....	4
5.3 Random and systematic effects	4
5.4 Uncertainty models — Probability distributions	5
5.5 Combining uncertainties — The law of propagation	5
5.6 Expressing results.....	6
6 Open channel flow — Velocity area methods.....	6
6.1 General.....	6
6.2 Mean velocity, \bar{V}_x	7
6.3 Velocity-area determination.....	8
6.4 Stationary determination of velocity.....	9
6.5 Moving determination of velocity.....	10
6.6 Velocity-area uncertainties	11
6.7 Integration uncertainties $[u^*(F_y), u^*(F_z)]$	15
6.8 Perimeter flow uncertainties, $u(Q_p)$	16
7 Open channel flow — Critical depth methods	16
7.1 General.....	16
7.2 Head and geometry determination.....	17
7.3 Iterative calculation	18
7.4 Evaluating uncertainty	18
8 Dilution methods.....	18
8.1 General.....	18
8.2 Continuous feed.....	19
8.3 Transient mass.....	20
9 Hydrometric instrumentation	21
9.1 Performance specifications.....	21
9.2 Validity of uncertainty statements	21
9.3 Manufacturer's performance specifications	22
9.4 Performance guide for hydrometric equipment for use in technical standard examples	23
10 Guide for the drafting of uncertainty clauses in hydrometric standards	24
10.1 General.....	24
10.2 Equipment, methods and measurement systems.....	24
Annex A (informative) Introduction to hydrometric uncertainty	26
Annex B (informative) An introduction to Monte Carlo Simulation (MCS).....	43
Annex C (informative) Performance guide for hydrometric equipment for use in technical standard examples	48
Bibliography	51

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In other circumstances, particularly when there is an urgent market requirement for such documents, a technical committee may decide to publish other types of normative document:

- an ISO Publicly Available Specification (ISO/PAS) represents an agreement between technical experts in an ISO working group and is accepted for publication if it is approved by more than 50 % of the members of the parent committee casting a vote;
- an ISO Technical Specification (ISO/TS) represents an agreement between the members of a technical committee and is accepted for publication if it is approved by 2/3 of the members of the committee casting a vote.

An ISO/PAS or ISO/TS is reviewed after three years in order to decide whether it will be confirmed for a further three years, revised to become an International Standard, or withdrawn. If the ISO/PAS or ISO/TS is confirmed, it is reviewed again after a further three years, at which time it must either be transformed into an International Standard or be withdrawn.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/TS 25377 was prepared by the European Committee for Standardization (CEN) Technical Committee CEN/TC 318, *Hydrometry*, in collaboration with Technical Committee ISO/TC 113, *Hydrometry*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This is a preview of "ISO/TS 25377:2007". [Click here to purchase the full version from the ANSI store.](#)

Introduction

The management of a natural environment requires knowledge, by measurement, of what is happening. Only then can effective action be taken and the effectiveness of the action assessed. Much depends on the quality of the knowledge itself.

The quality of measurable knowledge is stated in terms of measurement uncertainty. The internationally agreed method for assessing measurement quality is the *Guide to the estimation of uncertainty in measurement* (GUM). Without this uniformity of measurement standards, equitable sharing of the environment is not possible and international obligations to care for the environment would be weakened.

The essential purpose of the GUM is that a statement of the quality of a measurement result will be presented with all measurements described in technical standards. Without this, no two measurements can be compared or standards set. Whereas the GUM is a reference document serving the universal requirements of metrology, the *Hydrometric uncertainty guidance (HUG)* document is specific to hydrometry, i.e. to the measurement of the components of the hydrological cycle. It borrows from the GUM the methods that are the most applicable to hydrometry and applies them to techniques and equipment used in hydrometry.

In the past, error analysis has provided an indication of measurement quality, but such statements cannot properly convey the quality of the result because it presupposes a knowledge of a true, error-free, value against which the measured result can be compared. The true value can never be known. Uncertainty therefore remains. For this reason, the GUM uses the concept of uncertainty and uses it for all stages and components of the measurement process. This ensures consistency.

The GUM defines standard uncertainty of a result as being equivalent to a standard deviation. This can be the standard deviation of a set of measured values or of probable values. This is broadly similar to the approach used in error analysis that preceded the uncertainty technique. However, the GUM provides additional methods of estimating uncertainty based on probability models. The two approaches are equivalent but uncertainty requires only a knowledge or estimate of the dispersion of measurement about its mean value, and not the existence of a true value. It is assumed that a careful evaluation of the components of measurement uncertainty brings the mean value close to a probable true value, at least well within its margin of uncertainty.

In more general terms, uncertainty is a parameter that characterizes the dispersion of measurable values that can be attributed to their mean value.

By treating standard deviations and probability models as if they approximated to Gaussian (or normal) distributions, the GUM provides a formal methodology for combining components of uncertainty in measurement systems where several input variables combine to determine the result.

Within this formal framework, the GUM can be consistently applied to a range of applications and, thereby, be used to make meaningful comparisons of results.

The HUG seeks to promote an understanding of the nature of measurement uncertainty and its significance in estimating the 'quality' of a measurement or a determination in hydrometry.

Hydrometry is principally concerned with the determination of flow in rivers and man-made channels. This includes

- environmental hydrometry, i.e. the determination of the flow of natural waters (largely concerned with hydrometric networks, water supply and flood protection),
- industrial hydrometry, i.e. the determination of flows within industrial plants and discharges into the natural environment (largely concerned with environment protection and also irrigation).

This is a preview of "ISO/TS 25377:2007". [Click here to purchase the full version from the ANSI store.](#)

Both are the subject of international treaties and undertakings. For this reason, measured data needs to conform to the GUM to assure that results can be compared.

Hydrometry is also concerned with the determination of rainfall, the movement/diffusion of groundwater and the transport by water flow of sediments and solids. This version of the HUG is concerned with flow determination only.

The results from hydrometry are used by other disciplines to regulate and manage the environment. If knowledge is required of biomass, sedimentary material, toxins, etc., the concentration of these components is determined and their uncertainty estimated. The uncertainty of mass-load can then be determined from the uncertainty of flow determination. The components of this calculation are made compatible through compliance with the GUM.

For practitioners of hydrometry and for engineers, the GUM is not a simple document to refer to. The document has been drafted to provide a legal framework for professional metrologists with a working knowledge of statistical methods and their mathematical representation. A helpful document, NIST Technical Note 1297 ^[12], is an abbreviated version of the GUM written to be more accessible to engineers and to specialists in fields other than metrology.

The HUG, although simplifying the concepts, in no way conflicts with the principles and methods of the GUM. Accordingly, the HUG interprets the GUM to apply its requirements to hydrometry in a practical way, and, hopefully, in a way accessible to engineers and those responsible for managing the environment.

In addition, the HUG introduces and develops Monte Carlo Simulation, a complementary technique, which has benefits for hydrometry, inasmuch as complex measurement systems can be represented realistically.

The HUG summarizes basic hydrometric methods defined in various technical standards. The HUG develops uncertainty estimation formulae from the GUM for these basic methods. The basic hydrometric methods described in the HUG may not be identical to those recited in the published technical standards. In such cases, the methods described in these standards are to be taken as authoritative. However, clauses in technical standards that concern uncertainty should be adapted to be in accordance with the HUG.

NOTE There is no unified definition of space coordinates within the hydrometric standards. The textbook conventional axes are adopted in this document when describing open channel flow: the x axis being horizontal and positive in the mean flow direction, the y axis being orthogonal to the x axis in the horizontal plane and the z axis being vertical positive.