MH10.8.1 - 2005



Automatic Identification and Data Capture Techniques Used in Shipping, Receiving, and Transport Applications

Approved: 26 September 2005

Abstract

Specifies minimum requirements for design of labels containing linear bar code and two-dimensional (2D) symbols on transport units to convey data between trading partners; provides for traceability of transported units via a Unique Transport Unit Identifier (license plate); provides guidance for formatting data; provides specific symbology recommendations; specifies quality requirements; makes recommendations as to label placement, size, free text and graphics; provides label material guidance.

Developed by:

MH10 Committee, Unit-Loads and Transport-Packages Subcommittee 8, Coding & Labeling of Unit-Loads

Published by MH10 Secretariat:

Material Handling Industry 8720 Red Oak Blvd., Suite 201 Charlotte, NC 28217-3992 standards@mhia.org



American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Copyright© 2005 by Material Handling Industry All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the Materials Handling Industry, MH10 Secretariat, 8720 Red Oak Blvd., Suite 201, Charlotte, NC 28217-3992

Phone: 704-676-1190, Fax: 704-676-1199

Email: mhstandards@mhia.org

Printed in the United States of America.

ANSI MH10.8.1 - 2005

Automatic Identification and Data Capture Techniques Used in Shipping, Receiving, and Transport Applications

Developed by:

MH10 Committee, Unit-Loads and Transport-Packages Subcommittee 8, Coding & Labeling of Unit-Loads

Published by MH10 Secretariat:

Material Handling Industry 8720 Red Oak Blvd., Suite 201 Charlotte, NC 28217

Approved September 26, 2005American National Standards Institute, Inc.

Disclaimer

This standard, which was developed under the ANSI Committee method and approved by ANSI on 26 September 2005, represents suggested design practices and guidance for labeling and direct product marking with linear bar code and two-dimensional symbols. It was developed with the sole intent of offering information to parties engaged in the manufacture, marketing, purchase, or use of automatic identification equipment software and services. This standard is advisory only and acceptance is voluntary and the standard should be regarded as a guide that the user may or may not choose to adopt, modify, or reject. The information does not constitute a comprehensive safety program and should not be relied upon as such. Such a program should be developed and an independent safety adviser consulted to do so.

Material Handling Industry (MHI), the MH10 Committee and its officers and members assume no responsibility and disclaim all liability of any kind, however arising, as a result of acceptance or use or alleged use of this standard. User specifically understands and agrees that MHI, the MH10 Committee and their officers, committee members, agents, and members shall not be liable under any legal theory of any kind for any action or failure to act with respect to the design, installation, manufacture, preparation for sale, sale, characteristics, features, or delivery of anything covered by this standard. Any use of this information must be determined by the user to be in accordance with applicable federal, state, and local laws and regulations.

MHI, the MH10 Committee and its officers and members make no warranties of any kind, express, implied, or statutory, in connection with the information in this standard. MHI and the MH10 Committee specifically disclaim all implied warranties of merchantability or of fitness for particular purpose.

By referring to or otherwise employing this standard, the user agrees to defend, protect, indemnify, and hold MHI, the MH10 Committee, their officers, committee members, agents, and members harmless from and against all claims, losses, expenses, damages, and liabilities, direct, incidental, or consequential, arising from acceptance or use or alleged use of this standard, including loss of profits and reasonable attorneys' fees which may arise out of the acceptance or use or alleged use of this standard. The intent of this provision and of the user is to absolve and protect MHI, the MH10 Committee, their officers, committee members, agents, and members from any and all loss relating in any way to this standard, including those resulting from the user's own negligence.

Foreword (This foreword is not part of American National Standard MH10.8.1 – 2005)

This standard is an application standard for the marking of product packages with linear bar code and two-dimensional symbols. It defines minimum requirements for identifying product packages that are distributed outside the originating location. It specifies label data content and requirements, including data element requirements; data representation; rules for encoding of mandatory and optional data elements in machine-readable symbols; and human readable information.

Bar codes and Two-Dimensional (2D) Symbols for Product Packaging provides the option of one of four different linear bar code symbols and one of three different two-dimensional symbols. It relies upon the technology standards and data semantic and syntax standards developed within ASC MH10. These standards have in turn been published internationally through the work of ISO/IEC JTC 1/SC 31.

The international equivalent of this standard is the international standard ISO 22389, developed by ISO Technical Committee 122/Working Group 7. ANSI MH10.8.6 and ISO 22389 were developed concurrently and differ primarily with a recommended/preferred two-dimensional symbol in the ANS while the ISO standard provides no such recommendation or preference.

At the date of approval of this standard, the MH10 Committee, Unit-Loads and Transport-Packages, consisted of the following members:

AIM, USA

American Trucking Associations

American Wood Packaging Association

APA - The Engineered Wood Association

Association of American Railroads

Assoc. of Professional Material Handling Consultants

ASTM

Automotive Industry Action Group

Containerization & Intermodal Institute

Consumer Electronics Association

Fibre Box Association

Flexible Intermediate Bulk Containers Association

Glass Packaging Institute

IDEAlliance

IMC & WD, Product Section - Material Handing Industry

Institute of Packaging Professionals

Integrated Business Communications Alliance

International Cargo Handling Coordination Assoc.

International Food Distributors Association

International Safe Transit Association

Material Handling Industry of America

Material Handling Management Society

Motorola

National Wooden Pallet & Container Association

Plastic Drum Institute

PMMI

Q.E.D. Systems

Rack Manufacturers Institute

Reusable Industrial Packaging Association

Steel Shipping Container Institute

Textile Bag Manufacturers Association

U.S. Air Force

U.S. Dept. of Agriculture

U.S. Dept. of Defense Logistics

U.S. Forest Products Laboratory

Uniform Code Council

United Fresh Fruit & Vegetable Association

United Parcel ServiceIntermec Technologies Corporation

Suggestions for improvement, and questions regarding interpretation of this standard will be welcome. They should be sent to: MH 10 Committee (MHIA), Material Handling Industry of America, 8720 Red Oak Blvd., Suite 201, Charlotte, NC, 28217-3992 or mhstandards@mhia.org.

ANSI MH10.8.1 - 2005

Automatic Identification and Data Capture Techniques Used in Shipping, Receiving, and Transport Applications

Table of Contents

Forew	ordl	111
1	Scope	1
2	Normative references	1
3	Definitions	2
4.1 4.2 4.2.1 4.2.2 4.2.3 4.3 4.4 4.4.1 4.4.2	Concepts Principles Transport Package, Unit Load, and Transport Unit. Transport Package. Unit Load. Transport Unit. Unique Transport Unit Identifier. Label formats Base Label for shipping / transport / receiving Extended Label for shipping / transport / receiving	2 3 3 3 3 3 3 3
5.1 5.1.1 5.1.2 5.1.3 5.2 5.2.1 5.2.2 5.2.3 5.2.4 5.2.5 5.2.6 5.3.1 5.3.2 5.4	Data structure Data presentation Data in linear bar code symbols Data in two-dimensional (2D) symbols Data in human readable form Data elements Unique Transport Unit Identifier Ship To Ship From Key to carrier's database Key to customer's database Other data elements Concatenating data fields in linear and composite symbols Using EAN.UCC Application Identifiers (AI) Using ANSI MH10.8.2 Data Identifiers (DI) Structured data files	44445556666777
6 6.1 6.2 6.3 6.3.1 6.3.2 6.3.3 6.3.4	Data carriers Linear bar code symbols Two-dimensional symbols Human readable information Human translation Human translation Data area titles Free text and data	7 8 8 8 8
7 7.1 7.2	Label design	0

ANSI MH10.8.1 – 2005

Automatic Identification and Data Capture Techniques Used in Shipping, Receiving, and Transport Applications

7.2.1	Base Label layout	
7.2.2	Extended Label layout	
7.2.3	Other data	
7.3	Label dimensions	
7.3.1	General considerations	
7.3.2	Label height	
7.3.3 7.3.4	Data limits	
7.3.4 7.4	Text size	
7.4.1	General considerations	
7.4.2	Specific text dimensions	
7.5	Material	
8 8.1	Label placement	
8.2	Unitized Loads (pallets)	
8.3	Transport Packages	
8.4	Other Transport Units	
	·	
Annex	A (normative) Guidelines for using linear bar code symbols	
A.1	Symbology	
A.2	Symbol height	16
A.3	Narrow element dimension	16
A.4	Wide to narrow ratio for Code 39 symbols	16
A.5	Quiet zones	16
A.6	Orientation	17
A.7	Placement	17
A.8	Linear bar code symbol print quality	17
B.1	Shipping and receiving applications	19
B.1.1	Symbology recommendation	19
B.1.2	Error correction level	
B.1.3	Narrow element dimension	19
B.1.4	Row height	
B.1.5	Quiet zone	
B.1.6	Symbol size	
B.1.7	Print quality	
B.1.8	Orientation and placement	
	PDF417 and UCC.EAN Composite symbol orientation	
В.1.8.2	Label placement	
B.2	Supporting documentation applications	
B.2.1	Symbology recommendation	22

ANSI MH10.8.1 – 2005

Automatic Identification and Data Capture Techniques Used in Shipping, Receiving, and Transport Applications

B.2.2	Error correction levels	
B.2.3	Narrow element dimension	
B.2.4	Row height	
B.2.5	Quiet zones	
B.2.6	Print quality	
B.2.7	Orientation and placement	
	Orientation	
B.2.7.2	Concatenation of symbols	
	Planning for large messages	
	Printing concatenated symbols	
	Reading Macro PDF417 symbols	
	·	
B.3 B.3.1	Printing PDF417 and EAN.UCC Composite CC-C (PDF417) symbols	
B.3.1	Plan for scanning equipment likely to be used	
B.3.3	Plan for the maximum X dimension(s) and data columns	
B.3.4	Determine the appropriate label size	
	Symbols for labels having a width of at least 102 mm.	
	Symbols for labels having a width of greater than 102 mm.	
B.4	Carrier sortation and tracking applications	
в.4 В.4.1	Data encoding	
	Code set	
	Mode	
B.4.2	Error correction levels.	
B.4.3	Narrow element dimension	
B.4.4	Quiet zones	28
B.4.5	MaxiCode symbol print quality	28
B.4.6	Orientation and placement	
	MaxiCode symbol orientation	
	Symbol placement	
	Label placement	
B.4.7	Concatenation	
	Printing Structured Append MaxiCode symbols	
	Reading Structured Append MaxiCode symbols	
Annex	C (informative) Designing compliant labels using a building block approach	31
C.1	Label definition	31
C.2	Building blocks	31
C.3	Text lines-per-block	32
C.4	Segments	32
C.5	Label dimensions	33

ANSI MH10.8.1 – 2005

Automatic Identification and Data Capture Techniques Used in Shipping, Receiving, and Transport Applications

C.6	Label format	
C.6.1	Building blocks	
	Building block size	
	Sub-blocks	
C.6.2	Text block	33
C.6.3	Text building block and sub-block title line(s)	
C.6.4	Bar code symbol block	34
Annex	D (informative) Issues to consider in the drafting of application guidelines or standards conforming to this American National Standard	35
D.1	The domain	35
D.2	Data presentation	35
D.3	The label	35
D.4	Data elements	35
D.5	The Unique Transport Unit Identifier	36
D.6	2D symbol	36
D.7	Linear bar code	36
D.8	The X dimension	36
D.9	Symbol quality	36
D.10	Label design	37
D.11	Label placement	37
Annex	E (informative) Label examples	38
E.1	Base Label examples	
E.1.1 E.1.2	Minimum data examples Bar code symbols as pointers to a trading partner's databases	
E.2	Extended Label Examples	
E.2.1	Bar code symbols as pointers to trading partner's databases	
E.2.2	Using license plate and 2D symbols for trading partner data	42
E.3	Format 02 (with complete EDI message)	48
E.3.1	EDIFICE UN/EDIFACT Despatch Advice (DESADV) in Format 02	
	Descriptive transaction	
E.3.1.2 E.3.2	ANSI ASC X12 856 EDI Ship Notice Manifest in Format 02	
-	Descriptive transaction	
	2D encodation	
		00

ANSI MH10.8.1 – 2005

Automatic Identification and Data Capture Techniques Used in Shipping, Receiving, and Transport Applications

E.3.3	ANSI ASC X12 204 EDI Motor Carrier Information in Format 02	
	Descriptive transaction	
E.4	Format 03 (structured data (EDI segments) using ANSI ASC X12)	55
E.5	Format 04 (structured data (EDI segments) using UN/EDIFACT)	56
E.6	Format 05 (data using EAN.UCC Application Identifiers)	57
E.7	Format 06 (data using ANSI MH10.8.2 Data Identifiers)	59
E.8 E.8.1 E.8.2	Combining Format 01 with Format 03	60
E.9	Combining Format 01 with Format 06	65
E.10	Combining Format 03 with Format 05	66
E.11	Combining Format 03 with Format 06	69
E.12	Combining Format 04 with Format 06	70
E.13	Combining Format 01 with Format 03 and Format 05	71
E.14 E.14.1 E.14.2	Combining Format 01, Format 06, and Format 03 over two labels Label example: (transportation label)	73
E.15	Encoding Mixed Contents in a Transport Container	74
E.16	Bill of lading example	77
Annex	F (informative) Recommended label locations on various containers	78
Annex	G (informative) For applications using Code 39 and Code 128 symbologies	81
G.1	Systems where a single option is intended to be scanned	81
G.2	Systems where multiple options are intended to be scanned	82
Bibliog	raphy	83

ANSI MH10.8.1 - 2005

Automatic Identification and Data Capture Techniques Used in Shipping, Receiving, and Transport Applications

1 Scope

This American National Standard:

- specifies the minimum requirements for the design of labels containing linear bar code and two-dimensional (2D) symbols on Transport Units to convey data between trading partners;
- provides for traceability of transported units via a Unique Transport Unit Identifier (license plate);
- provides guidance for the formatting on the label of data presented in linear bar code, 2D symbol, or human readable form;
- provides specific recommendations regarding the choice of linear bar code and 2D symbologies, and specifies quality requirements;
- makes recommendations as to label placement, size, and the inclusion of free text and any appropriate graphics;
- provides guidance in the selection of label material.

2 Normative references

This American National Standard incorporates, by dated and undated references, provisions from other publications. These normative references are listed as follows. For dated references subsequent amendments to or revisions of any of these publications apply to this American National Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

ANS MH10.8.2	Data Identifier and Application Identifier Standard
ISO/IEC 2382	Information technology – Vocabulary
ANS MH10.8.3	Transfer Syntax for High Capacity ADC Media
General EAN.UCC Specifications	Available from Uniform Code Council (UCC), 7887 Washington Village Drive, Suite 300, Dayton, OH, 45459-8605. Telephone: (937) 435-3870 • Telefax: (937) 435-7317
ISO/IEC 15415	Information technology – Automatic identification and data capture techniques – Bar code print quality test specification – Two-dimensional symbols
ISO/IEC 15416	Information technology – Automatic identification and data capture techniques – Bar code print quality test specification – Linear symbols
ISO/IEC 15417	Information technology – Automatic identification and data capture techniques – Bar code symbology specification – Code 128