



ANSI/NEMA HP 3-2012
Revision of ANSI/NEMA HP 3-2001

American National Standard

Insulated High Temperature Hook-Up Wire; Types ET (250 Volts), E (600 Volts), and EE (1000 Volts)

Secretariat:

National Electrical Manufacturers Association

Approved: February 15, 2012

Published: January 30, 2013

American National Standards Institute, Inc.

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

The American National Standards Institute (ANSI) standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process and establishes rules to promote fairness in the development of consensus, it does not write the document and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. NEMA disclaims and makes no guaranty or warranty, express or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety-related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

FOREWORD

The standard publication was developed by the NEMA High Performance Wire and Cable Section to assure that Insulated High Temperature Hook-Up Wire of Types ET (250 Volts), E (600 Volts), and EE (1000 Volts) can be procured and they will meet requirements associated with high reliability commercial electrical and electronic equipment in which it is used. Compliance with provisions of this standards publication is strictly voluntary and any certification of compliance is left to the discretion of the buyer and seller.

This standards publication was designed as a non-government standard for replacement of MIL-W-16878 PTFE insulated wire slash sheets (/4, /5, /6, /20 through /27, /34, and /35).

The High Performance Wire and Cable Section approval of ANSI/NEMA HP 3 does not necessarily imply that all section members voted for its approval or participated in its development. At the time it was approved, the section was composed of the following members:

AFC Cable Systems	New Bedford, MA
Apical Division, Kaneka Texas Corporation	El Dorado, AR
Belden Inc.	St. Louis, MO
Cable USA LLC.	Naples, FL
Champlain Cable Corporation	Colechester, VT
Coleman Cable Inc.	Waukegan, IL
Freeport McMoRan Copper and Gold	Phoenix, AZ
General Cable	Highland Heights, KY
Harbour Industries LLC.	Shelburne, VT
IWG High Performance Conductors	Inman, SC
The Monroe Cable Corporation, Inc.	Middletown, NY
Nexans AmerCable	Houston, TX
The Okonite Company	Ramsey, NJ
Quirk Wire Company, Inc.	West Brookfield, MA
Rubadue Wire Company	Greeley, CO
RSCC Aerospace and Defense	East Granby, CT
Southwire Company	Carrollton, GA
The Monroe Cable Company, Inc.	Middletown, NY
TE Connectivity	Menlo Park, CA
WireMasters, Inc.	Columbia, TN

TABLE OF CONTENTS

	FOREWORD	iii
Section 1	GENERAL.....	1
1.1	SCOPE.....	1
1.2	REFERENCED STANDARDS AND SPECIFICATIONS	1
1.3	RECOMMENDED USES OF WIRE TYPES	2
1.4	PART IDENTIFICATION NUMBER (PIN)	3
Section 2	CONDUCTORS.....	5
2.1	CONDUCTOR MATERIALS	5
2.2	CONDUCTOR COATINGS	5
2.2.1	Silver-Coated Conductors	5
2.2.2	Nickel-Coated Conductors	5
2.2.3	Tin-Coated Conductors.....	5
2.3	STRANDING	5
2.4	MINIMUM WIRE DIAMETER	5
2.5	CONDUCTOR SPLICES.....	5
Section 3	INSULATION.....	7
3.1	GENERAL	7
3.2	PTFE INSULATION.....	7
Section 4	WIRE IDENTIFICATION.....	11
4.1	CIRCUIT IDENTIFICATION.....	11
4.1.1	Lay of Stripes.....	11
4.2	IDENTIFICATION BY PRINTING.....	11
4.2.1	Identification of Product.....	11
Section 5	PHYSICAL AND ELECTRICAL REQUIREMENTS.....	13
5.1	GENERAL	13
5.2	QUALITY CONFORMANCE INSPECTION OF FINISHED PRODUCT.....	13
5.2.1	Definitions.....	13
5.2.1.1	Inspection Lot	13
5.2.1.2	Unit of Product	13
5.2.2	Sampling Inspection	13
5.3	WORKMANSHIP.....	13
5.4	MATERIALS CERTIFICATION.....	13
Section 6	TEST PROCEDURES.....	15
6.1	PHYSICAL TESTS	15
6.1.1	Test Temperature	15
6.1.2	Wrapback Test.....	15
6.1.3	Insulation Tensile Strength and Elongation.....	15
6.1.4	Dimensional Inspection	15
6.1.4.1	Conductor Diameter.....	16
6.1.4.2	Insulation Diameter.....	16
6.1.4.3	Concentricity.....	16
6.1.5	Shrinkage	16

6.1.6	Marking and Stripe Durability	16
6.1.6.1	Specimen	16
6.1.6.2	Special Apparatus	16
6.1.6.3	Procedure	17
6.1.6.4	Observation.....	17
6.2	ELECTRICAL TESTS	17
6.2.1	Conductor Resistance.....	17
6.2.2	Spark or Impulse Test.....	17
6.2.3	Dielectric Strength.....	17
Section 7	NOTES.....	19
7.1	PACKAGING REQUIREMENTS.....	19
7.2	LABELING.....	19
7.3	LENGTHS.....	19
Section 8	ORDERING DATA.....	21
8.1	ORDERING INFORMATION.....	21
APPENDIX A	A-1

<This Page Intentionally Left Blank.>

Section 1 GENERAL

1.1 SCOPE

This standards publication covers specific requirements for PTFE (polytetrafluoroethylene) insulated solid and stranded wire designed for the internal wiring of high reliability electrical and electronic equipment. This Standards Publication addresses 250 volt (Type ET), 600 volt (Type E) and 1000 volt (Type EE) wire and permits continuous conductor temperature ratings of -65° C to +200° C with silver-coated conductors and -65° C to +260° C with nickel-coated conductors. These types of hook-up wire are used when the following properties are called for:

- High temperature resistance
- Low temperature resistance
- Low dielectric constant
- Solder iron resistance
- Resistance to cleaning solutions or a variety of chemicals that may come in contact with either the wire or the equipment
- Good flexibility and flex life when stranded conductors are used

1.2 REFERENCED STANDARDS AND SPECIFICATIONS

The following publications are adopted in part, by reference in this publication, and are available from the organizations below.

American Society for Quality Control

611 E. Wisconsin Ave.
Milwaukee, WI 53202

ANSI/ASQC Z1.4 *Sampling Procedures and Tables for Inspection by Attributes*

American Society for Testing and Materials

100 Barr Harbor Drive
West Conshohocken, PA 19428

B 286	<i>Copper Conductors for Use in Hook-up Wire for Electronic Equipment</i>
B 298	<i>Silver-Coated Soft or Annealed Copper Wire</i>
B 3	<i>Soft or Annealed Copper Wire</i>
B 355	<i>Nickel-Coated Soft or Annealed Copper Wire</i>
B 452	<i>Copper Clad Steel Wire for Electronic Applications</i>
B 501	<i>Silver-Coated Copper-Clad Steel Wire for Electronic Applications</i>
B 559	<i>Nickel-Coated Copper-Clad Steel Wire for Electronic Applications</i>
B 624	<i>High-Strength, High Conductivity Copper-Alloy Wire for Electronic Application</i>