

**NEMA Standards Publication HP 7-2011**

*Electrical and Electronic PVC, PVC/Nylon, and PE/Nylon  
105°C Hook-Up Wire, Types B, C, D, BN, CN, and DN (600, 1000, and 3000 V),  
and Types J and JN 75°C (600V)*

*Published by:*

**National Electrical Manufacturers Association**

1300 North 17th Street, Suite 1752  
Rosslyn, Virginia 22209

[www.nema.org](http://www.nema.org)

© Copyright 2011 by the National Electrical Manufacturers Association. All rights including translation into other languages, reserved under the Universal Copyright Convention, the Berne Convention for the Protection of Literary and Artistic Works, and the International and Pan American Copyright Conventions.

## NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

The National Electrical Manufacturers Association (NEMA) standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process and establishes rules to promote fairness in the development of consensus, it does not write the document and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. NEMA disclaims and makes no guaranty or warranty, express or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety-related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

**CONTENTS**

	<b>Page</b>
Foreword.....	iii
<b>Section 1 GENERAL</b>	
1.1 Scope.....	1
1.2 Referenced Standards and Specifications .....	1
1.3 Recommended Uses of Wire Types.....	3
1.3.1 Type B .....	3
1.3.2 Type C .....	3
1.3.3 Type D .....	3
1.3.4 Type BN.....	3
1.3.5 Type CN.....	3
1.3.6 Type DN.....	3
1.3.7 Type J.....	3
1.3.8 Type JN.....	3
1.4 Part Identification Number (PIN).....	3
<b>Section 2 CONDUCTORS</b>	
2.1 Conductor Materials .....	6
2.2 Conductor Coatings.....	6
2.2.1 Tin-Coated Conductors .....	6
2.2.2 Silver-Coated Conductors .....	6
2.3 Stranding .....	6
2.4 Minimum Wire Diameter .....	6
2.5 Conductor Splices .....	6
<b>Section 3 INSULATION</b>	
3.1 General.....	9
3.2 PVC, PVC/Polyamide, PE, and PE/Polyamide Insulation .....	9
<b>Section 4 WIRE IDENTIFICATION</b>	
4.1 Circuit Identification .....	14
4.1.1 Lay of Stripes.....	14
4.2 Identification by Printing .....	14
4.2.1 Identification of Product.....	14
<b>Section 5 PHYSICAL AND ELECTRICAL REQUIREMENTS</b>	
5.1 General.....	15
5.2 Quality Conformance Inspection of Finished Product .....	15
5.2.1 Definitions.....	15
5.2.2 Sampling Inspection .....	15
5.3 Workmanship.....	15
5.4 Materials Certification .....	15

**Section 6 TEST PROCEDURES**

6.1	Physical Tests.....	17
6.1.1	Test Temperature .....	17
6.1.2	Heat Resistance .....	17
6.1.3	Insulation Tensile Strength and Elongation.....	17
6.1.4	Dimensional Inspection .....	17
6.1.5	Cold Bend.....	18
6.1.6	Heat Aging.....	19
6.2	Electrical Tests .....	19
6.2.1	Conductor Resistance .....	19
6.2.2	Spark or Impulse Test .....	19
6.2.3	Dielectric Strength .....	19
6.2.4	Insulation Resistance .....	20
6.2.5	Surface Resistance (for wires with outer braid only).....	20

**Section 7 NOTES**

7.1	Packing Requirements .....	21
7.2	Labeling .....	21
7.3	Lengths.....	21

**Section 8 ORDERING DATA**

8.1	Ordering Information.....	22
-----	---------------------------	----

**TABLES**

1-1	Conductor Material and Coating.....	4
1-2	AWG Nominal Conductor Size .....	4
1-3	Number of Strands.....	4
1-4	Color (See Clause 4.1).....	5
2-1	Tin-Coated Conductor Specifications.....	7
2-2	Silver-Coated Conductor Specifications.....	8
3-1	Dimensions-All Type Wires (All Dimensions in Inches).....	9
3-2	Outside Diameter Increase Due to Braid.....	13
4-1	Length of Lay of Stripes.....	14
5-1	Physical and Electrical Requirements for Types B, BN, C, CN, D, DN, J, and JN Wires .....	16
6-1	Cold Bend Mandrel Sizes, Type B and BN .....	18
6-2	Cold Bend Mandrel Sizes, Type C and CN .....	18
6-3	Cold Bend Mandrel Sizes, Type D and DN .....	19
6-4	Cold Bend Mandrel Sizes, Type J and JN.....	19
7-1	Minimum Lengths .....	21

## FOREWORD

This standard publication was developed by the NEMA High Performance Wire and Cable Section. It was developed to assure that these types of hook-up wire can be procured and that they will meet requirements associated with high reliability commercial electrical and electronic equipment in which it is used. Compliance with provisions of this Standards Publication is strictly voluntary and any certification of compliance is left to the discretion of the buyer and seller.

This Standards Publication was designed as a non-government standard for replacement of the following MIL-W-16878 insulated wire slant sheets: /1 through /3, /10, /17 through /19, and /33.

This Standards Publication was developed by the High Performance Wire and Cable Section of NEMA. Section approval of the standard does not necessarily imply that all section members voted for its approval or participated in its development. At the time it was approved, the section was composed of the following members:

AFC Cable Systems, Inc. a part of Atkore International  
Apical Division, Kaneka Texas Corporation  
Belden  
Cable USA, Inc.  
Champlain Cable Corporation  
Coleman Cable, Inc.  
Freeport-McMoRan Copper and Gold  
General Cable  
Harbour Industries LLC  
IWG High Performance Conductors  
Leoni Wire, Inc.  
Marmon Innovation and Technology Group  
Prestolite Wire and Cable  
Quirk Wire Company, Inc.  
Radix Wire Company  
RSCC Wire and Cable Group  
Rubadue Wire Co., Inc.  
Southwire Company  
TE Connectivity Ltd., a Tyco Electronics Corporation  
The Monroe Cable Company, Inc.  
The Okonite Company

New Bedford, MA  
Pasadena, TX  
St. Louis, MO  
Naples, FL  
Colchester, VT  
Waukegan, IL  
Phoenix, AZ  
Highland Heights, KY  
Shelburne, VT  
Inman, SC  
Chicopee, MA  
Seymour, CT  
Southfield, MI  
West Brookfield, MA  
Euclid, OH  
East Granby, CT  
Greeley, CO  
Carrollton, GA  
Menlo Park, CA  
Middletown, NY  
Ramsey, NJ

**<This page is intentionally left blank.>**



## Section 1 GENERAL

### 1.1 SCOPE

This standard publication covers specific requirements for PVC, PVC/polyamide, PE, and PE/polyamide insulated stranded wire, designed to the internal wiring of high reliability electrical and electronic equipment. This standards publication addresses 600 volt (Type B, BN, J, and JN), 1000 volt (Type C and CN) and 3000 volt (Type D and DN) wire and permits continuous operating temperature ratings of -55°C up to 105°C (types B, C, D, BN, CN, and DN) or 75°C (types J and JN) with either tin or silver coated conductors.

### 1.2 REFERENCE STANDARDS AND SPECIFICATIONS

**American Society for Quality Control**  
611 E. Wisconsin Ave.  
Milwaukee, WI 53202

ANSI/ASQC Z1.4      *Sampling Procedures and Tables for Inspection by Attributes*

**American Society for Testing and Materials (ASTM)**

100 Barr Harbor Drive  
West Conshohocken, PA 19428-2959

B 286-07      *Copper Conductors for Use in Hook-Up Wire for Electronics*

B 298-07      *Silver Coated Soft or Annealed Copper Wire*

B 3-01      *Soft or Annealed Copper Wire*

D 3032-98      *Methods of Testing Hook-Up Wire Insulation*

B 33-04      *Tinned Soft or Annealed Copper Wire*

**DODISS-Customer Service**

Bldg. 4D  
700 Robbins Ave.  
Philadelphia, PA 19111-5094

MIL-STD-2223      *Test Methods for Insulated Electronic Wire*

**Electronics Industries Association**

2500 Wilson Blvd.  
Arlington, VA 22201

EIA-359-A-85      *EIA Standard Colors for Color Identification and Coding*