

NEMA Standards Publication TC 7-2013

Smooth-Wall Coilable Electrical Polyethylene Conduit

Published by:

National Electrical Manufacturers Association

1300 North 17th Street, Suite 900
Rosslyn, Virginia 22209

www.nema.org

© Copyright 2013 by the National Electrical Manufacturers Association. All rights including translation into other languages, reserved under the Universal Copyright Convention, the Berne Convention for the Protection of Literary and Artistic Works, and the International and Pan American Copyright Conventions.

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

The National Electrical Manufacturers Association (NEMA) standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process and establishes rules to promote fairness in the development of consensus, it does not write the document and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. NEMA disclaims and makes no guaranty or warranty, express or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety-related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

CONTENTS

| | |
|---|-----------|
| FOREWORD..... | iii |
| SECTION 1 GENERAL..... | 1 |
| 1.1 Scope..... | 1 |
| 1.2 Referenced Standards..... | 1 |
| SECTION 2 DEFINITIONS AND ABBREVIATIONS | 3 |
| 2.1 Definitions | 3 |
| 2.2 Abbreviations | 3 |
| SECTION 3 GENERAL REQUIREMENTS | 4 |
| 3.1 Materials | 4 |
| 3.1.1 Electrical Conduit | 4 |
| 3.2 Dimensions and Lengths | 4 |
| 3.2.1 Average Outside Diameter | 4 |
| 3.2.2 Wall Thickness | 4 |
| 3.2.3 Ovality..... | 4 |
| 3.2.4 Length..... | 4 |
| 3.3 Workmanship..... | 4 |
| 3.3.1 Bonding to Conduit..... | 4 |
| 3.3.2 Excess Pull Member..... | 5 |
| 3.4 Inspections..... | 5 |
| 3.5 Internal Ribs..... | 5 |
| SECTION 4 PERFORMANCE REQUIREMENTS..... | 7 |
| 4.1 Quality Control Tests | 7 |
| 4.1.1 Conditioning..... | 7 |
| 4.1.2 Dimensions..... | 7 |
| 4.1.3 Ovality..... | 7 |
| 4.1.4 Compression and Recovery | 7 |
| SECTION 5 TEST METHODS..... | 9 |
| 5.1 Conditioning, Test Conditions, and Sampling | 9 |
| 5.1.1 Conditioning Test Specimens..... | 9 |
| 5.1.2 Sampling..... | 9 |
| 5.2 Dimensions | 9 |
| 5.2.1 Outside Diameter (Average)..... | 9 |
| 5.2.2 Wall Thickness | 9 |
| 5.2.3 Ovality..... | 9 |
| 5.3 Compression and Recovery | 9 |
| SECTION 6 MARKINGS..... | 11 |
| 6.1 Marking Requirements | 11 |
| 6.2 Optional Markings..... | 11 |
| ANNEX A RECOMMENDED MINIMUM DRUM DIAMETERS | 13 |

TABLES

| | |
|--|---|
| Table 3-1 D 3350 Cell Classification Material Requirement for HDPE Conduit, per ASTM F 2160..... | 5 |
| Table 3-2 Sizes and Dimensions of HDPE Conduit..... | 6 |
| Table 4-1 Load for Compression and Recovery Test | 7 |

FOREWORD

The purpose of this Standards Publication for high-density polyethylene (HDPE) conduit (duct) intended for underground use in the installation and protection of electrical cables is:

1. To list dimensions and other significant requirements;
2. To state the required properties of these products and to assist in selecting and obtaining the proper product for a particular need.

In addition, this standard addresses the factory installation of electrical cable or pull media commonly used to assist in the installation of cables.

User needs have been considered throughout the development of this standard. The Polymer Raceway Products Section of NEMA, through its members, works closely with such organizations as ASTM International, appropriate government agencies, testing laboratories, and others in the periodic review and revision of this standard. The Plastics Pipe Institute, in particular, was helpful in proposing revisions for this edition of TC 7.



Proposed or recommended revisions to this Standards Publication should be addressed to:

Vice President, Technical Services
National Electrical Manufacturers Association
1300 North 17th Street, Suite 1752
Rosslyn, Virginia 22209

Publication No. TC 7-2013 revises and supersedes Publication No. TC 7-2005, the NEMA Standards Publication for Smooth Wall Coilable Electrical Polyethylene Conduit.

The Polymer Raceway Products Section developed this Standards Publication. Section approval of the standard does not necessarily imply that section members voted for its approval or participated in its development. At the time it was published, the Section was composed of the following members:

AFC Cable Systems, a part of Atkore International—www.afcweb.com—New Bedford, MA
Allied Tube and Conduit, a part of Atkore International—www.alliedtube.com—Harvey, IL
Anamet Electrical, Inc.—<http://www.anacondasealtite.com>—Mattoon, IL
Champion Fiberglass, Inc.—www.championfiberglass.com—Spring, TX
FRE Composites (2005) Inc.—www.frecomposites.com—St. Andre-d'Argenteuil, PQ, Canada
Heritage Plastics, Inc.—www.heritageplastics.com—Carrollton, OH
Hubbell Incorporated—www.hubbell.com—Shelton, CT
IPEX USA, LLC—www.ipexinc.com—Mississauga, ON, Canada
Legrand North America—www.legrand.us—West Hartford, CT
Panduit Corporation—www.panduit.com—Tinley Park, IL
Royal Pipe Systems—www.plasticstrends.com—Shelby Township, MI
Southern Pipe, Inc.—www.southern-pipe.com—New London, NC
Thomas & Betts, a member of the ABB Group—www.tnb.com—Memphis, TN
Underground Devices, Inc.—www.udevices.com—Northbrook, IL
United Fiberglass of America—www.unitedfiberglass.com—Springfield, OH

This is a preview of "NEMA TC 7-2013". [Click here to purchase the full version from the ANSI store.](#)

Section 1 GENERAL

1.1 SCOPE

This standard covers several types of high-density polyethylene (HDPE) conduit for use in providing a protective raceway for electrical cables buried underground. The HDPE conduit types in this specification can be installed direct buried or concrete encased, they are:

EPEC-17– HDPE This type represents the nominal dimensions for HDPE conduit as specified by ASTM D 3035, SDR 17 and UL 651B or UL1990 for CIC.

EPEC-13.5– HDPE This type represents the nominal dimensions for HDPE conduit as specified by ASTM F 2160, SDR 13.5 and UL 651B or UL 1990 for CIC.

EPEC-40– HDPE This type represents the nominal dimensions for HDPE conduit as specified by ASTM F 2160, Schedule 40 and UL 651B or UL 1990 for CIC.

EPEC-80– HDPE This type represents the nominal dimensions for HDPE conduit as specified by ASTM F 2160, Schedule 80 and UL 651B or UL 1990 for CIC.

EPEC-11-HDPE This type represents the nominal dimensions for HDPE conduit as specified by ASTM F 2160, SDR 11 and is not currently covered by UL.

NOTE—The values stated in U.S. customary units are to be regarded as the standard.

1.2 REFERENCED STANDARDS

In this publication, reference is made to the standards listed below. Where all or part of an ASTM, NFPA, or UL etc., standard specification is incorporated by reference in these Specifications, the reference standard shall be the latest edition and revision. Copies are available from the indicated sources.

American Society for Testing and Materials

100 Barr Harbor Drive
West Conshohocken, PA 19428-2959

| | |
|-----------|--|
| D 618-08 | <i>Standard Practice for Conditioning Plastics for Testing</i> |
| D 638-10 | <i>Standard Test Method for Tensile Properties of Plastics</i> |
| D 790-10 | <i>Standard Test Methods for Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials</i> |
| D 792-08 | <i>Standard Test Methods for Density and Specific Gravity (Relative Density) of Plastics by Displacement</i> |
| D 1238-10 | <i>Standard Test Method for Flow Rates of Thermoplastics by Extrusion Plastometer</i> |
| D 1505-10 | <i>Standard Test Method for Density of Plastics by the Density-Gradient Technique</i> |
| D 1600-08 | <i>Standard Terminology for Abbreviated Terms Relating to Plastics</i> |