

A Joint Standard of AASHTO, ITE, and NEMA

NTCIP 1203 version v03

National Transportation Communications for ITS Protocol Object Definitions for Dynamic Message Signs (DMS)

published September 2014

Published by

American Association of State Highway and Transportation Officials (AASHTO)

444 North Capitol Street, N.W., Suite 249
Washington, D.C. 20001

Institute of Transportation Engineers (ITE)

1627 I ("Eye") Street, N.W., Suite 600
Washington, D.C. 20006-4007

National Electrical Manufacturers Association (NEMA)

1300 North 17th Street, Suite 900
Rosslyn, Virginia 22209-3806

This is a preview of "NTCIP 1203 v03". [Click here to purchase the full version from the ANSI store.](#)

NOTICES

Copyright Notice

© 2014 by the American Association of State Highway and Transportation Officials (AASHTO), the Institute of Transportation Engineers (ITE), and the National Electrical Manufacturers Association (NEMA). All intellectual property rights, including, but not limited to, the rights of reproduction, translation, and display are reserved under the laws of the United States of America, the Universal Copyright Convention, the Berne Convention, and the International and Pan American Copyright Conventions. Except as licensed or permitted, you may not copy these materials without prior written permission from AASHTO, ITE, or NEMA. Use of these materials does not give you any rights of ownership or claim of copyright in or to these materials.

Visit www.ntcip.org for other copyright information, for instructions to request reprints of excerpts, and to request reproduction that is not granted below.

PDF File License Agreement

To the extent that these materials are distributed by AASHTO / ITE / NEMA in the form of an Adobe® Portable Document Format (PDF) electronic data file (the "PDF file"), AASHTO / ITE / NEMA authorizes each registered PDF file user to view, download, copy, or print the PDF file available from the authorized Web site, subject to the terms and conditions of this license agreement:

- a) you may download one copy of each PDF file for personal, noncommercial, and intraorganizational use only;
- b) ownership of the PDF file is not transferred to you; you are licensed to use the PDF file;
- c) you may make one more electronic copy of the PDF file, such as to a second hard drive or burn to a CD;
- d) you agree not to copy, distribute, or transfer the PDF file from that media to any other electronic media or device;
- e) you may print one paper copy of the PDF file;
- f) you may make one paper reproduction of the printed copy;
- g) any permitted copies of the PDF file must retain the copyright notice, and any other proprietary notices contained in the file;
- h) the PDF file license does not include: 1) resale of the PDF file or copies, 2) republishing the content in compendiums or anthologies, 3) publishing excerpts in commercial publications or works for hire, 4) editing or modification of the PDF file except those portions as permitted, 5) posting on network servers or distribution by electronic mail or from electronic storage devices, and 6) translation to other languages or conversion to other electronic formats;
- i) other use of the PDF file and printed copy requires express, prior written consent.

Data Dictionary and MIB Distribution Permission

To the extent that these materials are distributed by AASHTO / ITE / NEMA in the form of a Data Dictionary ("DD") or Management Information Base ("MIB"), AASHTO / ITE / NEMA extend the following permission:

You may make or distribute unlimited copies, including derivative works, of the DD or MIB, including copies for commercial distribution, provided that:

- a) each copy you make or distribute contains the citation "Derived from NTCIP 0000 [insert the standard number]. Used by permission of AASHTO / ITE / NEMA.";
- b) the copies or derivative works are not made part of the standards publications or works offered by other standards developing organizations or publishers or as works-for-hire not associated with

- commercial hardware or software products intended for field implementation;
- c) use of the DD or MIB is restricted in that the syntax fields may be modified only to reflect a more restrictive subrange or enumerated values;
- d) the description field may be modified but only to the extent that: 1) only those bit values or enumerated values that are supported are listed; and 2) the more restrictive subrange is expressed.

These materials are delivered "AS IS" without any warranties as to their use or performance.

AASHTO / ITE / NEMA and their suppliers do not warrant the performance or results you may obtain by using these materials. AASHTO / ITE / NEMA and their suppliers make no warranties, express or implied, as to noninfringement of third party rights, merchantability, or fitness for any particular purpose. In no event will AASHTO / ITE / NEMA or their suppliers be liable to you or any third party for any claim or for any consequential, incidental or special damages, including any lost profits or lost savings, arising from your reproduction or use of these materials, even if an AASHTO / ITE / NEMA representative has been advised of the possibility of such damages.

Some states or jurisdictions do not allow the exclusion or limitation of incidental, consequential, or special damages, or the exclusion of implied warranties, so the above limitations may not apply to a given user.

Use of these materials does not constitute an endorsement or affiliation by or between AASHTO, ITE, or NEMA and the user, the user's company, or the products and services of the user's company.

If the user is unwilling to accept the foregoing restrictions, he or she should immediately return these materials.

PRL and RTM Distribution Permission

To the extent that these materials are distributed by AASHTO / ITE / NEMA in the form of a Profile Requirements List ("PRL") or a Requirements Traceability Matrix ("RTM"), AASHTO / ITE / NEMA extend the following permission:

- a) you may make or distribute unlimited copies, including derivative works of the PRL (then known as a Profile Implementation Conformance Statement ("PICS")) or the RTM, provided that each copy you make or distribute contains the citation "Based on NTCIP 0000 [insert the standard number] PRL or RTM. Used by permission. Original text © AASHTO / ITE / NEMA.";
- b) you may only modify the PRL or the RTM by adding: 1) text in the Project Requirements column, which is the only column that may be modified to show a product's implementation or the project-specific requirements; and/or 2) additional table columns or table rows that are clearly labeled as ADDITIONAL for project-unique or vendor-unique features; and
- c) if the PRL or RTM excerpt is made from an unapproved draft, add to the citation "PRL (or RTM) excerpted from a draft standard containing preliminary information that is subject to change."

This limited permission does not include reuse in works offered by other standards developing organizations or publishers, and does not include reuse in works-for-hire, compendiums, or electronic storage devices that are not associated with procurement documents, or commercial hardware, or commercial software products intended for field installation.

A PICS is a Profile Requirements List which is completed to indicate the features that are supported in an implementation. Visit www.ntcip.org for information on electronic copies of the MIBs, PRLs, and RTMs.

TRF Distribution Permission

A Testing Requirements Form ("TRF") may be a Testing Requirements Traceability Table and/or Test Procedures. To the extent that these materials are distributed by AASHTO / ITE / NEMA in the form of a

TRF, AASHTO / ITE / NEMA extend the following permission:

- a) you may make and/or distribute unlimited electronic or hard copies, including derivative works of the TRF, provided that each copy you make and/or distribute contains the citation "Based on NTCIP 0000 [insert the standard number] TRF. Used by permission. Original text © AASHTO / ITE / NEMA.";
- b) you may not modify the logical flow of any test procedure, without clearly noting and marking any such modification; and
- c) if the TRF excerpt is made from an unapproved draft, add to the citation "TRF excerpted from a draft standard containing preliminary information that is subject to change."

Content and Liability Disclaimer

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

AASHTO, ITE, and NEMA standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together volunteers and seeks out the views of persons who have an interest in the topic covered by this publication. While AASHTO, ITE, and NEMA administer the process and establish rules to promote fairness in the development of consensus, they do not write the document and they do not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in their standards and guideline publications.

AASHTO, ITE, and NEMA disclaim liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. AASHTO, ITE, and NEMA disclaim and make no guaranty or warranty, express or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. AASHTO, ITE, and NEMA do not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, AASHTO, ITE, and NEMA are not undertaking to render professional or other services for or on behalf of any person or entity, nor are AASHTO, ITE, and NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

AASHTO, ITE, and NEMA have no power, nor do they undertake to police or enforce compliance with the contents of this document. AASHTO, ITE, and NEMA do not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety-related information in this document shall not be attributable to AASHTO, ITE, or NEMA and is solely the responsibility of the certifier or maker of the statement.

Trademark Notice

NTCIP is a trademark of AASHTO / ITE / NEMA. All other marks mentioned in this standard are the trademarks of their respective owners.

< This page intentionally left blank. >

ACKNOWLEDGEMENTS

NTCIP 1203 v03 was prepared by the NTCIP Dynamic Message Sign Working Group (DMS WG), a subdivision of the Joint Committee on the NTCIP. The Joint Committee is organized under a Memorandum of Understanding among the American Association of State Highway and Transportation Officials (AASHTO), the Institute of Transportation Engineers (ITE), and the National Electrical Manufacturers Association (NEMA). The NTCIP development effort is guided by the Joint Committee on the NTCIP, which consists of six representatives from each of the above organizations.

When NTCIP 1203 v03 was prepared, the following individuals were active members of the NTCIP DMS WG:

Lesly Bien-Aimé
Russell Brookshire
Patrick Chan
Felix Cuellar
Gene Daigle
Terry Haukom
Ira Huttner
Amit Misra

Mark Morse, chair
Peter Ragsdale
Robert Rausch
Joerg "Nu" Rosenbohm
Ken Smith
Ken Vaughn
Derek Vollmer

Other individuals providing input include:

Steve Alonge
Blake Christie

Tom Kurihara

In addition to the many volunteer efforts, recognition is also given to those organizations who supported the efforts of the working groups by providing comments and funding for the standard, including:

Consensus Systems Technologies
Daktronics
Intelligent Devices, Inc.
McCain
Minnesota DOT
PBS&J
Port Authority of NY & NJ

Skyline
Southwest Research Institute
Telvent Farradyne
TransCore ITS
Trevilon
Ver-Mac
Washington State DOT

The U.S. Department of Transportation Joint Program Office provided funding assistance for the development of NTCIP 1203 v03.

FOREWORD

NTCIP 1203 v03 uses only metric units.

NTCIP 1203 v03 identifies and defines how a management station may wish to interface with a field device to control and monitor dynamic message signs (DMS). NTCIP 1203 v03 defines requirements that are applicable to all NTCIP DMS and it also contains optional and conditional sections that are applicable to specific environments for which they are intended.

NTCIP 1203 v03 is an NTCIP Device Data Dictionary Standard. Device Data Dictionary Standards provide formal definitions of data elements for use within NTCIP systems.

For more information about NTCIP standards, visit the NTCIP Web Site at www.ntcip.org.

Approvals

NTCIP 1203 v03 was separately balloted and approved by AASHTO, ITE, and NEMA after recommendation by the Joint Committee on the NTCIP. Each organization has approved this standard as the following standard type, as of the date:

AASHTO—Standard Specification; December 2011
ITE—Software Standard; May 2012
NEMA—Standard; March 2012

History

The first version of NTCIP 1203 was published as NTCIP 1203:1997 and was also known as NEMA TS 3.6. In 2001, Amendment 1 was accepted by the Joint Committee on the NTCIP and subsequently Jointly Approved by all three SDOs. The Amendment did not add additional functionality but provided clarifications on object definitions and MULTI tags which have been detected by actual implementations.

NTCIP 1203 v02 was developed to reflect lessons learned, to update the document to the new documentation formats, and to add new features such as the colors, graphics, and a 3-tiered equipment management structure. NTCIP 1203 v02 also follows an established 'systems engineering' approach. Several new sections were added to relate user needs identified in a concept of operations, functional requirements, interface specifications and a requirements traceability matrix to the existing sections.

This Version 03 of the NTCIP 1203 standard adds test procedures that satisfy the functional requirements that has been provided. These test procedures, provided in Annex C of this standard, allows agencies procuring dynamic message signs to consistently test for conformance to this standard. Minor corrections and clarifications to the standard are also included. All changes are shown and explained in Annex D (Documentation of Revisions) of this standard.

User Comment Instructions

The term "User Comment" includes any type of written inquiry, comment, question, or proposed revision, from an individual person or organization, about any part of this standards publication's content. A "Request for Interpretation" of this standards publication is also classified as a User Comment. User Comments are solicited at any time. In preparation of this NTCIP standards publication, input of users and other interested parties was sought and evaluated.

All User Comments are referred to the committee responsible for developing and/or maintaining NTCIP 1209 v02. The committee chairperson, or their designee, may contact the submitter for clarification of the

User Comment. When the committee chairperson or designee reports the committee's consensus opinion related to the User Comment, that opinion is forwarded to the submitter. The committee chairperson may report that action on the User Comment may be deferred to a future committee meeting and/or a future revision of the standards publication. Previous User Comments and their disposition may be available for reference and information at www.ntcip.org.

A User Comment should be submitted to this address:

NTCIP Coordinator
National Electrical Manufacturers Association
1300 North 17th Street, Suite 900
Rosslyn, Virginia 22209-3801
e-mail: ntcip@nema.org

A User Comment should be submitted in the following form:

Standards Publication number and version:

Page:

Section and Paragraph (with Table or Figure, where appropriate):

Comment:

Editorial or Substantive?:

Suggested Alternative Language:

Please include your name, organization, and address in your correspondence.

Compatibility of Versions

To distinguish NTCIP 1203 v03 (as published) from previous drafts, NTCIP 1203 v03 also includes NTCIP 1203 v03.05 on each page header. All NTCIP Standards Publications have a major and minor version number for configuration management. The version number syntax is "v00.00a," with the major version number before the period, and the minor version number and edition letter (if any) after the period.

NTCIP 1203 v03 is designated, and should be cited as, NTCIP 1203 v03. Anyone using NTCIP 1203 v03 should seek information about the version number that is of interest to them in any given circumstance. The MIB, the PRL, and the PICS should all reference the version number of the standards publication that was the source of the excerpted material.

Conformant systems based on later, or higher, version numbers MAY NOT be compatible with conformant systems based on earlier, or lower, version numbers. Anyone using NTCIP 1203 v03 should also consult NTCIP 8004 v02 for specific guidelines on compatibility.

INTRODUCTION

NTCIP 1203 v03 provides definitions of data elements for use with dynamic message signs. The data is defined using the Simple Network Management Protocol (SNMP) object-type format as defined in RFC 1212 and would typically be exchanged using one of the NTCIP recognized Application Layers (e.g., SNMP). The content of one object, the `dmsMessageMultiString` object, uses a complex syntax called the Mark-Up Language for Transportation Information (MULTI) format, also defined in NTCIP 1203 v03.

The following keywords apply to this document: AASHTO, ITE, NEMA, NTCIP, DMS, VMS, CMS, data, data dictionary, object, message sign, message board, sign, MULTI.

In 1992, the NEMA 3-TS Transportation Management Systems and Associated Control Devices Section began the effort to develop the NTCIP. The Transportation Section's purpose was to respond to user needs to include standardized systems communication in the NEMA TS 2 standard, *Traffic Controller Assemblies*. Under the guidance of the Federal Highway Administration's NTCIP Steering Group, the NEMA effort was expanded to include the development of communications standards for all transportation field devices that could be used in an Intelligent Transportation Systems (ITS) network. Message signs were identified as one of the highest priority expansion areas. As a result, in August 1995, NEMA created the DMS Technical Subcommittee to standardize DMS equipment. Their first task was the development of this document.

In September 1996, an agreement was executed among AASHTO, ITE, and NEMA to jointly develop, approve, and maintain the NTCIP standards. One of the first tasks of this joint effort was to finalize the work that NEMA had already begun on the object definitions for dynamic message signs.

CONTENTS

Section 1 General [Informative]	1
1.1 Scope	1
1.2 References	1
1.2.1 Normative References.....	1
1.2.2 Other References	2
1.2.3 Contact Information	2
1.3 General Statements	3
1.4 Terms	3
1.5 Abbreviations	15
Section 2 Concept of Operations [Normative]	17
2.1 Tutorial [informative]	17
2.1.1 About NTCIP 1203 v03.....	18
2.1.2 Who are you?	18
2.1.3 How NTCIP 1203 v03 is Organized	19
2.1.4 Intended Audiences for the Sections in NTCIP 1203 v03	20
2.2 Current Situation and Problem Statement [informative]	20
2.3 Reference Physical Architecture [informative]	20
2.3.1 Typical Physical Architecture.....	20
2.3.2 DMS Characteristics	21
2.4 Architectural Needs	22
2.4.1 Fundamental Needs Driving DMS Deployment	22
2.4.2 Operational Environment.....	22
2.5 Features	23
2.5.1 Manage the DMS Configuration	23
2.5.2 Control the DMS	24
2.5.3 Monitor the Status of the DMS	26
2.5.4 Provide for Backwards Compatibility of DMS to NTCIP 1203 v1	28
2.6 Security	28
2.7 Operational Policies and Constraints	28
2.8 Relationship to the National ITS Architecture [Informative]	28
Section 3 Functional Requirements [Normative]	30
3.1 Tutorial [informative]	30
3.2 Scope of the Interface [Informative]	31
3.3 Protocol Requirements List (PRL)	31
3.3.1 Notation [Informative]	31
3.3.2 Instructions for Completing the PRL [Informative].....	33
3.3.3 Protocol Requirements List (PRL) Table.....	35
3.3.4 Protocol Requirements List – Supplemental Table	58
3.3.5 MULTI Field Traceability Matrix.....	66
3.4 Architectural Requirements	73
3.4.1 Support Basic Communications	73
3.4.2 Support Logged Data	73

3.4.3	Support Exception Reporting.....	73
3.4.4	Manage Access	73
3.5	Data Exchange and operational environment Requirements	74
3.5.1	Manage the DMS Configuration	74
3.5.2	Control the DMS	77
3.5.3	Monitor the Status of the DMS	82
3.5.4	Providing for Multi-Version Interoperability.....	87
3.6	Supplemental Non-Communications Requirements	87
3.6.1	Supplemental Requirements for Fonts.....	87
3.6.2	Supplemental Requirements for General Illumination Brightness.....	87
3.6.3	Supplemental Requirements for Automatic Brightness Control.....	87
3.6.4	Supplemental Requirements for Control Modes	88
3.6.5	Supplemental Requirements for Message Activation Request.....	88
3.6.6	Supplemental Requirements for Message Definition	89
3.6.7	Supplemental Requirements for Locally Stored Messages	93
3.6.8	Supplemental Requirements for Color Scheme.....	93
3.6.9	Supplemental Requirements for Monitoring Subsystems	94
3.6.10	Supplemental Requirements for Scheduling	94
3.6.11	Supplemental Requirements for Graphics	95
3.6.12	Supplemental Requirements for Page Justification	95
3.6.13	Supplemental Requirements for Line Justification	95
Section 4	Dialogs [Normative]	96
4.1	Tutorial [Informative].....	97
4.2	Specified Dialogs.....	98
4.2.1	Calculating the Checksum Value	98
4.2.2	Managing the DMS Configuration	98
4.2.3	Controlling the DMS	106
4.2.4	Monitoring the Status of the DMS	114
4.3	State Transition Diagrams	118
4.3.1	Font State Machine Definition	119
4.3.2	Graphic State Machine Definition.....	123
4.3.3	Control Mode State Machine Definition.....	126
4.3.4	Message Table State Machine Definition.....	128
4.3.5	Message Activation Consistency Check Definition	131
Section 5	Management Information Base (MIB) [Normative]	132
5.1	Object Definitions	132
5.2	Sign Configuration and Capability Objects	135
5.2.1	Sign Access Parameter.....	136
5.2.2	Sign Type Parameter.....	136
5.2.3	Sign Height Parameter	136
5.2.4	Sign Width Parameter	137
5.2.5	Horizontal Border Parameter.....	137
5.2.6	Vertical Border Parameter	137
5.2.7	Legend Parameter	137
5.2.8	Beacon Type Parameter.....	138
5.2.9	Sign Technology Parameter	138
5.3	VMS Configuration Objects	139
5.3.1	Character Height in Pixels Parameter.....	139
5.3.2	Character Width in Pixels Parameter	139

5.3.3	Sign Height in Pixels Parameter.....	139
5.3.4	Sign Width in Pixels Parameter.....	140
5.3.5	Horizontal Pitch Parameter.....	140
5.3.6	Vertical Pitch Parameter.....	140
5.3.7	Monochrome Color Parameter.....	140
5.4	Font Definition Objects.....	141
5.4.1	Number of Fonts Parameter.....	141
5.4.2	Font Table Parameter.....	141
5.4.3	Maximum Characters per Font Parameter.....	146
5.4.4	Character Table Parameter.....	146
5.4.5	Maximum Character Size Parameter.....	147
5.5	Multi-Configuration Objects.....	148
5.5.1	Default Background Color Parameter.....	148
5.5.2	Default Foreground Color Parameter.....	148
5.5.3	Default Flash On Time Parameter.....	149
5.5.4	Default Flash On Time Parameter at Activation.....	149
5.5.5	Default Flash Off Time Parameter.....	149
5.5.6	Default Flash Off Time Parameter at Activation.....	149
5.5.7	Default Font Parameter.....	150
5.5.8	Default Font Parameter at Activation.....	150
5.5.9	Default Line Justification Parameter.....	150
5.5.10	Default Line Justification Parameter at Activation.....	150
5.5.11	Default Page Justification Parameter.....	151
5.5.12	Default Page Justification Parameter at Activation.....	151
5.5.13	Default Page On Time Parameter.....	151
5.5.14	Default Page On Time Parameter at Activation.....	152
5.5.15	Default Page Off Time Parameter.....	152
5.5.16	Default Page Off Time Parameter at Activation.....	152
5.5.17	Default Background Color RGB Parameter.....	152
5.5.18	Default Background Color RGB Parameter at Activation.....	153
5.5.19	Default Foreground Color RGB Parameter.....	153
5.5.20	Default Foreground Color RGB Parameter at Activation.....	154
5.5.21	Default Character Set Parameter.....	154
5.5.22	Color Scheme Parameter.....	154
5.5.23	Supported MULTI Tags Parameter.....	155
5.5.24	Maximum Number of Pages Parameter.....	156
5.5.25	Maximum MULTI String Length Parameter.....	156
5.6	Message Objects.....	156
5.6.1	Number of Permanent Messages Parameter.....	156
5.6.2	Number of Changeable Messages Parameter.....	157
5.6.3	Maximum Number of Changeable Messages Parameter.....	157
5.6.4	Free Bytes within Changeable Memory Parameter.....	157
5.6.5	Number of Volatile Messages Parameter.....	157
5.6.6	Maximum Number of Volatile Messages Parameter.....	158
5.6.7	Free Bytes within Volatile Memory Parameter.....	158
5.6.8	Message Table Parameter.....	158
5.6.9	Validate Message Error Parameter.....	162
5.7	Sign Control Objects.....	163
5.7.1	Control Mode Parameter.....	163
5.7.2	Software Reset Parameter.....	163
5.7.3	Activate Message Parameter.....	163
5.7.4	Message Display Time Remaining Parameter.....	164
5.7.5	Message Table Source Parameter.....	165

5.7.6	Message Requester ID Parameter	165
5.7.7	Message Source Mode Parameter.....	165
5.7.8	Short Power Loss Recovery Message Parameter	166
5.7.9	Long Power Loss Recovery Message Parameter	167
5.7.10	Short Power Loss Time Definition Parameter	167
5.7.11	Reset Message Parameter	167
5.7.12	Communications Loss Message Parameter.....	168
5.7.13	Communication Loss Time Definition Parameter.....	168
5.7.14	Power Loss Message Parameter	169
5.7.15	End Duration Message Parameter	169
5.7.16	Memory Management Parameter.....	170
5.7.17	Activate Message Error Parameter	170
5.7.18	MULTI Syntax Error Parameter.....	172
5.7.19	Position of MULTI Syntax Error Parameter	172
5.7.20	Other MULTI Error Parameter	173
5.7.21	Pixel Service Duration Parameter	173
5.7.22	Pixel Service Frequency Parameter	173
5.7.23	Pixel Service Time Parameter	173
5.7.24	Message Code of the Activation Error Parameter.....	174
5.7.25	Activate Message State Parameter.....	174
5.8	Illumination/Brightness Objects	175
5.8.1	Illumination Control Parameter	175
5.8.2	Maximum Illumination Photocell Level Parameter	175
5.8.3	Status of Illumination Photocell Level Parameter.....	176
5.8.4	Number of Illumination Brightness Levels Parameter	176
5.8.5	Status of Illumination Brightness Level Parameter	176
5.8.6	Illumination Manual Level Parameter	176
5.8.7	Illumination Brightness Values Parameter	177
5.8.8	Brightness Values Error Parameter.....	178
5.8.9	Status of Illumination Light Output Parameter.....	178
5.9	Scheduling Action Objects.....	179
5.9.1	Action Table Entries Parameter	179
5.9.2	Action Table Parameter.....	179
5.10	Auxiliary I/O Objects	180
5.11	Sign Status	180
5.11.1	Core Status.....	180
5.11.2	Status Error Objects	182
5.11.3	Power Status Objects	208
5.11.4	Temperature Status Objects	210
5.12	Graphic Definition Objects	212
5.12.1	Maximum Number of Graphics Parameter	212
5.12.2	Number of Graphics Parameter	212
5.12.3	Maximum Graphic Size Parameter	212
5.12.4	Available Graphic Memory Parameter	213
5.12.5	Graphic Block Size Parameter	213
5.12.6	Graphics Table Parameter	213
5.12.7	Graphics Bitmap Table Parameter	218
Section 6	Markup Language for Transportation Information (MULTI) [Normative]	224
6.1	Scope	224
6.2	MULTI - Setup and Definition	224

6.2.1	Definition.....	224
6.3	Rules to apply attribute tags	224
6.4	Defined Tags	225
6.4.1	Color Background.....	226
6.4.2	Page Background Color	227
6.4.3	Color Foreground	227
6.4.4	Color Rectangle.....	228
6.4.5	Fields	229
6.4.6	Flash Time.....	231
6.4.7	Font.....	232
6.4.8	Graphic	233
6.4.9	Hexadecimal Character.....	234
6.4.10	Justification—Line	235
6.4.11	Justification—Page.....	236
6.4.12	Manufacturer Specific Tag.....	237
6.4.13	Moving Text Tag.....	237
6.4.14	New Line.....	240
6.4.15	New Page	241
6.4.16	Page Time	241
6.4.17	Spacing – Character.....	242
6.4.18	Text Rectangle	242
Annex A Requirements Traceability Matrix (RTM) [Normative]		245
A.1	Notation [Informative]	245
A.1.1	Functional Requirement Columns.....	245
A.1.2	Dialog Column	245
A.1.3	Object Columns.....	246
A.1.4	Additional Specifications.....	246
A.2	Instructions for Completing the RTM [Informative]	246
A.3	Requirements Traceability Matrix (RTM) Table	246
A.4	Supplemental Requirements Traceability Matrix	279
A.5	MULTI Field Traceability Matrix.....	288
Annex B Object Tree [Informative].....		296
Annex C Test Procedures [Normative]		297
C.1	Purpose	297
C.1.1	Scope.....	297
C.1.2	Keywords.....	297
C.1.3	Keyword Combinations.....	297
C.1.4	Rules for Executing Test Procedures	297
C.2	Testing Requirements.....	298
C.2.1	Field Device Test Environment	298
C.2.2	Test Case Traceability Table.....	298
C.3	Test Procedures	313
C.3.1	Configuration Tests	313
C.3.2	Font Tests.....	323
C.3.3	Graphic Tests	336
C.3.4	Illumination Tests.....	352
C.3.5	Diagnostic Tests	369
C.3.6	MULTI Default Tests.....	428

C.3.7	Sign Control Tests	460
C.3.8	MULTI Tag Tests	498
C.3.9	MULTI Field Tests	562
C.3.10	Scheduling Tests	588
C.3.11	Event Tests	597
C.3.12	Event Log Tests	608
C.3.13	Global Tests	623
C.3.14	Test Procedures	637
Annex D	Documentation of Revisions [Informative]	649
D.1	Changes to section headings	649
D.2	Corrections to the PRL	649
D.3	Conformance Changes	649
D.4	Added New requirements	650
D.5	updated requirements	650
D.6	Updated dialogs	650
D.7	Updated Objects	650
D.8	Added Clarifications to MULTI-agts	651
Annex E	Frequently Asked Questions [Informative]	652
E.1	Does NTCIP 1203 v02 include a feature to automatically blank a sign (or take other action) in the event that the sign becomes illegible due to pixel errors?	652
E.2	Does NTCIP 1203 v02 include a feature to automatically dim an LED sign at a defined high temperature in an attempt to reduce internal heat?	652
E.3	Does NTCIP 1203 v02 include a feature to control multiple physical signs from a single controller?	653
E.4	Does NTCIP 1203 v02 include a testing/training mode whereby a central can operate signs without any messages appearing on the face of the sign?	653
E.5	Does NTCIP 1203 v02 include a feature to control external devices such as HOV lane gates?	653
E.6	Wouldn't it be useful to have an object to report back the version of NTCIP 1203 v02/MIB that is implemented in the device (e.g. DMS)?	653
E.7	Does NTCIP 1203 v02 support the control of Lane Use Signals.	653
E.8	Why is the range of the "brightness output" in the dmsIllumBrightnessValues table 0..65535 instead of 0..dmsIllumNumBrightnessLevels?	653
E.9	What is the correct way to interpolate a brightness table, and why would you do it?	654
E.10	Why does NTCIP 1203 v02 not address NTCIP-specific traps?	654
E.11	Does NTCIP 1203 v02 support the capability to provide moving graphics (similar to moving text or arrows)?	654
E.12	How does NTCIP 1203 v02 address inverted fonts?	655
E.13	In the User Comment Drafts of NTCIP 1203 v02, there was a mechanism to allow triggers to activate actions. In this version, it has been removed. Why?	655
Annex F	ASCII Table and Description [Informative]	656
F.1	Standard ASCII Chart (7 bit = 2 ⁷)	656

F.2	Extended ASCII Codes (8th bit => 2⁸)	656
Annex G SNMP Interface [Normative]		658
G.1	Generic SNMP Get Interface	658
G.2	Generic SNMP Get-Next Interface	659
G.3	Generic SNMP Set Interface	659
G.4	Variable Binding List Structure	660
G.5	Additional Requirements	660
	G.5.1 Grouping of Objects in a Request	660
	G.5.2 Support of Get	660
	G.5.3 Support of Get-Next.....	660
	G.5.4 Support of Set.....	660
	G.5.5 Performance	660
Annex H NTCIP 1201 v03 Derived User Needs, Functional Requirements, and Dialogs [Informative]		662
H.1	Introduction	662
H.2	Derived GLOBAL Functional Requirements	662
	H.2.1 Determine Device Component Information	662
	H.2.2 Manage Time.....	662
	H.2.3 Schedule Device Actions.....	662
	H.2.4 Determine Supported Standards.....	663
	H.2.5 Supplemental Requirements for Scheduling	663
	H.2.6 Supplemental Requirements for Event Monitoring.....	663
	H.2.7 Support a Number of Events to Store in Log.....	664
H.3	Derived GLOBAL Dialogs	664
	H.3.1 Manage Communications Environment	664
	H.3.2 Automatic Reporting of Events (SNMP Traps).....	666
	H.3.3 Determining Device Component Information	666
	H.3.4 Global Time Data.....	666
H.4	External Data Elements	667

FIGURES

Figure 1	View of a Typical DMS System Architecture	21
Figure 2	Configuring a Font	101
Figure 3	Storing a Graphic.....	104
Figure 4	Configuring Light Output Algorithm.....	106
Figure 5	Activating a Message.....	107
Figure 6	Defining a Message	110
Figure 7	Defining a Schedule.....	112
Figure 8	Graphic State Machine	124
Figure 9	Control Mode State Machine	127
Figure 10	Message Table State Machine	129
Figure 11	Object Tree for NTCIP 1203 v03	296
Figure 12	Field Device Test Environment.....	298
Figure 13	SNMP Get Interface.....	658
Figure 14	SNMP GetNext Interface	659
Figure 15	SNMP Set Interface	659
Figure 16	SNMP Interface—View of Participating Classes	660
Figure 17	Global Time Data.....	667

TABLES

Table 1 Relationship between Main User Needs Groups and National ITS Architecture Flows	29
Table 2 Conformance Symbols	31
Table 3 Predicate Notations	32
Table 4 Predicate to NTCIP 1203 v03 Section Mapping	32
Table 5 Support/Project Requirement Column Entries	33
Table 6 MULTI Tags	225
Table 7 Field Descriptions	230
Table 8 Line Justification Codes	235
Table 9 Page Justification Codes	236
Table 10 Requirements to Test Case Traceability Table	299
Table 11 Section Heading Revisions	649

Section 1 General [Informative]

1.1 Scope

NTCIP 1203 v03 specifies the logical interface between Dynamic Message Signs (DMS) and the host systems that control them (commonly referred to as “central” systems). NTCIP 1203 v03 describes the supported DMS functionality in terms of user needs and requirements; however, the nature of the interface is determined in part by the operational nature of the devices being controlled, and therefore NTCIP 1203 v03 touches on such operational issues on occasion.

NTCIP 1203 v03 assumes a model of DMS operation in which DMS controllers possess intelligence, and the data used for message display and sign configuration is resident at the DMS controller. In particular, data elements such as fonts, graphics, message text, time-based schedules, and so forth may reside at the DMS controller, and the controller renders messages on the sign face based on this data (This model is typical of existing DMS applications, and may be contrasted with an alternate model in which, for example, the DMS controller only knows how to display static bitmaps, and all message layout and composition is performed by the central system.). We refer to the DMS controller’s status, control, and configuration data as the “controller database”; NTCIP 1203 v03 specifies interfaces whereby this data can be manipulated by the central system. There are no imperative commands such as “Display a message” or “Report status”; the central system controls the behavior of the DMS purely through queries of and changes to the controller database using a suite of communication protocols appropriate for the underlying communications infrastructure. These communications protocols are defined in the NTCIP 23xx series (Application Layer protocols), NTCIP 22xx series (Transport Layer protocols), and NTCIP 21xx series (Subnetwork Layer protocols).

1.2 References

For approved amendments, contact:

NTCIP Coordinator
National Electrical Manufacturers Association
1300 North 17th Street, Suite 900
Rosslyn, Virginia 22209-3806
e-mail: ntcip@nema.org

For draft amendments of this document, which are under discussion by the relevant NTCIP Working Group, and recommended amendments of the NTCIP Joint Committee, visit the World Wide Web at <http://www.ntcip.org>.

The following standards (normative references) contain provisions which, through reference in this text, constitute provisions of this Standard. Other documents and standards (other references) are referenced in these documents, which might provide a complete understanding of the entire protocol and the relations between all parts of the protocol. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this Standard are encouraged to investigate the possibility of applying the most recent editions of the standards listed below.

1.2.1 Normative References

AASHTO / ITE / NEMA NTCIP 1102 v02	<i>Octet Encoding Rules (OER) Base Protocol</i> published October 2005
AASHTO / ITE / NEMA NTCIP 1103 v02	<i>Transportation Management Protocols (TMP)</i> published July 2010