



ANSI/(NFPA)
T2.13.5-1991 (R2001)
First edition
20 November 1991

AMERICAN NATIONAL STANDARDS INSTITUTE • A NATIONAL STANDARD FOR FLUID POWER

**Hydraulic fluid power – Industrial systems –
Practice for the use of high water content fluids**

SPONSOR



NFPA
*Solutions through
motion technology*

Descriptors: none

AMERICAN NATIONAL STANDARD

This American National Standard is one of more than 10,000 standards approved as American National Standards by the American National Standards Institute. On 24 August 1966, the ASA was reconstituted as the USA Standard Institute; on October 1969, the USASI changed its name to the American National Standards Institute. Standards formerly designated as ASA or USASI are now designated as ANSI Standards. There is no change in their index identification or technical content.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. An American National Standard is intended as a guide to aid the manufacturer, the consumer and the general public. The existence of an American National Standard does not in any respect preclude anyone, whether they have approved the standard or not, from manufacturing, marketing, purchasing or using products, processes or procedures not conforming to the standard. An approved ANSI Standard does not constitute or indicate a warranty of any sort, express or implied, including but not limited to a warranty or representation as to quality, merchantability or fitness for a particular use or purpose. American National Standards are subject to periodic review and users are to obtain the latest editions. Producers of goods made in conformity with an American National Standard are encouraged to state on their own responsibility in advertising, promotional material or on tags or labels that the goods are produced in conformity with particular American National Standards.

NOTICE: An approved ANSI standard does not express or imply any judgment, certification or endorsement of or with respect to, the safety, design or performance of any product, component, or its use.

NFPA does not examine, investigate, test, recommend, or certify the design, use of safety of any product or component, even those which may incorporate one or more ANSI standards. Approved ANSI standards therefore have no application to and do not express or imply any recommendation, representation or warranty, with respect to the safety, design, use, performance, or functional interchangeability of components or products which incorporate ANSI standards.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken to reaffirm, revise, or withdraw this standard no later than five (5) years from the date of publication. Information on this and other FLUID POWER standards may be obtained by calling or writing the National Fluid Power Association, 3333 North Mayfair Road, Milwaukee, WI 53222-3219, (414) 778-3344.

Suggestions for improvement gained in the use of this standard will be welcome. They should be sent to the National Fluid Power Association, 3333 North Mayfair Road, Milwaukee, WI 53222-3219.

Any part of this standard may be quoted. Credit lines should read: Extracted from American National Standard *Hydraulic fluid power — Industrial systems — Practice for the use of high water content fluids*, ANSI/(NFPA)T2.13.5-1991.

Published by
NATIONAL FLUID POWER ASSOCIATION, INC.
Copyright 1991 by the National Fluid Power Association, Inc.
Printed in USA

This is a preview of "ANSI/(NFPA)T2.13.5-1...". [Click here to purchase the full version from the ANSI store.](#)

Foreword

This Foreword is not part of American National Standard *Hydraulic fluid power — Industrial systems — Practice for the use of high water content fluids*, ANSI/(NFPA)T2.13.5-1991.

Many new hydraulic systems are using high water content fluids as the hydraulic media. The personnel who are responsible for designing these systems or maintaining them have limited knowledge in the unique properties of these fluids.

The Fluids Coordinating Committee, T2.13, at its 19 March 1981 meeting recommended that a project be initiated to establish a recommended practice for the conversion to and use of hydraulic fluids which typically contain over 80 % water.

The title, scope and purpose of the project was approved on 13 May 1981 and the number T2.13.5 was assigned to the project.

Draft No. 1 was circulated and reviewed on 27 September 1982. Draft No. 2 was circulated and reviewed at the 14 March 1983 Project Group meeting. Draft No. 3 was circulated and reviewed on 3 October 1983 with the recommendation that Draft No. 3 be submitted to the NFPA Technical Staff to prepare the General Review Draft. Project Group Chairman, Ralph Perez (Lubrizol Corp.), forwarded the Final Working Draft No. 3 to Headquarters on 18 June 1984.

NFPA Technical Staff prepared the General Review Draft on 27 November 1985. Several comments were received on the first general review draft. The document was revised accordingly. At the 16 June 1988 meeting of the Fluids Technology Committee it was recommended that the document be submitted to the NFPA Technical Board for approval to ballot. The Technical Board supported this recommendation at their 15 September 1988 meeting.

The NFPA Headquarters Staff prepared T2.13.5 for Ballot on 18 November 1988. No negative comments were received. On 16 February 1989 T2.13 recommended that the document be submitted to the NFPA Technical Board for final approval.

On 16 March 1989 the NFPA Technical Board voted unanimously to approve the document as an NFPA Recommended Practice.

Project Group Members who developed this recommended practice:

Ralph Perez

Project Chairman
Lubrizol Corp.

Paul Schacht

Technology Committee Chairman
Racine Fluid Power, Inc.

Thelma Marougy

Technology Committee Vice Chairman
Vickers, Inc./TRINNOVA Corp.

John McLain*

Technology Committee Vice Chairman
Caterpillar Inc.

Walter Lewis*

Technology Committee Secretary
Union Carbide Corp.

Bruce McCord

Technical Auditor
Aro Corp.

Shirley C. Seal

Manager of Standards Development –
Industry/National
National Fluid Power Association

Richard Buckley*

Chemtool, Inc.

Lou MacDougall**

Sundstrand Hydro-Transmission Div.

Hy Ratner*

Vickers, Inc.

Joe Ivaska

Tower Oil Technology

Marsha Lester

Edwin Cooper Div./Ethyl

Myron Eberle

Hydro-Component Research

Ed Moronchik

Shell Development

It is intended that upon approval as an NFPA Recommended Practice, this document be forwarded to ANSI for promulgation as an American National Standard.

* Retired.

** Company affiliation has changed.

On 10 November 1989, ANSI/(NFPA)T2.13.5 was submitted to ANSI Committee B93 for ballot. Balloting closed on 23 October 1991 with two negative comments. One of the comments was incorporated into the document and the other negative ballot was changed to approval. ANSI/(NFPA)T2.13.5 was approved by ANSI's Board of Standards review on 20 November 1991. The membership roster of Standards Committee B93 at the time of ballot:

Jack C. McPherson

Chairman

Daniel B Shore

Vice Chairman

Shirley C. Seal

Secretary

American Society of Agricultural Engineers

David L. Newcom

Compressed Air & Gas Institute

David E. Bonn

John Addington (alternate)

Construction Industry Manufacturers Association

Glenn Stewart

Fluid Controls Institute

Jude Pauli

E. C. Rutter (alternate)

Fluid Power Distributors Association, Inc.

Thomas Neff

Fluid Power Society

William Adsit

Berry Ferguson

Robert Firth

Tom Frankenfield

Ray Hanley

Verne L. Middleton

Wayland Tenkku

Vincent Torrusio

Fluid Sealing Association

Alex Pileck

Material Handling Institute

Jack C. McPherson

Jeff Hansell (alternate)

National Fluid Power Association

Richard N. Bailey

Robert Kay

Paul Schacht

William Wilkerson

National Machine Tool Builders' Association

John B. Deam

Company Members

Lloyd L. Schmaltz

Don McGeachy

John Welker (alternate)

Logan Mathis

Individual Members

John Eleftherakis
Zdenek J. Lansky
A. O. Roberts
Daniel B. Shore
William L. Snyder
Jack Walrad
Tom Wanke
James C. White
Frank Yeaple

/leg

Introduction

In hydraulic fluid power systems, power is transmitted and controlled through a liquid under pressure within an enclosed circuit. One class of liquid is the High Water Content Fluids.

Most existing industrial power equipment has been designed to run on petroleum oil. Consequently, conversion to a High Water Content Fluid is not recommended without a thorough evaluation of the system, and the replacement of critical components with those that have been designed to run on fluids which typically contain between 80 % and 98 % water. Therefore, this practice must be read carefully.

ISO 6743/4, Lubricants, industrial oils and related products - (class L) - Classification - Part 4: Family H (Hydraulic systems), has defined two major categories of High Water Content Fluids; Class HFAE for oil-in-water emulsions with water content over 80 % and class HFAS for chemical solutions with water content above 80 %. Hydraulic fluids with water content below 80 % are covered in ANSI standard B93.5M entitled, *Practice for the Use of Fire Resistant Fluids in Industrial Hydraulic Fluid Power Systems*.

As a result of the long term development of this new class of fluids, various designations have received widespread usage. Some of the more common designations for High Water Content Fluid include: 95/5, 5-95, High Water Base Fluid, HWBF, HWCF and High Water Fire Resistant.

Information which is provided in fluid supplier's specification sheets shows that High Water Content Fluids can vary widely in physical and chemical properties, degradability and lubrication values. It is therefore, recommended that before a given fluid is selected, it is matched as closely as possible to the requirements of the intended application and is approved by the component manufacturers.

Since this document presents only generalized recommended practices for the use of High Water Content Fluids, it is suggested that the user consult the component manufacturer for detailed recommendations concerning approved equipment and design limitations as well as the fluid supplier for specific procedures for installing and maintaining the hydraulic media.

Hydraulic fluid power — Industrial systems — Practice for the use of high water content fluids

1 Scope and field of application

This recommended practice provides a general educational publication covering the following aspects of High Water Content Fluids used in hydraulic fluid power systems:

- product description;
- mixing and control of water quality and concentration;
- operating temperature;
- foaming and aeration;
- corrosive properties;
- effects on protective coatings;
- wear resistant characteristics;
- viscosity control;
- fluid stability;
- safety in exposure to fluid;
- spills;
- contamination;
- effects on elastomers;
- piping and accessory precautions;
- changing fluids in a system;
- system design.

This recommended practice will:

- provide a composite reference of pertinent general data, properties and characteristics of the types of High Water Content Fluids considered for use in fluid power systems;
- facilitate the design of industrial fluid power systems that use High Water Content Fluids;
- improve the operation and increase the reliability of fluid power systems using High Water Content Fluids;