



National Fluid Power Association

**ANSI/(NFPA)T3.12.10 R2-2000
(R2005)**

Third edition
15 March 2000

**Air line filter, regulator and/or lubricator – Pressure rating
supplement to NFPA/T2.6.1 R2-2000, Fluid Power components –
Method for verifying the fatigue and establishing the burst
pressure ratings of the pressure containing envelope of a metal
fluid power FRL**

(Revision of NFPA/T3.12.10 R1-1994)

A NATIONAL INDUSTRY STANDARD FOR FLUID POWER

Approved by Committee ASC B93,
accredited by the American National Standards Institute (ANSI)



Descriptors: air line filter regulator and/or lubricator fluid power pneumatic fluid power pressure cyclic test pressure rated fatigue pressure rated burst pressure burst test pressure rating by similarity pressure rating by test pressure rating

Developed and published by

NATIONAL FLUID POWER ASSOCIATION

3333 N. Mayfair Road, Suite 211 • Milwaukee, WI 53222-3219 USA
Phone: +1 414 778-3344 • Fax: +1 414 778 3361 • e-mail: nfpa@nfpa.com

AMERICAN NATIONAL STANDARD

This American National Standard is one of more than 10,000 standards approved as American National Standards by the American National Standards Institute. On 24 August 1966, the ASA was reconstituted as the USA Standard Institute; on October 1969, the USASI changed its name to the American National Standards Institute. Standards formerly designated as ASA or USASI are now designated as ANSI Standards. There is no change in their index identification or technical content.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. An American National Standard is intended as a guide to aid the manufacturer, the consumer and the general public. The existence of an American National Standard does not in any respect preclude anyone, whether they have approved the standard or not, from manufacturing, marketing, purchasing or using products, processes or procedures not conforming to the standard. An approved ANSI Standard does not constitute or indicate a warranty of any sort, express or implied, including but not limited to a warranty or representation as to quality, merchantability or fitness for a particular use or purpose. American National Standards are subject to periodic review and users are to obtain the latest editions. Producers of goods made in conformity with an American National Standard are encouraged to state on their own responsibility in advertising, promotional material or on tags or labels that the goods are produced in conformity with particular American National Standards.

NOTICE: An approved ANSI standard does not express or imply any judgment, certification or endorsement of or with respect to, the safety, design or performance of any product, component, or its use.

NFPA does not examine, investigate, test, recommend, or certify the design, use or safety of any product or component, even those which may incorporate one or more ANSI standards. Approved ANSI standards therefore have no application to and do not express or imply any recommendation, representation or warranty, with respect to the safety, design, use, performance, or functional interchangeability of components or products, which incorporate ANSI standards.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken to reaffirm, revise, or withdraw this standard no later than five (5) years from the date of publication. Information on this and other FLUID POWER standards may be obtained by calling or writing the National Fluid Power Association, 3333 North Mayfair Road, Milwaukee, WI 53222-3219, (414) 778-3344.

Suggestions for improvement gained in the use of this standard will be welcome. They should be sent to the National Fluid Power Association, 3333 North Mayfair Road, Milwaukee, WI 53222-3219.

Any part of this standard may be quoted. Credit lines should read: Extracted from the national industry standard ***Airline filter, regulator and/or lubricator – Pressuring rating supplement to NFPA/T2.6.1 R2-2000, Fluid power components – Method for verifying the fatigue and establishing the burst pressure ratings of the pressure containing envelope of a metal fluid power FRL, ANSI/(NFPA)T3.12.10 R2-2000 (R2005).***

Foreword

This Foreword is not part of NFPA Recommended Standard *Air line filter, regulator and/or lubricator – Pressure rating supplement to NFPA/T2.6.1 R2-2000, Fluid power components – Method for verifying the fatigue and establishing the burst pressure ratings of the pressure containing envelope of a metal fluid power FRL*, NFPA/T3.12.10 R2-2000.

This project was initiated on 11 February 1997 and the TSP was approved on 10 April 1997. The first draft was an update to coordinate the document with the updated NFPA/T2.6.1 R2. Both were issued for general review on 30 December 1998. Comments were reviewed at the T2.6 committee meeting of 9 February 1999, and proposed changes were reviewed by the T3.21 committee at its meeting of 18 May 1999. The ballot draft was prepared by NFPA headquarters on 2 August 1999. There were no negative ballots and the Technical Board granted final approval on 18 November 1999.

Project Group Members who developed this standard:

John Berninger
Project Chairman and T2.6 Chairman
Parker Hannifin Corp.

James Rosenbury
Section Chairman
Ingersoll-Rand Co.

Clifford Allen
Vice Chairman
Lexair Inc.

Paul Schacht
Technical Auditor
Bosch Automation Technology

June M. VanPinsker
Technical Coordinator
National Fluid Power Association

Shirley C. Seal*
Manager of Standards Development –
Industry/National
National Fluid Power Association

Dale Bauer
Rexroth Corp.

Jim Dietvorst
Wilkerson Corp.

John Pousma
NORGREN

* Retired

/jmv

Introduction

In fluid power systems, power is transmitted and controlled through a fluid (liquid or gas) under pressure within an enclosed circuit. During operation, filters, regulators and lubricators (FRLs) in a system may be loaded from internal pressure, gravity, inertia, thermal variations and external forces. The nature of these loads can vary from a single static application, to continuously varying amplitudes, repetitive loadings and even shock.

It is important to know how well FRLs can withstand these loads but this standard addresses only the loading due to internal pressure.

There are many ways in which internal pressure loads are imposed upon FRLs. This standard considers a broad range of waveforms but within prescribed time limits, temperatures, environmental conditions and only upon certain metals. It is anticipated that these limitations could still provide sufficient common ground for comparing products. This rating method, therefore, provides the system designer with certain information to assist in a selection of FRLs for an application. The designer still has the responsibility to consider the other loading characteristics described above and to determine how they might affect FRLs ultimate pressure retaining capability.

There may be other standards in existence for pressure rating FRLs and this standard is not intended to displace them. Furthermore, it is recognized that most FRL products use materials for various parts of the pressure containing envelope that are outside the scope of this standard. However, for those parts that do use applicable materials, this standard provides a fatigue verification method for pressure rating those elements of the product.

This standard serves as a universal "verification test" to give credibility to the many in-house and other methods of determining FRL pressure ratings. The credibility is based upon the fundamental nature of fatigue of metals with its statistical treatment and use of the pressure rating verification theory developed in NFPA/T2.6.1 R2. Nevertheless, design knowledge of the FRL population and its representative samples, including consistency in materials, shapes, fabrication techniques, etc., is necessary to maximize accuracy in the verification method.

This standard describes specific methods for testing FRLs, verifying their fatigue pressure ratings and establishing static burst ratings. It also provided specific means to determine some of the optional parameters.

This standard is a supplement to the basic pressure rating standard, NFPA/T2.6.1 R2. It follows the provisions of that document but is more specific to FRLs. Application of this pressure rating method will require use of both documents.

This version of NFPA/T3.12.10 R2 replaces earlier editions and utilizes the same basic theory. Products rated under the first (1976) edition may not be rated to the same values under this edition. See clause 11 for the differences in rating identification.

Air line filter, regulator and/or lubricator – Pressure rating supplement to NFPA/T2.6.1 R2-2000, Fluid power components – Method for verifying the fatigue and establishing the burst pressure ratings of the pressure containing envelope of a metal fluid power FRL

1 Scope

1.1 This standard provides:

- test and statistical methods for generating fatigue distribution data;
- test and statistical methods for conducting a verification of the pressure ratings on FRLs;
- common requirements and an industry-wide philosophy in judging one type of pressure capability for FRLs;
- uniform methods of product comparison.

1.2 This standard limits conditions as follows:

- constant amplitude, pressure-induced loading of the elements that constitute or maintain the pressure containing envelope;
- product life of at least 100,000 cycles;
- defined conditions for pressure levels and pulse durations;
- temperatures from the charpy impact transition temperature to the threshold of creep sensitivity;
- environments which are chemically compatible with the materials of the pressure containing envelope;
- materials that are aluminum, magnesium, steel, iron, copper based alloys, cobalt, titanium, stainless steels, nickel steels and monel. Specifically excluded are creep sensitive materials such as: zinc, plastic, rubber and sealing devices;
- pressure gauges are specifically excluded.

1.3 This standard encourages manufacturers to use this common method to enhance the credibility of their pressure ratings.