



National Fluid Power Association

**ANSI/(NFPA)T3.6.31 R2-2000
(R2006)**

Third edition
15 March 2000

**Telescopic cylinders and cylinders of nonbolted end construction –
Pressure rating supplement to NFPA/T2.6.1 R2-2000, Fluid power
components – Method for verifying the fatigue and establishing the
burst pressure ratings of the metal pressure containing envelope of
a telescopic and nonbolted end fluid power cylinder**

(Revision of NFPA/T3.6.31-1976)

A NATIONAL INDUSTRY STANDARD FOR FLUID POWER

**Approved by Committee ASC B93,
accredited by the American National Standards Institute (ANSI)**



Descriptors: cylinder element fluid power pressure cyclic test pressure rated fatigue burst analytical methods telescopic nonbolted end.

Developed and published by

NATIONAL FLUID POWER ASSOCIATION

3333 N. Mayfair Road, Suite 211 • Milwaukee, WI 53222-3219 USA
Phone: +1 414 778-3344 • Fax: +1 414 778 3361 • e-mail: nfpa@nfpa.com

AMERICAN NATIONAL STANDARD

This American National Standard is one of more than 10,000 standards approved as American National Standards by the American National Standards Institute. On 24 August 1966, the ASA was reconstituted as the USA Standard Institute; on October 1969, the USASI changed its name to the American National Standards Institute. Standards formerly designated as ASA or USASI are now designated as ANSI Standards. There is no change in their index identification or technical content.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. An American National Standard is intended as a guide to aid the manufacturer, the consumer and the general public. The existence of an American National Standard does not in any respect preclude anyone, whether they have approved the standard or not, from manufacturing, marketing, purchasing or using products, processes or procedures not conforming to the standard. An approved ANSI Standard does not constitute or indicate a warranty of any sort, express or implied, including but not limited to a warranty or representation as to quality, merchantability or fitness for a particular use or purpose. American National Standards are subject to periodic review and users are to obtain the latest editions. Producers of goods made in conformity with an American National Standard are encouraged to state on their own responsibility in advertising, promotional material or on tags or labels that the goods are produced in conformity with particular American National Standards.

NOTICE: An approved ANSI standard does not express or imply any judgment, certification or endorsement of or with respect to, the safety, design or performance of any product, component, or its use.

NFPA does not examine, investigate, test, recommend, or certify the design, use or safety of any product or component, even those which may incorporate one or more ANSI standards. Approved ANSI standards therefore have no application to and do not express or imply any recommendation, representation or warranty, with respect to the safety, design, use, performance, or functional interchangeability of components or products which incorporate ANSI standards.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken to reaffirm, revise, or withdraw this standard no later than five (5) years from the date of publication. Information on this and other FLUID POWER standards may be obtained by calling or writing the National Fluid Power Association, 3333 North Mayfair Road, Milwaukee, WI 53222-3219, (414) 778-3344.

Suggestions for improvement gained in the use of this standard will be welcome. They should be sent to the National Fluid Power Association, 3333 North Mayfair Road, Milwaukee, WI 53222-3219.

Any part of this standard may be quoted. Credit lines should read: Extracted from the national industry standard ***Telescopic cylinders and cylinders of nonbolted end construction – Pressure rating supplement to NFPA/T2.6.1 R2-2000, Fluid power components – Method for verifying the fatigue and establishing the burst pressure ratings of the metal pressure containing envelope of a telescopic and nonbolted end fluid power cylinder, ANSI/(NFPA)T3.6.31 R2-2000 (R2006).***

Published by
NATIONAL FLUID POWER ASSOCIATION, INC.
Copyright 2000 by the National Fluid Power Association, Inc.
Printed in USA

Foreword

This Foreword is not part of National Fluid Power Association Recommended Standard *Telescopic cylinders and cylinders of nonbolted end construction – Pressure rating supplement to NFPA/T2.6.1 R2-2000, Fluid power components – Method for verifying the fatigue and establishing the burst pressure ratings of the metal pressure containing envelope of a telescopic and nonbolted end fluid power cylinder, NFPA/T3.6.31 R2-2000.*

This project was initiated on 11 February 1997. The Technical Board approved the TSP on 10 April 1997. The first draft was an update to coordinate the document with the update of NFPA/T2.6.1 R2. Both were issued for general review on 30 December 1998. Comments were reviewed at the T2.6 committee meeting of 9 February 1999, and proposed changes were reviewed by the T3.21 committee at its meeting of 18 May 1999. NFPA Headquarters prepared the ballot draft on 2 August 1999. One negative ballot was reviewed by the T2.6 committee at its meeting on 22 September 1999 but not resolved. It was overridden by the Technical Board, and the document given final approval, at their meeting of 18 November 1999.

Project Group members who developed this standard:

John Berninger

Project Chairman and T2.6 Chairman
Parker Hannifin

Donald Blackman

Section Chairman
Miller Fluid Power Corp.

Donald Selke*

Section Chairman
The Sheffer Corp.

Thomas Hurley

Section Secretary
Mannesmann Rexroth Corporation

Paul Schacht

Technical Auditor
Bosch Automation Technology

June M. VanPinsker

Technical Coordinator
National Fluid Power Association

Lido Boni

Parker Hannifin Corp.

Matt Boswell

Bosch Automation Technology

Jerry Carlin

Eaton Corp.

Richard Schink

Eaton Corp.

* Retired

/jmv

Introduction

In fluid power systems, power is transmitted and controlled through a fluid (liquid or gas) under pressure within an enclosed circuit. During operation, telescopic and nonbolted end fluid power cylinders in a system may be loaded from internal pressure, gravity, inertia, thermal variations and external forces. The nature of these loads can vary from a single static application, to continuously varying amplitudes, repetitive loadings and even shock.

It is important to know how well a telescopic and nonbolted end fluid power cylinder can withstand these loads but this standard addresses only the loading due to internal pressure.

There are many ways in which internal pressure loads are imposed upon a telescopic and nonbolted end fluid power cylinder. This standard considers a broad range of waveforms but within prescribed time limits, temperatures, environmental conditions and only upon certain metals. It is anticipated that these limitations could still provide sufficient common ground for comparing products. This rating method, therefore, provides the system designer with certain information to assist in a selection of telescopic and nonbolted end fluid power cylinders for an application. The designer still has the responsibility to consider the other loading characteristics described above and to determine how they might affect the cylinder's ultimate pressure retaining capability.

This standard serves as a universal "verification test" to give credibility to the many in-house and other methods of determining telescopic and nonbolted end fluid power cylinders pressure ratings. The credibility is based upon the fundamental nature of fatigue of metals with its statistical treatment and use of the pressure rating verification theory developed in NFPA standard NFPA/T2.6.1 R2. Nevertheless, design knowledge of the component population and its representative samples, including consistency in materials, shapes, fabrication techniques, etc. is necessary to maximize accuracy in the verification method.

The basic pressure rating document, NFPA/T2.6.1 R2, established a group of common requirements intended to provide an industry-wide philosophy and basic standard, providing a rationale for judging a component's ability as a pressure containing envelope. Although the specific applicability of NFPA/T2.6.1 R2 is limited, it immediately established a uniform base for subsequent, more specific proposed NFPA recommended standards for individual fluid power components. This standard implements NFPA/T2.6.1 R2 and specifically applies to telescopic and nonbolted end fluid power cylinders.

The method for verifying the fatigue and establishing the burst pressure ratings of the metal pressure containing envelope of a tie rod or bolted cylinders is covered in a separate document, NFPA/T3.6.29 R2.

This version of NFPA/T3.6.31 R2 replaces earlier editions and utilizes the same basic theory. Products rated under the first (1977) edition may not be rated to the same values under this edition. See 13.1 for the differences in rating identification.

Telescopic cylinders and cylinders of nonbolted end construction – Pressure rating supplement to NFPA/T2.6.1 R2-2000, Fluid power components – Method for verifying the fatigue and establishing the burst pressure ratings of the metal pressure containing envelope of a telescopic and nonbolted end fluid power cylinder

1 Scope

1.1 This standard provides:

- test and statistical methods for generating fatigue distribution data;
- test and statistical methods for conducting a verification of the pressure ratings on telescopic and nonbolted end fluid power cylinders;
- common requirements and an industry-wide philosophy in judging one type of pressure capability for telescopic and nonbolted end fluid power cylinders;
- uniform methods of product comparison.

1.2 Follow NFPA/T2.6.1 R2.

1.3 This standard encourages manufacturers to use this common method to enhance the credibility of their pressure ratings.

2 Normative references

The following standards contain provisions, which, through reference in this text, constitute provisions of this NFPA document. At the time of publication, the editions indicated were valid. All documents are subject to revision, and parties to agreements based on this NFPA document are encouraged to investigate the possibility of applying the most recent editions of the documents indicated below. NFPA maintains registers of currently valid NFPA/ANSI standards.

NFPA/T2.6.1 R2-2000, *Fluid power components – Method for verifying the fatigue and establishing the burst pressure ratings of the pressure containing envelope of a metal fluid power component.*

NFPA/T3.6.29 R2-19xx, *Tie rod or bolted cylinder pressure rating supplement to NFPA/T2.6.1 R2-19xx, Fluid power systems and products – Method for verifying the fatigue and establishing the burst pressure ratings of the metal pressure containing envelope of a tie rod or bolted cylinder.*

ANSI/B93.8-1968, *Bore and rod size combinations and rod end configurations for cataloged square head industrial fluid power cylinders.*

ASTM E466-1996, *Standard Practice for Conducting Force Controlled Constant Amplitude Axial Fatigue Tests of Metallic Materials.*

ISO 1000-1992, *SI units and recommendations for the use of their multiples and of certain other units.*