



ANSI/(NFPA)
T3.6.59-1993 (R2001)
First edition
22 March 1993

AMERICAN NATIONAL STANDARDS INSTITUTE • A NATIONAL STANDARD FOR FLUID POWER

Hydraulic fluid power – Cylinders – Cushion performance

SPONSOR



NFPA
*Solutions through
motion technology*

AMERICAN NATIONAL STANDARD

This American National Standard is one of more than 10,000 standards approved as American National Standards by the American National Standards Institute. On 24 August 1966, the ASA was reconstituted as the USA Standard Institute; on October 1969, the USASI changed its name to the American National Standards Institute. Standards formerly designated as ASA or USASI are now designated as ANSI Standards. There is no change in their index identification or technical content.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. An American National Standard is intended as a guide to aid the manufacturer, the consumer and the general public. The existence of an American National Standard does not in any respect preclude anyone, whether they have approved the standard or not, from manufacturing, marketing, purchasing or using products, processes or procedures not conforming to the standard. An approved ANSI Standard does not constitute or indicate a warranty of any sort, express or implied, including but not limited to a warranty or representation as to quality, merchantability or fitness for a particular use or purpose. American National Standards are subject to periodic review and users are to obtain the latest editions. Producers of goods made in conformity with an American National Standard are encouraged to state on their own responsibility in advertising, promotional material or on tags or labels that the goods are produced in conformity with particular American National Standards.

NOTICE: An approved ANSI standard does not express or imply any judgment, certification or endorsement of or with respect to, the safety, design or performance of any product, component, or its use.

NFPA does not examine, investigate, test, recommend, or certify the design, use or safety of any product or component, even those which may incorporate one or more ANSI standards. Approved ANSI standards therefore have no application to and do not express or imply any recommendation, representation or warranty, with respect to the safety, design, use, performance, or functional interchangeability of components or products which incorporate ANSI standards.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken to reaffirm, revise, or withdraw this standard no later than five (5) years from the date of publication. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute, 11 West 42nd Street, 13th Floor, New York, NY 10036-8002, (212) 642-4900. Information on this and other FLUID POWER standards may also be obtained by calling or writing the National Fluid Power Association, 3333 North Mayfair Road, Milwaukee, WI 53222-3219, (414) 778-3363.

Suggestions for improvement gained in the use of this standard will be welcome. They should be sent to the American National Standards Institute, 11 West 42nd Street, 13th Floor, New York, NY 10036-8002.

Any part of this standard may be quoted. Credit lines should read: Extracted from American National Standard Hydraulic fluid power — Cylinders — Cushion performance, ANSI/(NFPA)T3.6.59-1993.

Published by
NATIONAL FLUID POWER ASSOCIATION, INC.
Copyright 1993 by the National Fluid Power Association, Inc.
Printed in USA

Foreword

This foreword is not part of American National Standard Hydraulic fluid power — Cylinders — Cushion performance, ANSI/(NFPA)T3.6.59-1993.

At the 16 March 1988 meeting of the Cylinder Section (T3.6) it was recommended that a document be initiated dealing with cushion performance. John Harding (Hydro-Line Mfg.) agreed to serve as project chairman. On 17 May 1989 a TSP was presented to the Cylinder Section for their approval. It was recommended by the section to alter the abbreviated title to "Hydraulic Cylinder Cushion Performance" and the word "performance" in the Purpose section be replaced by "suitability". The Cylinder Section approved the revised TSP and recommended that it be submitted to the NFPA Technical Board for approval. On 15 June 1989 the Technical Board concurred with the Cylinder Section and granted approval of the TSP.

At the 16 August 1989 meeting of the Cylinder Section, John Harding resigned as project chairman. Richard Schink (Hydro-Line Mfg.) agreed to serve as project chairman.

On 15 November 1989 Chairman Schink (Miller Fluid Power Corp., company affiliation has changed) reported that the project was progressing well. A working draft was prepared and discussed by the project group on 21 March 1990. It was recommended that the document be submitted to NFPA headquarters for processing. This draft will be submitted to the Cylinder Section for discussion at their 22 August 1990 meeting. If approved by the Section it will be submitted for general review.

On 22 August 1990 the Cylinder Section concurred with the project group's recommendation to submit the document for general review. NFPA's Technical Staff prepared the document for General Review on 19 October 1990.

The General Review closed with comments from two companies. These editorial changes were incorporated into the document. At the 13 November 1991 meeting, T3.6 agreed to send the document to the Technical Board for approval to ballot.

The Technical Board met on 16 January 1992 and approved T3.6.59 for ballot. NFPA Headquarters prepared the document for ballot and it was sent out 29 January 1992.

The ballot closed 10 March 1992 with two negatives. Project Chairman Schink (Vickers, Inc., company affiliation has changed) discussed the negative comments with both commentators and made minor changes to the document. Both negatives were changed to approvals by 4 June 1992.

The Technical Board granted final approval on 17 September 1992.

Project Group members who developed this standard:

Richard Schink
Project Chairman
Vickers, Inc.

Donald Selke
Section Chairman
The Sheffer Corp.

Paul Gies
Section Vice Chairman
Vickers, Inc./T-J Division

E. Wayne Hays
Section Secretary
Bimba Manufacturing Co.

David Prevallet
Technical Auditor
Dana Corp.

Linda E. Gasso
Technical Coordinator
National Fluid Power Association

Shirley C. Seal
Manager of Standards Development
Industry/National
National Fluid Power Association

Lido Boni
Parker Hannifin Corp.

Eric Johnston*
S-P Manufacturing

Gregory Pesch
Hanna Corp.

*Company affiliation has changed

On 16 October 1992, ANSI/(NFPA)T3.6.59 was submitted to ANSI Committee B93 for Ballot. Balloting closed on 21 December 1992 with no negative comments.

ANSI/(NFPA)T3.6.59 was approved by ANSI's Board of Standards Review on 22 March 1993.

The membership roster of Standards Committee B93 at the time of ballot:

Jack C. McPherson
Chairman

Daniel B. Shore
Vice Chairman

Shirley C. Seal
Secretary

American Society of Agricultural Engineers
David L. Newcom

Compressed Air & Gas Institute
David E. Bonn
John Addington (alternate)

Fluid Controls Institute
Jude Pauli
E. C. Rutter (alternate)

Fluid Power Distributors Association, Inc.
Thomas Neff

Fluid Power Society
William Adsit
Probir K. Chatterjea
Art DesMarais III
Greg Gordon
Ray Hanley
Bernard Larson
Jim Morgan (alternate)
Paul Prass
N. Pliny Smith
James J. Staczek

Material Handling Institute
Jack C. McPherson

National Fluid Power Association
Bruce McCord
David Prevallet
Paul Schacht
William Wilkerson

National Machine Tool Builders' Association
John B. Deam

US Department of Defense
Wayne K. Wilcox

Company Members
Don McGeachy
John Welker (alternate)
Logan Mathis

Individual Members
John Eleftherakis
William Jones
Zdenek J. Lansky
A. O. Roberts
Daniel B. Shore
William L. Snyder
Vince Torrusio
Jack Walrad
Tom Wanke
James C. White
Frank Yeaple

/leg

Hydraulic fluid power — Cylinders — Cushion performance

0 Introduction

In hydraulic fluid power systems, power is transmitted and controlled through a liquid under pressure within an enclosed circuit.

Standardization of presentation of cushion information will allow users to better apply cylinders and compare various company's products. This standard would be used by individual manufacturers to establish cushion capabilities if the stated assumptions are taken into account.

1 Scope

1.1 This standard defines maximum energy absorption guidelines for ANSI/B93.15.

1.2 This standard will develop a method of presenting hydraulic cushion suitability.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this ANSI document. At the time of publication, the editions indicated were valid. All documents are subject to revision, and parties to agreements based on this ANSI document are encouraged to investigate the possibility of applying the most recent editions of the documents indicated below. NFPA maintain registers of currently valid NFPA/ANSI standards.

ANSI/B93.2-1986, *Fluid power systems and products - Glossary*.

ANSI/B93.15-1981, *Fluid power systems and products - Square head industrial cylinders - Mounting dimensions*.

3 Terms

For definition of terms used, see ANSI/B93.2.

4 Key assumptions and limitations

These assumptions provide either ideal or arbitrary parameters for determining maximum cushion performance. Actual performance may be different than determined by these methods if assumptions are not maintained. The efficiency factors may also vary with application differences.

- 4.1** Maximum cushion pressure is 150% of rated pressure.
- 4.2** The cushion achieves constant deceleration - pressure is constant for the length of the cushion plunger.
- 4.3** The upper limit of velocity is 18 in/sec.
- 4.4** If velocity is below 4 in/sec the cushions become ineffective on smaller sizes.
- 4.5** Friction force is zero.
- 4.6** The cylinder is used in a linear system - not for rotary applications.
- 4.7** Fluid viscosity is equivalent to 25 centistokes.
- 4.8** Drive pressure is equal to the system relief valve setting.
- 4.9** Cushion adjustment screws may be provided to tune cushion performance within limits.
- 4.10** Each manufacturer is to adjust the reported energy absorbing potential of his own product with an efficiency factor to reflect characteristics of their cushion design compared to ideal cushion performance.