



NFPA
Solutions through motion technology

NFPA Recommended Standard

NFPA/T3.20.15-1990

First edition
13 September 1990

AN INDUSTRY STANDARD FOR FLUID POWER

**Hydraulic fluid power — Quick-action coupling —
Flush face type**

Descriptors: coupling, Hydraulic Tool Manufacturers Association (HTMA), coupling, flush face, quick-action coupling, hydraulic tool coupling

PUBLISHED BY

NATIONAL FLUID POWER ASSOCIATION

3333 N. MAYFAIR ROAD / MILWAUKEE, WI 53222-3219 USA

PHONE: +1 414 778 3344 / FAX: +1 414 778 3361 / E-MAIL: NFPA@NFPA.COM

Copyright 1990 by the

NATIONAL FLUID POWER ASSOCIATION, INC.

Printed in the USA

All technical reports, citations, references and related data including standards and practices approved and/or recommended are advisory only. Use thereof by anyone for any purpose is entirely voluntary and in any event without risk of any nature to the National Fluid Power Association, Inc., its officers, directors or authors of such work. There is no agreement by or between anyone to adhere to any NFPA Recommended Standard, policy or practice, and related matters. In formulating and approving technical reports, the Technical Board, its councils and committees and/or the National Fluid Power Association, Inc. will not investigate or consider citations, references or patents which may or may not apply to such subject matter since prospective users of such reports and data alone are responsible for establishing necessary safeguards in connection with utilization of such matters, including technical data, proprietary rights or patentable materials.

Recommended standards and/or policies and procedures are subject to periodic review and may be changed without notice. Recommended standards, after publication, may be revised or withdrawn at any time and current information on all approved recommended standards may be received by calling or writing the National Fluid Power Association, Inc.

An approved NFPA Recommended Standard implies a consensus of those substantially concerned with its scope and provisions and is intended as a guide to aid the manufacturer, the consumer and the general public. The publication of the NFPA Recommended Standard does not in any respect preclude anyone, whether they have participated in the development of or approved the recommended standard or not, from manufacturing, marketing, purchasing, or using of products, processes or procedures not conforming to the recommended standard. An approved NFPA Recommended Standard does not constitute or indicate a warranty of any sort, express or implied, including but not limited to a warranty or representation as to quality, merchantability or fitness for a particular use or purpose.

Participation by federal agency representative(s) or person(s) affiliated with the industry is not to be interpreted as government or industry endorsement of this standard and/or policy and procedure.

NOTICE

An approved NFPA recommended standard does not express or imply any judgment, certification or endorsement of or with respect to, the safety, design or performance of any product, component, or its use.

NFPA does not examine, investigate, test, recommend, or certify the design, use or safety of any product or component, even those which may incorporate one or more NFPA recommended standards. Approved NFPA recommended standards therefore have no application to and do not express or imply any recommendation, representation or warranty, with respect to the safety, design, use, performance, or functional interchangeability of components or products which incorporate NFPA recommended standards

This publication may not be reproduced in whole or in part without the written permission of the National Fluid Power Association, Inc.

Printed by
NATIONAL FLUID POWER ASSOCIATION
3333 North Mayfair Road
Milwaukee, WI 53222-3219

Foreword

This Foreword is not part of National Fluid Power Association Recommended Standard Hydraulic fluid power — Quick-action coupling — Flush face type, NFPA/T3.20.15-1990.

NFPA T3.20.15 Hydraulic fluid power — Quick action coupling for tool applications project work was initiated in October 1983, per request of the Hydraulic Tool Manufacturers Association (HTMA). The NFPA T3.20 Section approved the title scope and purpose (TSP) of the project at their 20 April 1984 meeting. The NFPA Technical Board approved the TSP at their 17 May 1984 meeting.

A rough draft which included HTMA requirements was reviewed by the T3.20 Section at their 2 October 1984, and 5 March 1985 meetings.

Draft No. 3 and proposed revisions were reviewed at the 18 March 1986 meeting following comments from HTMA.

Draft No. 4 reviewed at 30 September 1986 meeting again following comments from HTMA.

Following the 30 November 1986 HTMA meeting at E.H. Wash's Co. in Chicago, Draft No. 5 was revised to conform to HTMA requests.

Following an HTMA meeting in Portland on 4 September 1987, in which representatives from Stanley, Fairmont, Bruning, Hansen and Aeroquip were present, Draft No. 6 was revised to include connect under pressure, disconnect under flow and stencil requirements.

Draft No. 7 was submitted to committee members and reviewed. Corrections were made to an abbreviation on page 7 of 9 ("GMP" to "GPM") and the illustration of figure 2 (deleted a line through the blocked portion of the control valve).

At the 15 March 1988 meeting of T3.20, it was recommended that this project be submitted for General Review. NFPA Technical Staff prepared the document for general review on 27 May 1988.

After the resolution of negative comments, on 14 February 1989 T3.20 recommended that the document be forwarded to the NFPA Technical Board for approval to Ballot.

NFPA Technical Board granted approval to Ballot on 16 March 1989. Headquarters prepared the Ballot Draft on 5 May 1989.

The ballot closed with several comments which, where appropriate, were incorporated into the standard. The Quick-Action Couplings Section, T3.20, was balloted for their approval to submit T3.20.15 to the NFPA Technical Board for final approval. The ballot was favorable. On 13 September 1990 the Technical Board granted final approval to this standard.

Project Group Members who developed this standard:

Pete Straman

Project Group Chairman and
Section Secretary
Aeroquip Corp./TRINOVA Corp.

Greg Haunhorst

Project Co-Chairman
Aeroquip Corp./TRINOVA Corp.

Edward Saloum

Section Chairman
Snap-Tite, Inc.

Ken Koch

Section Vice Chairman
Imperial Clevite/Bruning Hydraulic

James Goss

Technical Auditor
Hagglunds Denison

Shirley C. Seal

Manager of Standards Development-Industry/National
National Fluid Power Association

Eugene Herzan

Parker Hannifin Corp.

Thomas Karcher

The Hansen Mfg. Co.

R. Kalls

Parker Hannifin Corp.

Hydraulic fluid power — Quick-action coupling — Flush face type

0 Introduction

In hydraulic fluid power systems, power is transmitted and controlled through a liquid under pressure within an enclosed circuit. Quick-action couplings are used to quickly join or separate fluid conducting lines without the use of tools or special devices.

1 Scope and field of application

1.1 To include dimensions and performance requirements of a flush face valved coupling with both connected and disconnected sealing capabilities.

1.2 This Standard defines dimensional interchange only and does not guarantee functional interchange.

1.3 Series "A" is intended for medium duty service, i.e., hand tools and rigid mountings. Series "B" is intended for heavy duty service, i.e., hose lines and other areas subject to abuse or rough handling.

1.4 To promote interchangeability of quick-action coupling halves of the same rating.

1.5 To discourage interchangeability of quick-action coupling halves of different ratings.

2 References

ANSI/B93.2-1986, *Fluid power systems and products — Glossary*.

NFPA/T3.20.1 R1-1989, *Fluid power systems — Quick-action couplings — Glossary*.

NFPA/T2.10.1M-1978 (R1986), *Metric Units for Fluid Power Applications*.

ANSI/(NFPA)T3.20.2 R2-1991, *Hydraulic fluid power - Quick-action coupling - Test method (revision and redesignation of ANSI/B93.42-1977)*.

NFPA/T2.6.1 R1-1991, *Fluid power systems and products - Method for verifying the fatigue and establishing the burst pressure ratings of the pressure containing envelope of a metal fluid power component*.

3 Terms and definitions

For definitions of terms used, see ANSI/B93.2 and NFPA/T3.20.1 R1.

4 Units of measurement

4.1 Units of measurement are used in accordance with 73 NFPA/T2.10.1M. This document agrees with ISO 1000.

4.2 Approximate conversions to customary U.S. units are shown in parentheses after their metric counterparts and are made in accordance with NFPA/T2.10.1M.

5 Requirements

5.1 Rated pressure and rated flow are shown in table 1.

5.2 Verify rated operating pressure by impulse testing in accordance with ANSI/(NFPA)T3.20.2 R2 for 150,000 cycles.

5.3 Verify rated static pressure by static pressure testing in accordance with NFPA/T2.6.1 R1 for one cycle.