This is a preview of "NFPA/T2.13.7 R1-1997...". Click here to purchase the full version from the ANSI store.



# NFPA Recommended Standard NFPA/T2.13.7 R1-1997 (R2019)

Second edition 12 June 1997

# Hydraulic fluid power – Petroleum fluids – Prediction of bulk moduli

(Revision and redesignation of ANSI/B93.63-1984) Reaffirmed 2019

**Descriptors:** hydraulic fluid power petroleum products liquids mineral oils hydrocarbons physical properties compressibility bulk modulus computation

Developed and published by

NATIONAL FLUID POWER ASSOCIATION, INC.

6737 W. Washington St., Suite 2350 • Milwaukee, WI 53214 USA Phone: +1 414 778-3344 • Fax: +1 414 778 3361 • e-mail: nfpa@nfpa.com

## Copyright 2005 by the **NATIONAL FLUID POWER ASSOCIATION** Printed in the USA

All standards, recommended practices, information reports, and bibliographies (collectively, "NFPA Documents") are advisory only. Use thereof by anyone for any purpose is entirely voluntary and in any event without risk of any nature to the National Fluid Power Association (NFPA), its officers, directors or authors of such work. There is no agreement by or between anyone to adhere to any NFPA Document. In formulating and approving NFPA Documents, NFPA and/or its councils and committees will not investigate or consider citations, references or patents which may or may not apply to such subject matter since prospective users of such NFPA Documents alone are responsible for establishing necessary safeguards in connection with utilization of such matters, including technical data, proprietary rights or patentable materials.

The information and data contained in NFPA Documents has been obtained from sources believed to be reliable. However, it should not be assumed that all acceptable or applicable sources of information, procedures, methods or techniques are contained in NFPA Documents, or that additional measures may not be required under certain circumstances or conditions.

NFPA Documents and/or policies and procedures are subject to periodic review and may be changed without notice. NFPA Documents are only current as of their publication date. NFPA Documents, after publication, may be revised or withdrawn at any time and current information on all NFPA Documents may be received by calling or writing NFPA. Additionally, the various codes and regulations referenced in NFPA Documents may be amended from time to time and it should not be assumed that the versions referenced therein are the most current versions of such codes and regulations. Please consult the appropriate regulatory authorities for the most up-to-date versions.

NFPA Documents imply a consensus of those substantially concerned with their scope and provisions and are intended as a guide to aid the manufacturer, the consumer and the general public. The publication of NFPA Documents does not in any respect preclude anyone, whether they have participated in the development of or approved such NFPA Documents or not, from manufacturing, marketing, purchasing, or using of products, processes or procedures not conforming to the NFPA Documents. NFPA Documents do not constitute or indicate a warranty of any sort, express or implied, including but not limited to a warranty or representation as to quality, merchantability or fitness for a particular use or purpose.

Participation by federal agency representative(s) or person(s) affiliated with the industry is not to be interpreted as government or industry endorsement of an NFPA Document(s).

## NOTICE

NFPA Documents do not express or imply any judgment, certification or endorsement of or with respect to, the safety, design or performance of any product, component, or its use.

NFPA does not examine, investigate, test, recommend, or certify the design, use or safety of any product or component, even those which may incorporate one or more NFPA Documents. NFPA Documents therefore have no application to and do not express or imply any recommendation, representation or warranty, with respect to the safety, design, use, performance, or functional interchangeability of components or products which incorporate NFPA Documents.

This publication may not, in whole or in part, be reproduced, copied or disseminated, entered into or stored in a computer database or retrieval system, or otherwise utilized without the prior written permission of NFPA.

This is a preview of "NFPA/T2.13.7 R1-1997...". Click here to purchase the full version from the ANSI store.

# Foreword

This Foreword is not part of

Hydraulic fluid power — Petroleum flluids — Prediction of bulk moduli, (NFPA)/T2.13.7 R1-1997, (Revision and redesignation of ANSI/B93.63M-1984)

At the 9 February 1995 T2.13 meeting, Chairman Paul Schacht recommended that ANSI/B93.63M be revised. At the 25 May 1995 T2.13 meeting, Chairman Schacht agreed to serve as Project Chairman for this document and began revising the document.

The Technical Board approved the TSP at the 17 August 1995 meeting. At the 21 September 1995 T2.13 meeting, additional changes to the document were discussed. At the 13 February 1996 T2.13 meeting Draft No. 1 was reviewed and approved for General Review.

The document was sent out for General Review on 10 April 1996. The General Review closed with comments from two companies. At the 19 August 1996 Technical Board meeting this document was granted approval to be sent out for Ballot. The document was updated at Headquarters on 20 August 1996 and sent to Project Chairman Schacht to complete. The revised draft was received at Headquarters on 26 August 1996.

The document was sent out for Ballot on 27 August 1996. Balloting closed with no negative votes. This document was granted final approval at the 5 December 1996 Technical Board Meeting.

Project Group members who developed this standard:

#### Paul Schacht

Project Chairman and Technology Committee Chairman Robert Bosch Fluid Power

Theima Marougy Technology Committee Vice Chairman Aeroquip-Vickers, Inc.

Paul Michael Technology Committee Secretary Benz Oil

Jerry Carlin Technical Auditor Eaton Corp.

Jean M. Flesch Technical Coordinator National Fluid Power Association Shirley C. Seal Manager of Standards Development -Industry/National National Fluid Power Association This is a preview of "NFPA/T2.13.7 R1-1997...". Click here to purchase the full version from the ANSI store.

## NFPA/T2.13.7 R1-1997 (R2009)

# Hydraulic fluid power — Petroleum fluids — Prediction of bulk moduli

#### 0 Introduction

In hydraulic fluid power systems, power is transmitted and controlled through a liquid under pressure in an enclosed circuit. Bulk modulus measures the fluid's resistance to volume reduction by pressure.

#### 1 Scope

1.1 This standard specifies a procedure for predicting the bulk moduli of petroleum or hydrocarbon oils used as fluids (in the absence of air bubbles) in hydraulic fluid power systems and for other purposes.

**1.2** This standard provides graphical techniques to obtain moduli of these fluids without extended calculations and with such accuracy as would be required for the practical calculation of hydraulic system parameters.

**1.3** The useful temperature range is from 0  $^{\circ}$ C to 270  $^{\circ}$ C, with a pressure range from atmospheric to 700,000 kPa (7,000 bar).<sup>1)</sup>

1.4 Select the appropriate bulk modulus according to the problem and conditions of operation (see definitions).

1.5 Refer to annex A for range of measurement.

1.6 Refer to annex B for sample calculations.

### 2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this document. At the time of publication, the editions indicated were valid. All documents are subject to revision, and parties to agreements based on this document are encouraged to investigate the possibility of applying the most recent editions of the documents indicated below. NFPA maintains registers of currently valid NFPA standards.

ISO 91/1 Petroleum measurement tables — Part 1:Tables based on reference temperature of 15 degrees C and 60 degrees F.

ISO 3675 Crude petroleum and liquid petroleum products — Laboratory determination of density or relative density — Hydrometer method.

ISO 3838 Crude petroleum and liquid or solid petroleum products — Determination of density or relative cansity — Capillary-stopped pyknometer and graduated bicapillary pyknometer methods.

ANSI/B93.2 Fluid power systems and products — Glossary.

#### 3 Definitions

For definitions of terms not listed below, see ANSI/B93.2.

3.1 bulk modulus: The measure of resistance to compressibility of a fluid. It is the reciprocal of the compressibility.

3.2 isothermal bulk modulus: Modulus data based on equilibrium conditions and constant temperature.

3.3 isothermal secant bulk modulus (B<sub>T</sub>): The bulk modulus, resulting from pressure change from atmospheric to the pressure of interest.

$$B_{T} = -V_{o} [(p-p_{o})/(V_{o}-V)]_{T}$$

<sup>&</sup>lt;sup>1)</sup> 1 Pa = 1 N/m<sup>2</sup>; 1 bar = 100 kPa ≈ 14.5 lbf/in<sup>2</sup>