



**NFPA/T3.6.54 R1-1997 (R2019)**  
Second edition  
22 July 1997

---

AN INDUSTRY STANDARD FOR FLUID POWER

**Hydraulic fluid power – Cylinders ports –  
SAE straight thread O-ring and four-bolt flange ports –  
ISO straight thread O-ring and four-bolt flange ports –  
Heavy duty and light duty square head tie rod  
cylinders**

**(Revision and redesignation of ANSI/B93.75M-1987, R1-1997)  
Reaffirmed 2019**

Descriptors: fluid power, industrial hydraulic fluid power cylinder, port sizes, square head cylinder, straight thread cylinder, four-bolt flange

---

published by

**NATIONAL FLUID POWER ASSOCIATION, INC.**

6737 W. Washington St., Suite 2350 / Milwaukee, WI 53214 USA  
PHONE: +1 414 778 3344 / FAX: +1 414 778 3361 / E-mail: [nfpa@nfpa.com](mailto:nfpa@nfpa.com)

Copyright 2002 by the  
**NATIONAL FLUID POWER ASSOCIATION**  
Printed in the USA

All standards, recommended practices, information reports, and bibliographies (collectively, "NFPA Documents") are advisory only. Use thereof by anyone for any purpose is entirely voluntary and in any event without risk of any nature to the National Fluid Power Association (NFPA), its officers, directors or authors of such work. There is no agreement by or between anyone to adhere to any NFPA Document. In formulating and approving NFPA Documents, NFPA and/or its councils and committees will not investigate or consider citations, references or patents which may or may not apply to such subject matter since prospective users of such NFPA Documents alone are responsible for establishing necessary safeguards in connection with utilization of such matters, including technical data, proprietary rights or patentable materials.

The information and data contained in NFPA Documents has been obtained from sources believed to be reliable. However, it should not be assumed that all acceptable or applicable sources of information, procedures, methods or techniques are contained in NFPA Documents, or that additional measures may not be required under certain circumstances or conditions.

NFPA Documents and/or policies and procedures are subject to periodic review and may be changed without notice. NFPA Documents are only current as of their publication date. NFPA Documents, after publication, may be revised or withdrawn at any time and current information on all NFPA Documents may be received by calling or writing NFPA. Additionally, the various codes and regulations referenced in NFPA Documents may be amended from time to time and it should not be assumed that the versions referenced therein are the most current versions of such codes and regulations. Please consult the appropriate regulatory authorities for the most up-to-date versions.

NFPA Documents imply a consensus of those substantially concerned with their scope and provisions and are intended as a guide to aid the manufacturer, the consumer and the general public. The publication of NFPA Documents does not in any respect preclude anyone, whether they have participated in the development of or approved such NFPA Documents or not, from manufacturing, marketing, purchasing, or using of products, processes or procedures not conforming to the NFPA Documents. NFPA Documents do not constitute or indicate a warranty of any sort, express or implied, including but not limited to a warranty or representation as to quality, merchantability or fitness for a particular use or purpose.

Participation by federal agency representative(s) or person(s) affiliated with the industry is not to be interpreted as government or industry endorsement of an NFPA Document(s).

#### **NOTICE**

NFPA Documents do not express or imply any judgment, certification or endorsement of or with respect to, the safety, design or performance of any product, component, or its use.

NFPA does not examine, investigate, test, recommend, or certify the design, use or safety of any product or component, even those which may incorporate one or more NFPA Documents. NFPA Documents therefore have no application to and do not express or imply any recommendation, representation or warranty, with respect to the safety, design, use, performance, or functional interchangeability of components or products which incorporate NFPA Documents.

This publication may not, in whole or in part, be reproduced, copied or disseminated, entered into or stored in a computer database or retrieval system, or otherwise utilized without the prior written permission of NFPA.

## Foreword

This Foreword is not part of *Hydraulic fluid power — Cylinder ports — SAE straight thread O-ring and four-bolt flange ports — ISO straight thread O-ring and four-bolt flange ports — Heavy duty and light duty cylinders*, (NFPA)T3.6.54 R1-1997 (Revision of ANSI/B93.75M-1987).

At the T3.6 Cylinders meeting on 24 March 1993 it was decided to update this documents reference section. Gregory Pesch (Hanna Corp.) agreed to serve as Project Chairman. All members of T3.6 were included in the Project Group. The TSP was approved by the Technical Board at their 20 May 1993 meeting.

At the T3.6 meeting on 18 August 1993 the Project Group agreed that after the SAE reference number was updated by project Chairman Pesch, the document should be sent out for General Review.

The document was updated and a few minor editorial changes were made. The document was sent out for General Review on 25 October 1993. The General Review closed with comments from four companies.

At the 9 February 1994, T3.6 meeting, the title of the document was changed from *Hydraulic fluid power — Cylinder ports — SAE straight thread O-ring and four-bolt flange ports — Heavy duty and light duty cylinders*. The new title of the document is *Hydraulic fluid power — Cylinder ports — SAE straight thread O-ring and four-bolt flange ports — ISO straight thread O-ring and four-bolt flange ports — Heavy duty and light duty cylinders*.

The Project Group revised the document and at their 21 September 1994 meeting voted to send the document out for Second General Review. The document was sent out for Second General Review on 20 October 1994. The Second General Review closed with comments from two companies. Project Chairman Pesch wrote to the commentators on 9 February 1995 and both signed off by 16 February 1995. Headquarters received the revised document from Project Chairman Pesch on 13 February 1995.

T3.6 met on 8 February 1995 and voted to put this document on the Technical Board agenda for approval to Ballot. This document was approved for Ballot at the 13 April 1995 Technical board meeting.

This document was sent out for Ballot on 17 April 1995. Balloting closed with two negative comments. Both negative commentators asked that the document be changed to metric dimensions. At the 11 April 1996 Technical Board meeting Donald Selke reviewed the history of this document. At the General Review stage it was asked that metric units be added. This is an inch document, however, the committee added the units. At the Ballot stage the committee was asked to delete the original U.S. units. The committee believes that since this is an inch document, the U.S. units should be retained. The Technical Board agreed with the T3.6 Committee and approved the document with the editorial changes from the two commentators to be added.

The updated document was received at Headquarters on 21 March 1997.

Project Group members who developed this standard:

**Lido Boni**  
Project Chairman  
Parker Hannifin Corp.

**Gregory Pesch<sup>†</sup>**  
Project Chairman & Section Secretary  
Hanna Corp.

**Donald Selke**  
Section Chairman  
Sheffer Corp.

**E. Wayne Hays**  
Section Vice Chairman  
Bimba Mfg. Co.

**Paul Schacht**  
Technical Auditor  
Robert Bosch Fluid Power

**Jean M. Flesch**  
Technical Coordinator  
National Fluid Power Association

**Shirley C. Seal**  
Manager of Standards Development  
Industry/National  
National Fluid Power Association

<sup>†</sup> Deceased

This is a preview of "NFPA/T3.6.54 R1-1997...". [Click here to purchase the full version from the ANSI store.](#)

NFPA/T3.6.54 R1-1997 (R2009)

# Hydraulic fluid power — Cylinder ports — SAE straight thread O-ring and four-bolt flange ports — ISO straight thread O-ring and four-bolt flange ports — Heavy duty and light duty square head tie rod cylinders

## 0 Introduction

In fluid power systems, power is transmitted and controlled through a fluid (liquid or gas) under pressure within an enclosed circuit.

One component of such systems is the fluid power cylinder. This is a device which converts power into linear mechanical force and motion. It usually consists of a movable element, such as a piston and piston rod, plunger, or ram operating within a cylindrical bore.

The square head cylinder is a specific design initially developed for industrial (in plant) use. It is manufactured and sold as an interchangeable component by a majority of suppliers. Standardization of O-ring port sizes in this document is further recognition of this interchangeability.

## 1 Scope

**1.1** This standard includes recommended sizes of SAE and ISO straight thread O-ring and four-bolt flange ports in NFPA standard heavy duty and light duty hydraulic cylinders.

**1.2** This standard intends to:

- encourage the use of SAE O-ring sealed ports;
- promote cylinder interchangeability by establishing uniform O-ring port recommendations.

**1.3** This standard only applies to the dimensional criteria of products manufactured in conformance with this standard. It does not apply to their functional characteristics.

## 2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this document. At the time of publication, the editions indicated were valid. All documents are subject to revision, and parties to agreements based on this document are encouraged to investigate the possibility of applying the most recent editions of the documents indicated below. NFPA maintain registers of currently valid NFPA standards.

ANSI/B93.2-1986, *Fluid power systems and products — Glossary.*

(NFPA)T3.6.7 R2-1996, *Fluid power systems and products — Square head industrial cylinders — Mounting dimensions.*

ISO 6149-1-1993, *Connections for fluid power and general use — Ports and stud ends with ISO 261 threads and O-ring sealing — Part 1: Port with O-ring in truncated housing.*

ISO 6162:1994, *Hydraulic fluid power — Four-screw split-flange connections for use at pressures of 2,5 MPa to 40 MPa (25 bar to 400 bar) — Type I metric series and type II inch series.*

SAE J1926-1:1988, *Specification for Straight Thread O-ring Boss Port.*

SAE J846-1989, *Coding System for Identification of Fluid Conductors and Connectors.*

SAE J518-1993, *Hydraulic Flanged Tube, Pipe, and Hose Connections, Four-Bolt Split Flange Type.*